

HD 655 H

Commercial Cold Water Electric High-Pressure Washer









The HD 655 H pressure washer is specially designed for water supply temperatures up to 185° F making it ideally suited for cleaning applications in the food service industry. In addition, the unit is equipped with a food service grade heavy-duty frame and can be paired with an optional stainless steel cart* with oversized pneumatic tires for easy transport. This, along with features such as Kärcher's patented direct-drive pump and the Triple Changeover Nozzle, makes the HD 655 H both rugged and efficient.

Air-cooled, single phase, 4-pole electric motor with overload protection

Patented Kärcher direct-drive three piston axial pump with brass cylinder head and highgrade stainless steel pistons



Low-pressure chemical injection and infinitely variable detergent metering





Ergonomic trigger gun with built-in pressure gauge and automatic shut-off when trigger is released



Heavy-duty cage frame (foodservice grade) with **stainless steel splash protection cover**

Optional cage-type cart with 10' pneumatic tires available (shown above - Part #9.103-551.0)

AVS: Anti-twist system — highpressure hose is pivot-mounted in trigger gun



HD 655 H

Commercial Cold Water Electric High-Pressure Washer

Technical Specs

Part Number

1.902-412.0

Power Supply

110 V / 1~ / 60 Hz / 2.1 HP 4-pole motor / 18.7 A

Operating Pressure

300 - 1450 PSI (Infinitely Variable)

Water Volume

0.6 - 2.2 GPM (Infinitely Variable)

Maximum Water Inlet Temp.

185°F

Machine Weight Without Accessories

48.9 lbs

Machine Dimensions

20" x 14" x 17"

Warranty

2 year limited

Standard Accessories

- Trigger gun with pressure gauge
- Stainless steel wand
- Triple Changeover Nozzle (0° HP pencil jet, 25° HP fan jet, 40° LP chemical injection)
- 50 ft. high-pressure hose with integrated swivel (food service grade)
- Optional hose reel (Part # 9.103-055.0)

* Part #9.103-551.0

