

## Jet Pump, Single Phase

Dripproof, C-Face



**Applications:** Commercial and industrial water pumps and water systems.

**Features:**

- Jet Pump Service Factors
- Double sealed ball bearings, mechanically locked on shaft end
- Capacitor start design for high starting torque
- Fixed CW rotation, viewed opposite shaft end
- Automatic reset thermal protector
- 56C = carbon steel shaft with key, drip cover not included, see Accessories Section
- 56J = 416 stainless steel threaded shaft with slinger, drip cover included
- UL Recognized and CSA Certified

HP	RPM	VOLTS	FRAME	CAT NO.	MODEL NO.	LIST PRICE	MULT. SYMB.	SERVICE FACTOR	F.L. AMPS	APPROX. WGT. LBS.	"C" DIM.	FOOT NOTES
<b>1/3</b>	3600	115/208-230	56C	J025 *	56C34D2111	\$143	F1	1.75	5.6/2.7-2.8	15	10.44	2
	3600	115/208-230	56J	J033 *	56C34D2110	\$151	F1	1.75	5.6/2.7-2.8	8	11.13	2
<b>1/2</b>	3600	115/208-230	56C	J009 *	56C34D2097	\$157	F1	1.6	7.4/3.5-3.7	17	10.69	2
	3600	115/208-230	56J	J034 *	56C34D2096	\$164	F1	1.6	7.4/3.5-3.7	16	11.38	2
<b>3/4</b>	3600	115/208-230	56C	J013 *	56C34D2103	\$184	F1	1.5	9.8/4.8-4.9	19	10.94	2
	3600	115/208-230	56J	J035 *	56C34D2102	\$192	F1	1.5	9.8/4.8-4.9	20	11.63	2
<b>1</b>	3600	115/208-230	56C	J017 *	56C34D1173	\$207	F1	1.4	12.0/6.2-6.0	23	11.94	2
	3600	115/208-230	56J	J036 *	56C34D1172	\$213	F1	1.4	12.0/6.2-6.0	24	12.44	2
<b>1 1/2</b>	3600	115/208-230	56C	J019 *	56B34D2025	\$283	F1	1.3	13.4/7.4-6.7	26	11.97	1
	3600	115/208-230	56J	J037 *	56B34D2024	\$300	F1	1.3	13.4/7.4-6.7	26	12.43	1
<b>2</b>	3600	115/208-230	56C	J021 *	56B34D5325	\$351	F1	1.2	18.2/9.8-9.1	32	11.44	1
	3600	115/208-230	56J	J038 *	56B34D5326	\$368	F1	1.2	18.2/9.8-9.1	33	12.24	1
<b>3</b>	3600	230	56C	J023 *	56B34D5327	\$557	F1	1.15	12.7	38	11.94	1
	3600	230	56J	J039	56B34D5328	\$587	F1	1.15	12.7	37	12.44	1

\* Stock Model

## Jet Pump, Single Phase

Dripproof, 56J C-Face with Rigid Base



**Applications:** Commercial and industrial water pumps and water systems.

**Features:**

- Jet Pump Service Factors
- Double sealed ball bearings, mechanically locked on shaft end
- Capacitor start design for high starting torque
- Fixed CW rotation, viewed opposite shaft end
- Automatic reset thermal protection
- 416 Stainless steel threaded shaft with slinger
- Drip cover included
- UL Recognized and CSA Certified

HP	RPM	VOLTS	FRAME	CAT. NO.	MODEL NO.	LIST PRICE	MULT. SYMB.	SERVICE FACTOR	F.L. AMPS	APPROX. WGT. LBS.	"C" DIM.	FOOT NOTES
<b>1/3</b>	3600	115/208-230	56J	J054 *	56C34D2118	\$155	F1	1.75	5.6/2.7-2.8	15	10.94	2
<b>1/2</b>	3600	115/208-230	56J	J055 *	56C34D2119	\$168	F1	1.6	7.4/3.5-3.7	17	11.19	2
<b>3/4</b>	3600	115/208-230	56J	J056 *	56C34D2120	\$196	F1	1.5	9.8/4.8-4.9	20	11.44	2
<b>1</b>	3600	115/208-230	56J	J057 *	56C34D2121	\$218	F1	1.4	12.0/6.2-6.0	23	12.44	2
<b>1 1/2</b>	3600	115/208-230	56J	J058 *	56B34D2033	\$304	F1	1.3	13.4/7.4-6.7	23	12.43	1
<b>2</b>	3600	115/208-230	56J	J059 *	56B34D5341	\$374	F1	1.2	18.2/9.8-9.1	39	11.94	1

\* Stock Model

**Footnotes:**

- 1 Capacitor Start/Capacitor Run design for reduced amperage
- 2 Capacitor Start Induction Run design

# Jet Pump, Three Phase

Dripproof, C-Face

**Applications:** Commercial and industrial centrifugal or hydraulic pumps, water pumps and water systems. May also be used on industrial compressors requiring NEMA C-Face mount.

- Features:**
- Jet Pump Service Factors
  - Continuous duty
  - Nameplated 60/50 hertz, 190/380 volts at next lower HP
  - Double sealed ball bearings, mechanically locked on shaft end
  - 56C = carbon steel shaft with key
  - 56J = 416 stainless steel threaded shaft with slinger
  - UL Recognized and CSA Certified
  - Drip cover not included, see Accessories section



HP	RPM	VOLTS	FRAME	CAT NO.	MODEL NO.	LIST PRICE	MULT. SYMB.	SERVICE FACTOR	F.L. AMPS	APPROX. WGT. LBS.	"C" DIM.
1/3	3600	208-230/460	56C	P001 *	56T34D5310	\$166	F1	1.75	1.2-1.1/55	19	9.94
	3600	208-230/460	56J	J040 *	56T34D5347	\$166	F1	1.75	1.2-1.1/55	18	10.44
1/2	3600	208-230/460	56C	P002 *	56T34D5311	\$188	F1	1.6	2.1-2.2/1.1	19	10.44
	3600	208-230/460	56J	J041 *	56T34D5348	\$188	F1	1.6	2.1-2.2/1.1	20	10.94
3/4	3600	208-230/460	56C	P003 *	56T34D5312	\$226	F1	1.5	3.0-3.2/1.6	20	10.44
	3600	208-230/460	56J	J042 *	56T34D5349	\$226	F1	1.5	3.0-3.2/1.6	21	10.94
1	3600	208-230/460	56C	P004 *	56T34D5313	\$257	F1	1.4	3.7-3.7/1.85	23	10.44
	3600	208-230/460	56J	J043 *	56T34D5350	\$257	F1	1.4	3.7-3.7/1.85	22	10.94
1 1/2	3600	208-230/460	56C	P005 *	56T34D5314	\$313	F1	1.3	4.9-5.0/2.5	22	10.44
	3600	208-230/460	56J	J044 *	56T34D5351	\$313	F1	1.3	4.9-5.0/2.5	22	10.94
2	3600	208-230/460	56C	P006 *	56T34D5315	\$367	F1	1.2	6.4-6.2/3.1	24	10.44
	3600	208-230/460	56J	J045 *	56T34D5352	\$367	F1	1.2	6.4-6.2/3.1	25	10.94
3	3600	208-230/460	56C	P007 *	56T34D5316	\$412	F1	1.15	8.9-8.4/4.2	34	11.44
	3600	208-230/460	56J	J046 *	56T34D5353	\$412	F1	1.15	8.9-8.4/4.2	31	11.94

★ Stock Model

# Jet Pump, Three Phase

Dripproof, 56J C-Face with Rigid Base

**Applications:** Commercial and industrial centrifugal or hydraulic pumps, water pumps and water systems.

- Features:**
- Jet Pump Service Factors
  - Continuous duty
  - Nameplated 60/50 hertz, 190/380 volts at next lower HP
  - Double sealed ball bearings, mechanically locked on shaft end
  - 416 stainless steel threaded shaft with slinger
  - Drip cover included
  - UL Recognized and CSA Certified



HP	RPM	VOLTS	FRAME	CAT NO.	MODEL NO.	LIST PRICE	MULT. SYMB.	SERVICE FACTOR	F.L. AMPS	APPROX. WGT. LBS.	"C" DIM.
1/3	3600	208-230/460	56J	J047	56T34D5368	\$170	F1	1.75	1.2-1.1/55	21	10.43
1/2	3600	208-230/460	56J	J048 *	56T34D5367	\$192	F1	1.6	2.1-2.2/1.1	21	10.93
3/4	3600	208-230/460	56J	J049 *	56T34D5365	\$230	F1	1.5	3.0-3.2/1.6	22	10.93
1	3600	208-230/460	56J	J050 *	56T34D5366	\$261	F1	1.4	3.7-3.7/1.85	25	10.93
1 1/2	3600	208-230/460	56J	J051 *	56T34D5369	\$317	F1	1.3	4.9-5.0/2.5	29	10.93
2	3600	208-230/460	56J	J052 *	56T34D5370	\$371	F1	1.2	6.4-6.2/3.1	30	10.93
3	3600	208-230/460	56J	J053 *	56T34D5371	\$416	F1	1.15	8.9-8.4/4.2	33	11.93

★ Stock Model

## Jet Pump, Three Phase

Totally Enclosed, 56C C-Face



**Applications:** Commercial and industrial centrifugal or hydraulic pumps, water pumps and water systems. May also be used on industrial compressors requiring NEMA C-Face mount.

- Features:**
- Double sealed ball bearings, mechanically locked on shaft end
  - Continuous duty
  - Nameplated 60/50 hertz, 190/380 volts at next lower HP
  - 1.15 Service Factor
  - UL Recognized, CSA Certified and CE Marked
  - Drip cover not included, see Accessories section

HP	RPM	VOLTS	FRAME	CAT NO.	MODEL NO.	LIST PRICE	MULT. SYMB.	SERVICE FACTOR	F.L. AMPS	APPROX. WGT. LBS.	"C" DIM.	FOOT NOTES
<b>1/3</b>	3600	208-230/460	56C	P101★	56T34T5306	\$192	F1	1.35	1.7-2.0/1.0	19	9.94	N
<b>1/2</b>	3600	208-230/460	56C	P102★	56T34F5321	\$213	F1	1.15	2.1-2.2/1.1	22	11.82	
<b>3/4</b>	3600	208-230/460	56C	P103★	56T34F5322	\$253	F1	1.15	3.0-3.2/1.6	22	11.82	
<b>1</b>	3600	208-230/460	56C	P104★	56T34F5323	\$283	F1	1.15	3.7-3.7/1.85	24	11.82	
<b>1 1/2</b>	3600	208-230/460	56C	P105★	56T34F5324	\$329	F1	1.15	4.6/2.3	25	11.82	
<b>2</b>	3600	208-230/460	56C	P106★	56T34F5325	\$382	F1	1.15	6.0-6.0/3.0	29	12.32	
<b>3</b>	3600	208-230/460	56C	P107★	56T34F5326	\$414	F1	1.15	8.4-7.6/3.8	39	13.32	

★ Stock Model

## Jet Pump, Three Phase

Totally Enclosed, 56J C-Face with Removable Rigid Base



**Applications:** Commercial and industrial centrifugal or hydraulic pumps, water pumps and water systems.

- Features:**
- Double sealed ball bearings, mechanically locked on shaft end
  - Continuous duty
  - Nameplated 60/50 hertz, 190/380 volts at next lower HP
  - 1.15 Service Factor
  - 416 Stainless steel threaded shaft with slinger
  - UL Recognized and CSA Certified
  - CE Marked

HP	RPM	VOLTS	FRAME	CAT NO.	MODEL NO.	LIST PRICE	MULT. SYMB.	SERVICE FACTOR	F.L. AMPS	APPROX. WGT. LBS.	"C" DIM.	FOOT NOTES
<b>1/3</b>	3600	208-230/460	56J	J060	56T34T5308	\$209	F1	1.15	1.7-2.0/1.0	21	10.44	N
<b>1/2</b>	3600	208-230/460	56J	J061★	56T34F5342	\$230	F1	1.15	2.1-2.2/1.1	23	12.32	
<b>3/4</b>	3600	208-230/460	56J	J062★	56T34F5343	\$270	F1	1.15	3.0-3.2/1.6	26	12.32	
<b>1</b>	3600	208-230/460	56J	J063★	56T34F5344	\$300	F1	1.15	3.7-3.7/1.85	27	12.32	
<b>1 1/2</b>	3600	208-230/460	56J	J064★	56T34F5345	\$361	F1	1.15	4.7-4.6/2.3	28	12.32	
<b>2</b>	3600	208-230/460	56J	J065★	56T34F5346	\$414	F1	1.15	6.0-6.0/3.0	32	12.82	
<b>3</b>	3600	208-230/460	56J	J066★	56T34F5347	\$472	F1	1.15	8.4-7.6/3.8	42	13.82	

★ Stock Model

**Footnotes:**

N Totally Enclosed, Non-Ventilated