

## 4 - SOURCE 4 - ZONE WALL MOUNT HUB

### FEATURES:

- Digital Delivery System (DDS)
- 4 Source 110 punch-down inputs
- 4 Zone 110 punch-down outputs
- 4 Source Loop-Thru, expansive capable
- Zone power output for longer distances
- Serial RS-232 control port



**Order: D5SH4**

### General Info:

- Requires D5PS Power Supply
- Requires D5IP Source Input Plate
- Mounting Holes: 6" Width, 4" Height  
(structured wiring enclosed compatible)
- Dimensions: 6.50"W x 1.89"D x 6.80"H

## SINGLE - SOURCE 4 - ZONE WALL MOUNT HUB

### FEATURES:

- DIGI-5 Technology
- Single Source 110 punch-down inputs
- 4 Zone 110 punch-down outputs
- Single Source Loop-Thru, expansive capable
- Zone power output for longer distances
- Serial RS-232 control port



**Order: D5SH**

### General Info:

- ~120V 50/60Hz Power Supply: 240W max.
- Dimensions: 17"W x 14.25"D x 2.41"H
- Optional RM1UKIT rack ears available

## WALL MOUNT POWER SUPPLY

### FEATURES:

- Universal input 90 to 264VAC, 47 to 63Hz
- Incredible efficiency (up to 89%)
- Standard IEC power cord compatible
- Over voltage protection
- Over temperature protection
- Standard IEC power cord compatible
- Use additional D5ERGPS1 to increase keypad distances over 300 feet



**Order: D5PS**

### General Info:

- 24VAC, 8.3A rated
- Intended for Wall Mount hubs
- Mounting Holes: 6" Width, 3" Height (structured wiring enclosure compatible)
- Dimensions: 6.55"W x 1.74"D x 4.50"H

Shipped with International power cords

**Order: D5PSE**

## LOCAL SOURCE INPUT PLATE

### FEATURES:

- Digital coax audio inputs
- Analog Left & Right audio inputs
- Audio input level control
- IR emitter output
- 110 punch-down output



**Order: D5IP**

### General Info:

- Decora style, fits into a single-gang box