

PRE-AMP A/V DISTRIBUTION SYSTEM

The ZPR68-10 is an extremely versatile, rack-mountable Pre-amp A/V distribution system, distributing up to eight source components through six zones. When combined with EXP9 Expansion Modules (see below), the ZPR68-10 can be used to control distribution to up to 24 separate zones. Each zone output can be individually pre-programmed to achieve proper volume and tonal balance to compensate for the speakers and acoustics in each zone. The ZPR68-10 is controllable by either IR or RS232 serial commands through any of Xantech's keypad control systems, including SPLCD Touchpanels, SmartPad3™ Keypads, or WPK Waterproof Keypads.

- Eight-source, six-zone A/V control system, expandable to 24 zones with EXP9 (see below)
- Zone pre-amp outputs allow flexibility to match amplifier power to job requirements
- Controllable via IR or RS232 commands (IR control requires RC68X programmer, not included)
- Rack-mountable (requires RMZPR, not included)

Order: ZPR6810**ZONE EXPANSION CABLE KIT FOR ZPR68-10****Order: EXP1524****RACK MOUNT ADAPTOR FOR ZPR68-10****Order: RMZPR****ZPR68-10 EXPANSION MODULES**

The EXP9 is a nine-zone expansion module designed to work exclusively with the ZPR68-10 Six-Zone Eight-Source Remote Preamp. A single EXP9 expands the ZPR68-10 to a total of 15 zones of control, while two EXP9 units can be used to create 24 zones of control (requires EXP1524 cable, not included).

1 ZONE MODULE	Order: EXP9-1
2 ZONE MODULE	Order: EXP9-2
3 ZONE MODULE	Order: EXP9-3
4 ZONE MODULE	Order: EXP9-4
5 ZONE MODULE	Order: EXP9-5
6 ZONE MODULE	Order: EXP9-6
7 ZONE MODULE	Order: EXP9-7
8 ZONE MODULE	Order: EXP9-8
9 ZONE MODULE	Order: EXP9-9

1 ZONE OUTPUT BOARD FOR EXP9 Order: XCARD**RACK MOUNT ADAPTOR FOR EXP9 Order: RMEXP**

6-WAY A/V DISTRIBUTION AMPLIFIER

- Flat pack case allows easy space-saving positioning and mounting
- Drives up to six audio/video components from a single A/V source
- Low A/V distortion for crisp sound and picture
- A/V input/outputs: RCA-type phono jacks
- Power Supply: 16V DC @ 300 mA (included)
- Dimensions: 10"W x 2 3/4"D x 1 1/4"H (254mm x 70mm x 32mm)
- Power supply ISVAC @ 400 mA (included)

Order: AV61



IR REMOTE PREAMP

Four in, one out infrared remote controlled audio/video preamp.
IR control of Source Select, Volume, Bass, Treble, Balance and Mute.

- Four Source A/V inputs
- Separate Volume (Up/Down), Balance (Left/Right), Bass and Treble controls feature continuous adjustment in 2 dB steps, in either direction, all IR controlled
- Comes complete with power supply
- "Flat Pack" design for ease of placement and mounting
- IR input with IR confirm LED for use with Xantech IR controlled systems
- Requires RC68X hand-held remote programmer for IR control codes
- The RP41AV is adjustable to different RC68X IR control code groups, allowing individual control of multiple RS41AV's in a system
- "Flat Pack" design for ease of placement and mounting
- Power supply ISVAC @ 400 mA (included)

Order: RP41AV

