

# ReadyLine™ Cooling Tower Duty, Three Phase, Totally Enclosed Fan Cooled (TEFC), Inverter Duty 10:1 (6-60Hz Variable Torque)



## APPLICATIONS:

Designed for use in Cooling Tower, Evaporative Condenser and other commercial and industrial applications requiring protection from harsh operating conditions with up to 100% humidity.

**List A: For mounting positions F1, F2, C1, C2, W1, W2. List B: For mounting positions W5, W6, W7, W8.**

| HP  | RPM  | Voltage | Frame | Catalog Number | List A   | List B   | Discount Symbol | "C" Dim. (inches) | Ship Wt. (lbs.) | Full Load Eff. | Full Load Amps | Notes |
|-----|------|---------|-------|----------------|----------|----------|-----------------|-------------------|-----------------|----------------|----------------|-------|
| 60  | 1800 | 200     | 364T  | HW60V2H?       | \$7,502  | \$7,762  | DS-3HTL         | 32.6              | 830             | 95.0           | 159.0          | -     |
|     | 1800 | 230/460 | 364T  | HW60V2E?       | \$6,946  | \$7,206  | DS-3HTL         | 32.6              | 830             | 95.0           | 137.0/69.0     | -     |
|     | 1800 | 575     | 364T  | HW60V2G?       | \$7,988  | \$8,248  | DS-3HTL         | 32.6              | 830             | 95.0           | 55.0           | -     |
|     | 1200 | 200     | 404T  | HW60V3H?       | \$13,878 | \$14,228 | DS-3HTL         | 36.1              | 1050            | 94.5           | 161.0          | -     |
|     | 1200 | 230/460 | 404T  | HW60V3E?       | \$12,850 | \$13,200 | DS-3HTL         | 36.1              | 1200            | 94.5           | 140.0/70.0     | -     |
|     | 1200 | 575     | 404T  | HW60V3G?       | \$14,778 | \$15,128 | DS-3HTL         | 36.1              | 1050            | 94.5           | 56.0           | -     |
| 75  | 1800 | 200     | 365T  | HW75V2H?       | \$8,706  | \$8,966  | DS-3HTL         | 33.6              | 910             | 95.4           | 194.0          | -     |
|     | 1800 | 230/460 | 365T  | HW75V2E?       | \$8,061  | \$8,321  | DS-3HTL         | 33.6              | 920             | 95.4           | 169.0/84.0     | -     |
|     | 1800 | 575     | 365T  | HW75V2G?       | \$9,270  | \$9,530  | DS-3HTL         | 33.6              | 900             | 95.4           | 68.0           | -     |
|     | 1200 | 200     | 405T  | HW75V3H?       | \$16,106 | \$16,456 | DS-3HTL         | 37.7              | 1260            | 94.5           | 201.0          | -     |
|     | 1200 | 230/460 | 405T  | HW75V3E?       | \$14,913 | \$15,263 | DS-3HTL         | 37.7              | 1260            | 94.5           | 173.0/87.0     | -     |
|     | 1200 | 575     | 405T  | HW75V3G?       | \$17,150 | \$17,500 | DS-3HTL         | 37.7              | 1260            | 94.5           | 70.0           | -     |
| 100 | 1800 | 200     | 405T  | HW100V2H?      | \$13,019 | \$13,369 | DS-3HTL         | 37.7              | 1250            | 95.4           | 261.0          | -     |
|     | 1800 | 230/460 | 405T  | HW100V2E?      | \$12,055 | \$12,405 | DS-3HTL         | 37.7              | 1250            | 95.4           | 226.0/113.0    | -     |
|     | 1800 | 575     | 405T  | HW100V2G?      | \$13,863 | \$14,213 | DS-3HTL         | 37.7              | 1260            | 95.4           | 91.0           | -     |
|     | 1200 | 200     | 444T  | HW100V3H?      | \$24,086 | \$24,486 | DS-3HTL         | 43.4              | 1635            | 95.0           | 284.0          | -     |
|     | 1200 | 230/460 | 444T  | HW100V3E?      | \$22,302 | \$22,702 | DS-3HTL         | 43.4              | 1635            | 95.0           | 248.0/124.0    | -     |
|     | 1200 | 575     | 444T  | HW100V3G?      | \$25,647 | \$26,047 | DS-3HTL         | 43.4              | 1660            | 95.0           | 99.0           | -     |

† All non-Emerson Electric Co. marks shown within this document are properties of their other respective owners