

General Purpose Three Phase, Totally Enclosed Fan Cooled (TEFC) UNIMOUNT® Premium Efficient



UTE

APPLICATIONS:

Designed for general industrial equipment including fans, blowers, compressors, pumps and direct connected equipment.

FEATURES:

- Class F Insulation, Class B Rise At Full Load (4)
- Extruded Aluminum Frame (180-280)
- Rolled Steel Frame (56-140)
- Aluminum End Shields With Steel Bearing Inserts
- Oversized Diagonally Split Conduit Box
- Field Convertible To F2 Assembly 180 Frame & Up
- 40°C Ambient, NEMA® Design B Performance (4)
- Regreasable Shaft-End Bearings 180 Frame & Up
- Sealed Bearings 56-140, Doubled Shielded 180-280
- CE Mark On Nameplate, Removable Base 180 Frame & Up
- Lifting Provisions 180 Frame & Up
- Conversion Kits: C&D Flanges, Canopy, Brakes (56-210 Frame)

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Eff.	Full Load Amps	Notes
1	3600	208-220/440	56	T1P1M	\$213	DS-3FMP	1.00	10.0	23	0	3.4-3.2/1.6	-
	3600	208-230/460	56HZ	T1P1AHZ	\$209	DS-3F	1.00	12.8	28	80	3.4-3.2/1.6	-
	1800	230/460	143T	U1P2B	\$413	DS-3XE	1.25	12.8	40	85.5	3.0/1.5	-
	1800	575	143T	U1P2G	\$413	DS-3XE	1.25	12.8	40	85.5	1.1	-
	1200	230/460	145T	U1P3B	\$498	DS-3XE	1.25	12.8	40	82.5	3.5/1.8	-
	1200	575	145T	U1P3G	\$498	DS-3XE	1.25	12.8	40	82.5	1.4	-
1-1/2	3600	230/460	143T	U32P1B	\$485	DS-3XE	1.25	12.8	35	84	3.9/1.9	-
	3600	575	143T	U32P1G	\$485	DS-3XE	1.25	12.8	35	84	1.6	-
	1800	230/460	145T	U32P2B	\$429	DS-3XE	1.25	12.8	40	86.5	4.3/2.1	-
	1800	575	145T	U32P2G	\$429	DS-3XE	1.25	12.8	40	86.5	1.7	-
	1200	230/460	182T	U32P3B	\$532	DS-3XE	1.25	16.1	60	87.5	4.7/2.3	-
	1200	575	182T	U32P3G	\$532	DS-3XE	1.25	16.1	60	87.5	1.8	-
2	3600	230/460	145T	U2P1B	\$532	DS-3XE	1.25	12.8	40	86.5	4.9/2.5	-
	1800	230/460	145T	U2P2B	\$446	DS-3XE	1.25	12.8	45	86.5	5.7/2.8	-
	1800	575	145T	U2P2G	\$446	DS-3XE	1.25	12.8	45	86.5	2.3	-
	1200	230/460	184T	U2P3B	\$588	DS-3XE	1.25	16.1	70	88.5	6.2/3.1	-
	1200	575	184T	U2P3G	\$588	DS-3XE	1.25	16.1	70	88.5	2.5	-
3	3600	230/460	182T	U3P1B	\$589	DS-3XE	1.25	16.1	60	88.5	7.8/3.9	-
	3600	575	182T	U3P1G	\$589	DS-3XE	1.25	16.1	60	87.5	3.1	-
	1800	230/460	182T	U3P2B	\$492	DS-3XE	1.25	16.1	60	89.5	7.9/3.9	-
	1800	575	182T	U3P2G	\$492	DS-3XE	1.25	16.1	60	89.5	3.2	-
	1200	230/460	213T	U3P3B	\$903	DS-3XE	1.25	18.6	110	89.5	8.6/4.3	-
	1200	575	213T	U3P3G	\$903	DS-3XE	1.25	18.6	110	89.5	3.4	-
5	3600	230/460	184T	U5P1B	\$654	DS-3XE	1.25	17.0	75	89.5	12.2/6.1	-
	3600	575	184T	U5P1G	\$654	DS-3XE	1.25	16.1	75	88.5	4.9	-
	1800	230/460	184T	U5P2B	\$539	DS-3XE	1.25	17.0	80	90.2	12.3/6.2	-
	1800	575	184T	U5P2G	\$539	DS-3XE	1.25	16.1	80	89.5	5.0	-
	1200	230/460	215T	U5P3B	\$1,021	DS-3XE	1.25	20.1	135	90.2	14.0/7.0	-
	1200	575	215T	U5P3G	\$1,021	DS-3XE	1.25	20.1	135	89.5	5.6	-
7-1/2	3600	230/460	213T	U7P1B	\$982	DS-3XE	1.25	18.6	100	91.7	17.9/8.9	-
	3600	575	213T	U7P1G	\$982	DS-3XE	1.25	18.6	100	89.5	7.5	-
	1800	230/460	213T	U7P2B	\$779	DS-3XE	1.25	18.6	110	91.7	18.2/9.1	-
	1800	575	213T	U7P2G	\$779	DS-3XE	1.25	18.6	110	91.7	7.2	-
	1200	230/460	254T	U7P3B	\$1,623	DS-3XE	1.25	23.9	200	91.7	20.2/10.1	-
	1200	575	254T	U7P3G	\$1,623	DS-3XE	1.25	23.9	200	91	8.3	-

Note 04 On 60 Hertz Sine Wave power

† All non-Emerson Electric Co. marks shown within this document are properties of their other respective owners