

General Purpose Three Phase, Open Dripproof (ODP) Light Industrial U Frame Standard Efficient



APPLICATIONS:

Designed for pumps, fans, compressors, material handling, and other general purpose applications in damp, dusty, or dirty environments.

FEATURES:

- Class F Insulation
- Rolled Steel Frame
- Aluminum End Shields
- 40°C Ambient, NEMA[®] Design B Performance
- Double Shielded Bearings
- F1 Assembly
- Lifting Provision 210 Frame & Up
- Eliminates Need For Mounting Kits To Replace Pre-"T" Frame Motors

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Eff.	Full Load Amps	Notes
1	1800	208-220/440	182	D1S2MGZ	\$503	DS-3FTE	1.25	13.5	45	81.5	3.4-3.4/1.7	-
1-1/2	1800	208-220/440	184	D32SMGZ	\$524	DS-3FTE	1.20	13.5	50	82.5	4.8-4.7/2.4	-
2	1800	208-220/440	184	D2S2MGZ	\$564	DS-3FTE	1.20	15.4	55	84	6-5.8/2.9	-
3	1800	208-220/440	213	D3S2MGZ	\$694	DS-3FTE	1.15	15.3	75	85.5	8.8-8.6/4.3	-
	1200	208-220/440	215	D3S3MGZ	\$772	DS-3FTE	1.15	15.4	80	86.5	10.2-9.9/5	-
5	1800	208-220/440	215	D5S2MGZ	\$717	DS-3FTE	1.15	15.4	93	86.5	14.2-13.4/6.7	-
7-1/2	1800	208-220/440	254U	D7S2MGZ	\$1,309	DS-3FTE	1.15	17.8	127	87.5	20.9-19.7/9.8	-
10	1800	208-220/440	256U	D10S2MGZ	\$1,581	DS-3FTE	1.15	22.0	142	88.5	28.3-26.5/13.2	-

† All non-Emerson Electric Co. marks shown within this document are properties of their other respective owners