

**Pressure Washer,
Single Phase,
TEFC and ODP**

1-1/2 thru 5 Hp

NEMA 56 thru 184TC

Applications: Pressure washers, steam cleaners, portable and self contained stationary system for direct drive mount and doubled mount designs.

Features: Ball bearing design. 1 1/2 horsepower ratings are rated at 14 amps or less on 115 volts. Manual thermal overload located in the conduit box. UL and CSA recognized component approval. 200°C copper windings. Capacitor start, capacitor run (two value capacitor).



Hp	RPM	NEMA Frame	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
Foot Mounted, TEFC											
1 1/2	3600	56	PL3513M	489	K	13.25	34	75.5	115/230	6.6	
	1800	56	PL3514M	649	K	14.12	50	82.5	115/230	6	
2	3600	56	PL3515M	591	K	13.25	39	77	115/230	8.8	1
	1800	56HZ	L3516TM	804	K	14.18	48	78	230	8.3	1,57,65
3	3600	56	PL3519M	648	K	14.12	47	85.5	230	12.5	1,30
	1800	184T	L3609TM	888	L1	16.54	76	78	115/230	14.5	2,20,65
5	3600	184T	L3608TM	1,023	L1	18.05	86	83	230	19.5	2,20,65
	1800	184T	L3612TM	1,033	L1	18.05	99	80	230	23	2,20,65
C-Face, Foot Mounted, ODP											
3	1800	184TC	CL1408TM	781	L1	15.00	78	78	115/230	16	65
5	1800	184TC	CL1410TM	940	L1	16.50	88	82.5	230	23	1,30,65
C-Face, Foot Mounted, TEFC											
1 1/2	3600	56C	PCL3513M	523	K	13.25	35	75.5	115/230	6.6	
	1800	56C	PCL3514M	683	K	14.12	50	82.5	115/230	6	
2	3600	56C	PCL3515M	620	K	13.24	43	77	115/230	8.8	1
	1800	145TC	CL3516TM	811	L1	14.19	49	78	230	8.3	1,65
3	3600	56C	PCL3519M	680	K	14.12	52	85.5	230	12.5	1,30
	1800	184TC	CL3619TM	1,056	L1	16.54	81	81.5	230	13.2	2,20
5	3600	184TC	CL3608TM	1,143	L1	18.05	91	83	230	19.5	2,20
	1800	184TC	CL3612TM	1,106	L1	18.05	101	80	230	23	2,20
Foot Mounted, ODP											
1 1/2	3600	56H	PL1313M	425	K	11.75	34	75.5	115/230	6.6	36
	1800	56	PL1319M	564	K	12.06	39	74	115/230	7	
2	3600	56	PL1317M	554	K	12.06	38	77	115/230	8.8	
	1800	56	PL1322M	591	K	12.94	43	78.5	115/230	9.2	
3	3600	56	PL1326M	612	K	12.94	45	85.5	230	12.5	30
	1800	184T	L1408TM	739	L1	15.00	78	78	115/230	16	65
5	3600	56/56H	PL1327M	630	K	13.81	54	74.2	230	23	2,20,30,36
	1800	184T	L1410TM	899	L1	16.50	84	82.5	230	23	1,30,65
C-Face, Foot Mounted, ODP											
1 1/2	3600	56C	PCL1313M	461	K	12.06	35	75.5	115/230	6.6	
	1800	56C	PCL1319M	591	K	12.06	40	74	115/230	7	
2	3600	56C	PCL1317M	591	K	12.06	39	77	115/230	8.8	
	1800	56C	PCL1322M	613	K	12.94	45	78.5	115/230	9.2	
3	3600	56C	PCL1326M	648	K	12.94	47	85.5	230	12.5	30
5	3600	56HCY	PCL1327M	664	K	14.11	55	74.2	230	23	2,20,30,37,47

(a) See notes on inside back flap and pages 5-6.

Farm Duty Motors

Definite Purpose Motors

Unit Handling

Brake Motors

200 & 575 Volt Motors

IEC Frame Motors

50 Hertz Motors

Inverter/Vector Motors & Controls

DC Motors and Controls

Soft Start & Dynamic Brakes