

General Purpose Single Phase, 50 Hz Open Dripproof (ODP) & Totally Enclosed Fan Cooled (TEFC)



APPLICATIONS:

Designed for air compressors, pumps, conveyors, blowers and general industrial equipment

FEATURES:

- Double Shielded Ball Bearings, unless noted
- Class B Insulation, Continuous Duty, 40°C Ambient
- Split Phase, Capacitor Start
- F1 Assembly
- Reversible Rotation
- D13BA2LZ9 shaft extension is 1/2" dia. x 1 1/2" long

Open Dripproof (ODP), Split Phase, Resilient Base

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Amps	Notes
1/4	1500	110/220	48	D14B2L4A9	\$119	DS-3FMP	1.00	9.0	16	6.8/3.4	25, 61
1/3	1500	110/220	48	D13BA2L49	\$135	DS-3FMP	1.00	9.0	11	7.1/3.6	24
	1500	110/220	56Z	D13BA2LZ9	\$140	DS-3FMP	1.00	9.0	17	6.8/3.4	24
1/2	1500	110/220	56	D12BA2L9	\$156	DS-3FMP	1.00	12.0	19	9.2/4.6	24

Totally Enclosed Fan Cooled (TEFC), Capacitor Start, Footed

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Amps	Notes
1/3	1500	110/220	56	T13C2L	\$303	DS-3FMP	1.00	10.0	24	7.4/3.7	25
1/2	1500	110/220	56	T12C2L	\$263	DS-3FMP	1.00	11.0	28	8.4/4.2	25
3/4	1500	110/220	56	T34C2L	\$321	DS-3FMP	1.00	12.0	36	12.2/6.1	25
1	1500	110/220	56H	T1C2LH	\$363	DS-3FMP	1.00	13.0	40	14.4/7.2	25

Totally Enclosed Fan Cooled (TEFC), Capacitor Start, C-Face Footless

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Amps	Notes
1/3	1500	110/220	56C	T13C2LCR	\$247	DS-3FMP	1.00	10.0	24	7.4/3.7	25, F
1/2	1500	110/220	56C	T12C2LCR	\$271	DS-3FMP	1.00	11.0	26	8.4/4.2	25, F

Note 24 Automatic Reset Thermal Overload Protector
Note 25 Non-protected

Note 61 Sleeve Bearings
Note F Footless