

General Purpose Three Phase Totally Enclosed Fan Cooled (TEFC) Light Industrial U Frame Standard Efficient



APPLICATIONS:

Designed for pumps, fans, compressors, material handling, and other general purpose applications in damp, dusty, or dirty environments.

FEATURES:

- Class F Insulation, Class B Rise At Full Load
- Rolled Steel Frame
- Aluminum End Shields
- 40°C Ambient, NEMA® Design B Performance
- Double Shielding Bearings
- F1 Assembly
- Lifting Provision
- Eliminates Need For Mounting Kits To Replace Pre-"T" Frame Motors

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Eff.	Full Load Amps	Notes
1	1800	208-220/440	182	T1S2MGZ	\$549	DS-3FTE	1.00	14.4	45	78.5	3.4-3.4/1.7	-
	1200	208-220/440	184	T1S3MGZ	\$700	DS-3FTE	1.00	14.4	45	77	3.9-3.9/1.9	-
1-1/2	1800	208-220/440	184	T3S2MGZ	\$559	DS-3FTE	1.00	14.4	50	81.5	4.8-4.8/2.4	-
	1200	208-220/440	184	T3S3MGZ	\$661	DS-3FTE	1.00	14.4	50	77	5.6-5.4/2.7	-
2	3600	208-220/440	184	T2S1MGZ	\$718	DS-3FTE	1.00	15.4	50	75.5	6.4-6.1/3.1	-
	1800	208-220/440	184	T2S2MGZ	\$589	DS-3FTE	1.00	14.4	60	84	6.1-5.8/2.9	-
3	3600	208-220/440	184	T3S1MGZ	\$590	DS-3FTE	1.00	14.4	60	81.5	8.8-8.4/4.2	-
	1800	208-220/440	213	T3S2MGZ	\$527	DS-3FTE	1.00	16.2	62	85.5	8.9-8.5/4.3	-
	1200	208-220/440	215	T3S3MGZ	\$891	DS-3FTE	1.00	18.5	80	84	10.6-10.5/5.3	-
5	1800	208-220/440	215	T5S2MGZ	\$914	DS-3FTE	1.00	18.5	98	85.5	14.5-14/7	-
7-1/2	1800	208-220/440	254U	T7S2MGZ	\$1,017	DS-3FTE	1.00	21.1	135	88.5	20.7-19.6/9.8	-

† All non-Emerson Electric Co. marks shown within this document are properties of their other respective owners