

Special Application Single Phase, Open Dripproof (ODP) Jet Pump, Square Flange & C-Face, Capacitor Start



APPLICATIONS:

Designed for jet pumps, booster pumps, centrifugal pumps, lawn sprinkler pumps.

FEATURES:

- 416 Stainless Steel Shaft
- C-Face: 7/16-20 UNF2A thread
- Square Flange: 1/2-20 UNC-2A thread
- Ball Bearings (Locked Drive End Bearing)
- Continuous Duty
- 60 Hertz
- E-Z Access® Cover
- 40C Ambient
- Automatic Reset Thermal Overload Protector
- Round Frame (Without Base), NEMA®† 56C Mounting
- Power Leads Supplied For Proper Connection To Pressure Switch
- Voltage Selector Switch (Catalog Numbers Ending With "-2V")

C-Face, Two Compartment, E-Z Access®

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Amps	Notes
1/2	3600	115/230	56J	JJ0502-2V	\$136	DS-3FJP	1.60	13.0	15	9.4/4.8	-
3/4	3600	115/230	56J	JJ0752-2V	\$158	DS-3FJP	1.50	13.8	19	12.8/6.4	-
1	3600	115/230	56J	JJ1002-2V	\$182	DS-3FJP	1.40	14.0	21	13.4/6.7	-
1-1/2	3600	115/230	56J	JJ1502-2	\$203	DS-3FJP	1.30	14.5	25	14.0/7.0	18
2	3600	230	56J	JJ2002-2	\$232	DS-3FJP	1.20	13.5	25	8.6	18
3	3600	230	56J	JJ3002-2	\$264	DS-3FJP	1.15	14.8	32	14.2	18

Square Flange, Two Compartment, E-Z Access®

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	SF Amps	Notes
1/2	3600	115/230	48Y	JS050UPR	\$131	DS-3FJP	1.3	11.35	15	9.8/4.9	UL
	3600	115/230	48Y	JS0502-2V	\$139	DS-3FJP	1.9	11.6	17	11.8/5.7	
3/4	3600	230/115	48Y	JS075UPR	\$152	DS-3FJP	1.27	11.6	17	4.8/9.6	UL
	3600	115/230	48Y	JS0752-2V	\$161	DS-3FJP	1.65	11.9	20	14.8/7.4	
1	3600	230/115	48Y	JS100UPR	\$176	DS-3FJP	1.24	11.9	20	7.4/14.8	UL
	3600	115/230	48Y	JS1002-2V	\$185	DS-3FJP	1.65	12.4	22	18.4/9.2	
1.5	3600	115/230	48Y	JS1502-2V	\$210	DS-3FJP	1.5	12.9	24	19.6/9.8	
2	3600	230	48Y	JS2002-2	\$241	DS-3FJP	1.3	12.9	25	11.2	18
3	3600	230	48Y	JS3002-2	\$271	DS-3FJP	1.15	13.96	33	14.2	18

Square Flange, Single Compartment

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	SF Amps	Notes
1/3	3600	115	48Y	JS0332-1	\$118	DS-3FJP	1.95	10.3	13	8.8	94
1/2	3600	115/230	48Y	JS0502-1	\$130	DS-3FJP	1.9	10.8	17	11.4/5.7	
3/4	3600	115/230	48Y	JS0752-1	\$152	DS-3FJP	1.65	11	19	14.8/7.4	
1	3600	115/230	48Y	JS1002-1	\$175	DS-3FJP	1.65	11.5	22	18.4/9.2	
1.5	3600	115/230	48Y	JS1502-1	\$200	DS-3FJP	1.5	12	25	19.6/9.8	18
2	3600	230	48Y	JS2002-1	\$235	DS-3FJP	1.3	12	25	11	18

Note 18 Incorporates Run Capacitor

Note 94 Split Phase

Note UL UL® 778 Approvable Design

† All non-Emerson Electric Co. marks shown within this document are properties of their other respective owners