

# General Purpose Single Phase Open Dripproof (ODP), Rigid Base, Split Phase



## APPLICATIONS:

Designed for commercial and industrial ventilation systems.

## FEATURES:

- 40°C Ambient, 60 Hertz
- Reversible Rotation
- Continuous Duty
- Class A or B Insulation
- Sleeve Bearings Have All Angle Thrust System
- 56Z has 1/2" X 1-1/2" Shaft

## Rigid Base

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Amps	Notes
1/4	1800	110/220	48	D14BA2L4	\$125	DS-3FMP	1.00	9.3	15	4.7/2.3&5.5/2.7	24, 98
	1800	115	48	D14B2N4A	\$79	DS-3FMP	1.00	9.4	14	5.4	61
	1800	115	48	D14BA2N4A	\$102	DS-3FMP	1.00	9.7	14	5.4	24, 61
	1800	115	48Z	D14B2N4Z	\$69	DS-3FMP	1.00	9.3	14	5.1	
	1800	115	56Z	D14B2NZA	\$96	DS-3FMP	1.00	9.4	14	5.4	61
1/3	3600	115	48	D13B1N4	\$111	DS-3FMP	1.00	9.0	14	6.6	
	1800	115	48	D13B2N4A	\$85	DS-3FMP	1.00	9.7	16	6.8	61
	1800	115	48	D13BA2N4A	\$113	DS-3FMP	1.00	9.4	16	6	24, 61
	1800	230	48	D13BA2K4A	\$121	DS-3FMP	1.00	9.4	15	3	24, 61
	1800	115	48Z	D13B2N4Z	\$71	DS-3FMP	1.15	9.6	14	5.9	
	1800	115	56Z	2911	\$134	DS-3FMP	1.00	9.4	17	6.0	61
	1800	115	56Z	D13B2NZA	\$93	DS-3FMP	1.00	9.4	15	6	61
	1800	115	56Z	D13BA2NZ	\$129	DS-3FMP	1.00	9.4	15	6	24
1/2	3600	115	48	D12B1N4A	\$142	DS-3FMP	1.00	10.0	15	8.6	61
	1800	115	48	D12B2N4	\$136	DS-3FMP	1.00	9.8	18	8.8	
	1800	115	56	D12B2NA	\$136	DS-3FMP	1.00	9.3	20	8.6	61
	1800	115	56	D12BM2N	\$165	DS-3FMP	1.00	9.3	21	8.6	23
	1800	115	56Z	D12B2NZ	\$83	DS-3FMP	1.15	9.8	21	8.6	
3/4	1800	115	56Z	D34B2NZ	\$102	DS-3FMP	1.15	10.8	24	11.3	

Note 23 Manual Reset Thermal Overload Protector  
 Note 24 Automatic Reset Thermal Overload Protector  
 Note 61 Sleeve Bearing

Note 98 50/60 Hz  
 Note LA Limited Availability