

Three Phase Commercial Condenser Fan

Open Dripproof, Air Over



APPLICATIONS:

Designed for use on condenser cooling fans in commercial air conditioning applications where 3 phase power is required.

FEATURES:

- Automatic Reset Thermal Overload Protector
- Reversible Rotation
- Continuous Duty, Air Over
- Double-sealed Ball Bearings
- Dual Voltage
- Class B Insulation
- 140°F (60°C) Ambient Rated
- Shaft-up Mounting
- Discount Symbol: DS-3HAC

Belly Band Mount, Flat and Keyway on Shaft

HP	RPM	Volts	NEMA Frame	Catalog Number	List Price	Bearings	Amps	Shaft Length	Shaft Dia.	SF	Total Length	Ship Wgt.	Notes	OEM
1/3	1600	380/460	48	2387	\$394	Slv	1.0	2.0	.500	1.00	10.4	14	1	TE
3/4	1140	208-230/460	56YZ	1817	\$319	Ball	3.6/1.8	6.0	.625	1.00	16.8	28		
1	850	208-230/460	56YZ	1828	\$430	Ball	5.0/2.5	6.0	.625	1.00	17.2	33		
	1140	208-230/460	56YZ	1818	\$348	Ball	4.8/2.4	6.0	.625	1.00	16.8	29		
	1140	200-230/460	56YZ	1816	\$388	Ball	6.0/3.0	3.0	.625	1.00	13.6	35		CA
	1140	200-230/460	56YZ	1326	\$313	Ball	3.5-3.3/1.7	5.0	.500	1.00	14.5	19		DB
	1140	200-230/460	56Z	8058	\$360	Ball	3.6/1.8	3.4	.625	1.00	13.7	30		LE
1-1/2	1140	208-230/460	56YZ	1819	\$380	Ball	7.1/3.6	6.0	.625	1.00	16.8	36		
2	1140	208-230/460	56YZ	8987	\$406	Ball	7.8/3.9	6.0	.625	1.00	16.8	43		

Rigid Base Mount, Flat and Keyway on Shaft

HP	RPM	Volts	NEMA Frame	Catalog Number	List Price	Bearings	Amps	Shaft Length	Shaft Dia.	SF	Total Length	Ship Wgt.	Notes	OEM
1	1140	208-230/460	56YZ	1820	\$414	Ball	4.8/2.4	6.0	.625	1.00	16.8	32		
1-1/2	1140	208-230/460	56YZ	1821	\$443	Ball	7.2/3.6	6.0	.625	1.00	16.8	39		
2	1140	208-230/460	56Y	1822	\$495	Ball	7.8/3.9	6.0	.625	1.00	17.3	45		

Note 1 50/60 Hz
Note 2 Totally Enclosed Air Over

Note LA Limited Availability