

BALDOR • RELIANCE®

**575 Volt,
Three Phase,
Close-Coupled Pump,
TEFC and ODP,
C-Face**

1 thru 20 Hp

NEMA 143JM thru 256JM

Applications: Applications for circulating and transferring fluids.

Features: Over-sized ball bearings with locked drive end construction for minimum shaft movement. Open drip-proof, close coupled pump motors are furnished with rodent screens at both ends. EJMM Super-E® motors have NEMA Premium® efficiency. 3 year warranty.



Hp	RPM	NEMA Frame	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
C-Face, Foot Mounted, Totally Enclosed Fan Cooled											
1	1800	143JM	JMM3546T-5	469	L1	15.43	34	75	575	1.4	
1 1/2	3600	143JM	JMM3550T-5	492	L1	15.43	36	75	575	1.8	
	1800	145JM	JMM3554T-5	492	L1	15.43	37	78.5	575	2	
2	3600	145JM	JMM3555T-5	549	L1	15.43	41	78.5	575	2.2	
	1800	145JM	JMM3558T-5	514	L1	15.43	44	82.5	575	2.5	
3	3600	145JM	JMM3559T-5	616	L1	15.43	50	82.5	575	3	1
		182JM	JMM3610T-5	639	L1	16.69	60	81.5	575	3.1	
5	3600	182JM	JMM3611T-5	616	L1	16.69	63	82.5	575	3.6	1
		184JM	JMM3613T-5	788	L1	18.06	75	85.5	575	4.8	1
7 1/2	3600	184JM	JMM3615T-5	688	L1	18.06	79	85.5	575	5.3	1
		184JM	JMM3616T-5	892	L1	19.56	88	87.5	575	6.9	2,20
10	3600	213JM	JMM3710T-5	881	L1	19.81	122	87.5	575	8.2	1
		215JM	JMM3711T-5	1,202	L1	19.81	127	85.5	575	9.6	1
15	3600	215JM	JMM3714T-5	1,112	L1	20.94	134	87.5	575	10.4	2,20
		254JM	JMM3713T-5	1,584	L1	20.94	151	86.5	575	13.7	
20	3600	254JM	JMM2394T-5	1,649	L1	23.07	192	86.5	575	13.7	1
		254JM	JMM2333T-5	2,032	L1	23.07	203	87.5	575	16	1
C-Face, Footless, Totally Enclosed Fan Cooled											
1	1800	143JM	VJMM3546T-5	477	L1	14.43	36	75	575	1.4	
1 1/2	1800	145JM	VJMM3554T-5	500	L1	14.43	37	78.5	575	2	
2	1800	145JM	VJMM3558T-5	523	L1	15.43	45	82.5	575	2.5	
3	1800	182JM	VJMM3611T-5	625	L1	16.83	65	82.5	575	3.6	1
5	1800	184JM	VJMM3615T-5	701	L1	18.05	76	85.5	575	5.3	1
7 1/2	1800	213JM	VJMM3710T-5	910	L1	19.76	121	87.5	575	8	1
10	1800	215JM	VJMM3714T-5	1,124	L1	16.64	130	87.5	575	10.4	2,20
15	1800	254JM	VJMM2333T-5	2,050	L1	21.82	190	87.5	575	16	1
20	1800	256JM	VJMM2334T-5	2,119	L1	25.16	267	91	575	19.1	1
C-Face, Foot Mounted, Open Drip Proof											
3	3600	145JM	JMM3158T-5	530	L1	14.25	45	80	575	3.2	
	1800	182JM	JMM3211T-5	525	L1	15.63	60	82.5	575	3.3	1
5	3600	182JM	JMM3212T-5	596	L1	15.12	59	84	575	4.8	
	1800	184JM	JMM3218T-5	568	L1	16.50	66	82.5	575	5.6	
7 1/2	3600	184JM	JMM3219T-5	729	L1	16.50	70	84	575	7.2	1
	1800	213JM	JMM3311T-5	825	L1	18.19	100	85.5	575	8.8	
10	3600	213JM	JMM3312T-5	991	L1	18.19	92	82.5	575	10	
	1800	215JM	JMM3313T-5	980	L1	18.19	110	85.5	575	11.2	
15	3600	215JM	JMM3314T-5	1,332	L1	19.78	113	85.5	575	14.5	1

(a) See notes on inside back flap and pages 5-6.

MEETS NRC CANADIAN STANDARDS FOR EFFICIENCY.

■ Cast Iron Frame