

Three Phase Commercial Belt-Drive Blower Motor

Open Dripproof, Air Over Not Required



APPLICATIONS:

Designed for use on belt-drive blowers in commercial air conditioning applications where 3 phase power is required.

FEATURES:

- Automatic Reset Thermal Overload Protector
- Reversible Rotation
- Continuous Duty
- Double-sealed Ball Bearings
- Dual Voltage
- Class B Insulation
- 104°F (40°C) Ambient
- Discount Symbol: DS-3HAC

Rigid Base Mount

HP	RPM	Volts	NEMA Frame	Catalog Number	List Price	Bearings	Amps	Shaft Length	Shaft Dia.	SF	Total Length	Ship Wgt.	Notes	OEM
1	1725	208-230/460	56	1813	\$291	Ball	3.4/1.7	1.9	.625	1.15	11.9	24	1	
1-1/2	1725	208-230/460	56	1814	\$325	Ball	5.0/2.5	1.9	.625	1.15	12.4	27	1	
	1725	200-230/460	56HZ	7913	\$393	Ball	5.0/2.5	2.3	.875	1.15	12.4	39		LE
2	1725	208-230/460	56H	1815	\$355	Ball	6.6/3.3	1.9	.625	1.15	12.4	29	1	
	1725	200-230/460	56HZ	7914	\$420	Ball	7.6-7.8/3.9	2.3	.875	1.15	12.4	45		LE
	1725	208-230/460	145T	8461	\$488	Ball	6.3-6.2/3.1	2.3	.875	1.00	12.5	37	2, 4	
3	1725	200-230/460	56HZ	7915	\$519	Ball	9.0-9.2/4.6	2.3	.875	1.15	13.3	48		LE

Resilient Mount

HP	RPM	Volts	NEMA Frame	Catalog Number	List Price	Bearings	Amps	Shaft Length	Shaft Dia.	SF	Total Length	Ship Wgt.	Notes	OEM
1/3	1725	208-230/460	56	8496	\$244	Ball	1.5-1.6/0.8	1.9	.625	1.0	10.3	18	2, 3	
1/2	1140	208-230/460	56	8458	\$423	Ball	2.4-2.4/1.2	1.9	.625	1.0	11.1	26	4	
	1725	208-230/460	56	8488	\$324	Ball	2.1-2.2/1.1	1.9	.625	1.25	10.3	20		
3/4	1725	208-230/460	56	8489	\$353	Ball	2.9-2.9/1.5	1.9	.625	1.25	10.8	22		
1	1725	208-230/460	56	8498	\$313	Ball	4.3/2.2	1.9	.625	1.25	11.3	26		
	1725	208-230/460	56	8460	\$333	Ball	3.0/1.5	1.9	.625	1.00	11.1	27	4	
1-1/2	1725	208-230/460	56H	8490	\$390	Ball	5.2-5.1/2.6	1.9	.625	1.15	12.8	32		
	1725	208-230/460	145T	8491	\$500	Ball	5.0-4.6/2.4	2.3	.875	1.15	13.2	40		
2	1725	208-230/460	56H	8493	\$448	Ball	6.1-6.3/3.1	1.9	.625	1.15	12.8	41		
	1725	208-230/460	145T	8494	\$503	Ball	6.1-6.3/3.1	2.3	.875	1.15	13.2	44		

Note 1 Quick Voltage Change Device

Note 2 Conduit Box

Note 3 5.6" Diameter

Note 4 Totally Enclosed Air Over