

BALDOR • RELIANCE®

**Jet Pump,
Single Phase,
TEFC and ODP**

1/3 thru 3 Hp

NEMA 56C and 56J

Applications: Residential and industrial pumps, swimming pool pumps, etc.



Features: Diecast aluminum end plates with machined steel bearing seat insert.

Hp	RPM	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)	Reliance M/N
TEFC, 56J, Foot Mounted											
1/3	1800	CJL3501A	326	K	11.84	23	60	115/230	3	30	
1/2	1800	CJL3504A	384	K	12.47	28	68	115/230	3.7	30	
3/4	1800	CJL3507A	468	K	12.97	35	74	115/230	4.1	30	
TEFC, 56J, Footless											
1/3	3600	JL3405A	241	K	9.29	23	60	115/230	3		C56H5011
	1800	JL3501A	300	K	9.29	21	60	115/230	3	30	C56H3002
1/2	3600	JL3503A	276	K	10.29	25	62	115/230	3.7	30	C56H5010
	1800	JL3504A	350	K	10.29	26	68	115/230	3.7	30	C56H1590
3/4	3600	JL3506A	329	K	10.29	28	66	115/230	5.4	30	C56H1594
	1800	JL3507A	415	K	12.97	32	74	115/230	4.1	30	C56H1589
1	3600	JL3509A	402	K	13.74	39	66	115/230	6		C56H1593
	1800	JL3510A	476	K	13.74	42	67	115/230	6.2	2	C56H1782
1 1/2	3600	JL3513A	476	K	13.74	44	70	115/230	8.3	2,30	C56H1592
	1800	JL3514A	523	K	14.62	49	75.5	115/230	8	2	C56H1781
2	3600	JL3515A	561	K	14.62	54	74	115/230	11.5	2	
	1800	JL3516A	596	K	14.62	50	78	115/230	8.6	2,20	
ODP, 56J, Foot Mounted											
1/3	3600	CJL1205A	236	K	11.91	24	58	115/230	3.1		
	1800	CJL1301A	355	K	11.89	23	60	115/230	3	30	
1/2	3600	CJL1303A	246	K	12.51	27	66	115/230	3.7		
	1800	CJL1304A	402	K	12.14	26	62	115/230	4.2	30	
3/4	3600	CJL1306A	313	K	13.39	29	69	115/230	5.5		
	1800	CJL1307A	462	K	12.25	31	63	115/230	5.4		
1	3600	CJL1309A	321	K	13.89	33	65	115/230	7	30	
1 1/2	3600	CJL1313A	447	K	13.89	37	78.5	115/230	6.5		
2	3600	CJL1317A	598	K	13.25	44	70	115/230	13	30	
ODP, 56J, Footless											
1/2	3600	JL1303A	234	K	12.51	26	66	115/230	3.7		
3/4	3600	JL1306A	308	K	13.39	28	69	115/230	5.5		
1	3600	JL1309A	319	K	13.89	33	65	115/230	7	30	
1 1/2	3600	JL1313A	445	K	13.89	37	78.5	115/230	6.5		
	1800	JL1319A	480	K	13.25	39	68	115/230	9	2	
2	3600	JL1317A	549	K	13.25	41	70	115/230	13	30	
	1800	JL1322A	532	K	14.13	47	78.5	115/230	9.2		
3	3600	JL1323A	564	K	14.13	50	82.5	230	13	30	
ODP, 56C, Footless											
1/2	3600	VL1303A	259	K	12.00	26	66	115/230	3.7		
3/4	3600	VL1306A	309	K	12.88	30	69	115/230	5.5		
	1800	VL1307A	422	K	11.75	31	63	115/230	5.4		
1	3600	VL1309A	326	K	13.40	32	65	115/230	7	30	
	1800	VL1318A	448	K	12.75	41	67	115/230	6.2	2	
1 1/2	3600	VL1313A	445	K	13.01	35	78.5	115/230	6.5		
2	3600	VL1317A	576	K	12.75	41	70	115/230	13	30	
3	3600	VL1323A	596	K	13.63	49	82.5	230	13	30	

(a) See notes on inside back flap and pages 5-6.
All threaded shaft single phase motors are connected single rotation - CCW when viewing drive end.

ALL ABOVE RATINGS CAN BE UL 1081 COMPLIANT THROUGH MOD EXPRESS. SEE THE MOD EXPRESS PROGRAM SECTION IN THIS CATALOG FOR MORE DETAILS.