

Three Phase, ODP

1/2 thru 5 Hp

NEMA 56 thru 184T



Applications: Ventilators, direct-drive or belted fan and ventilation applications.

Features: Heavy-gauge steel base, ball bearings, suitable for mounting in any position. Dynamically balanced rotors for reduced vibration and quiet operation.

Hp	RPM	NEMA Frame	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
Foot Mounted											
1/2	1800	56	HM3108	266	K	9.51	22	74	230/460	1	1,30
		56	HM3108A	342	K	10.34	23	74	230/460	1	30
3/4	1800	56	HM3112	294	K	10.97	26	75.5	208-230/460	1.5	
		56	HM3112A	376	K	10.97	26	74	230/460	1.5	30
1	1800	56HZ	HM3116	332	K	12.13	32	78.5	230/460	1.7	30
		56HZ	HM3116A	415	K	12.13	32	74	208-230/460	2	
1 1/2	1800	56HZ	HM3154	382	K	12.13	36	81.5	208-230/460	2.2	
		56HZ	HM3154A	458	K	12.13	33	81.5	208-230/460	2.2	
2	1800	56HZ	HM3157	401	K	12.13	39	81.5	208-230/460	2.9	
		56HZ	HM3157A	477	K	12.13	36	81.5	208-230/460	2.9	
3	1800	56HZ	HM3161A	520	K	13.00	47	82.5	208-230/460	4.1	
5	1800	184T	HM3218TA	587	L1	15.00	72	87.5	208-230/460	7	
Resilient Base											
1/4	1800	48	RHM3003	233	K	10.34	19	64	230/460	0.65	30
1/3	1800	48	RHM3007	236	K	10.34	25	68	230/460	0.8	30
		56	RHM3104	267	K	10.97	21	68	230/460	0.8	30
1/2	1800	48	RHM3010	296	K	10.34	22	72	230/460	1	30
		56	RHM3108	307	K	10.97	24	74	230/460	1	30
		56	RHM3108A	354	K	11.59	24	74	230/460	1	30
3/4	3600	56	RHM3111	309	K	10.97	24	75.5	230/460	1.2	30
		56H	RHM3111A	357	K	11.59	21	74	230/460	1.3	30
	1800	56	RHM3112	338	K	12.47	31	77	230/460	1.2	30
1	3600	56H	RHM3112A	382	K	11.59	26	74	230/460	1.5	30
		56	RHM3115	328	K	10.97	24	75.5	230/460	1.8	30
		56	RHM3115A	378	K	11.59	24	75.5	230/460	1.6	30
1 1/2	1800	56	RHM3116	355	K	12.47	32	78.5	230/460	1.7	30
		56H	RHM3116A	403	K	12.47	33	78.5	230/460	1.7	30
		56H	RHM3120A	428	K	12.47	32	81.5	230/460	2	30
2	3600	56H	RHM3154	410	K	11.42	37	81.5	208-230/460	2.2	
		56H	RHM3154A	414	K	11.42	38	81.5	208-230/460	2.2	
		56H	RHM3155A	496	K	12.47	33	80	230/460	2.7	30
3	1800	56H	RHM3157	446	K	12.42	38	81.5	208-230/460	2.9	
		56H	RHM3157A	477	K	12.42	38	81.5	208-230/460	2.9	
		56H	RHM3158	549	K	12.42	42	82.5	208-230/460	3.8	
5	3600	145T	RHM3158TA	541	L1	12.79	45	84	208-230/460	3.9	
		145T	RHM3161TA	527	L1	15.04	60	86.5	208-230/460	4	1
5	3600	56HZ	RHM3162TA	739	K	13.64	51	80	208-230/460	6.5	1

(a) See notes on inside back flap and pages 5-6.

General Information

Single Phase Motors

General Purpose Industrial Motors

Premium Efficient Super-E® Motors

Severe Duty Motors

Washdown Duty Motors

Explosion Proof Motors

Pump Motors

Commercial Motors

HVAC Motors