

Farm Duty Motors

**F-2 Mount,  
Three Phase,  
TEFC and ODP,  
Foot Mounted**

**1 thru 60 Hp**

**NEMA 145T thru 364T**

**Applications:** Pumps, compressors, fans, conveyors, machine tools and other applications requiring three phase F-2 mounted motors.

**Features:** Copper windings, ball bearings, heavy-gauge steel frame with base seam-welded. EFM Super-E® motors have NEMA Premium® efficiency and 3 year warranty.



Definite Purpose Motors

Unit Handling

Brake Motors

200 & 575 Volt Motors

IEC Frame Motors

50 Hertz Motors

Inverter/Vector Motors & Controls

DC Motors and Controls

Soft Start & Dynamic Brakes

Hp	RPM	NEMA Frame	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes <sup>(a)</sup>
<b>Totally Enclosed Fan Cooled</b>											
2	1800	145T	FM3558T	397	L1	13.31	42	84	208-230/460	2.9	
3	1800	182T	FM3611T	469	L1	16.55	70	87.5	208-230/460	4.1	1
5	1800	184T	FM3615T	540	L1	16.56	74	87.5	208-230/460	7.1	1
7 1/2	1800	213T	FM3710T	689	L1	17.89	110	89.5	208-230/460	10.1	1
10	1800	215T	FM3714T	838	L1	19.01	126	89.5	208-230/460	13.5	1
15	1800	254T	EFM2333T	1,780	L1	23.16	255	92.4	230/460	18.5	1,30
20	1800	256T	EFM2334T	2,156	L1	23.16	286	93	230/460	24	1,30
25	1800	284T	EFM4103T	2,820	L1	27.76	392	93.6	230/460	30	1,30
30	1800	286T	EFM4104T	3,349	L1	27.76	444	94.1	230/460	36	1,30
<b>Open Drip Proof</b>											
1	1800	145T	EFM3116T	478	L1	11.12	36	85.5	208-230/460	1.4	1
1 1/2	1800	145T	EFM3154T	500	L1	12.12	37	88.5	208-230-460	2.1	1
2	1800	145T	EFM3157T	536	L1	13.00	43	86.5	208-230/460	2.7	1
3	1800	182T	EFM3211T	578	L1	15.00	66	90.2	230/460	4	1
		182T	FM3211T	415	L1	14.00	63	86.5	208-230/460	4.2	1
5	1800	184T	EFM3218T	633	L1	16.50	84	90.2	230/460	6.6	1,30
		184T	FM3218T	459	L1	15.00	65	87.5	208-230/460	6.9	
7 1/2	1800	213T	EFM3311T	931	L1	16.32	111	91.7	230/460	9.6	1,30
		213T	FM3311T	651	L1	17.00	98	88.5	208-230/460	10	
10	1800	215T	EFM3313T	1,127	L1	17.45	123	91.7	230/460	12.5	1,30
		215T	FM3313T	798	L1	16.32	107	89.5	208-230/460	13.4	
15	1800	254T	EFM2513T	1,597	L1	21.69	234	93	230/460	17.7	1,30
		254T	FM2513T	1,206	L1	19.75	170	91	208-230/460	19	1
20	1800	256T	EFM2515T	2,005	L1	21.69	237	93	230/460	23.5	1,30
		256T	FM2515T	1,553	L1	22.25	220	91.7	230/460	24	30
25	1800	284T	EFM2531T	2,444	L1	23.81	332	94.1	230/460	30	1,30
		284T	FM2531T	1,882	L1	23.44	226	91.7	230/460	31	30
30	1800	286T	EFM2535T	2,673	L1	25.06	372	94.1	230/460	35	1,30
		286T	FM2535T	2,201	L1	24.94	248	92.4	230/460	36	30
40	1800	324T	EFM2539T	3,487	L1	26.69	477	94.5	230/460	46	1,30
		324T	FM2539T	2,806	L1	26.19	378	93	230/460	49	30
50	1800	326T	EFM2543T	3,848	L1	27.69	472	94.5	230/460	57	1,30
		326T	FM2543T	3,294	L1	27.19	371	93	230/460	62	30
60	1800	364T	EFM2547T	4,845	L1	30.69	782	95	230/460	68	1,30

<sup>(a)</sup> See notes on inside back flap and pages 5-6.

■ Cast Iron Frame