

# General Purpose Single Phase Open Dripproof (ODP), C-Face Footless, Capacitor Start



## APPLICATIONS:

Designed for air compressors, pumps, conveyors, blowers and general industrial equipment.

## FEATURES:

- Double Shielded Ball Bearings
- Class A or B Insulation
- Continuous Duty
- 40°C Ambient
- F1 Assembly
- Reversible Rotation

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Amps	Notes
1/4	1800	115/230	56C	D14C2PCR	\$135	DS-3F	1.35	9.9	22	4.8/2.4	25, LA
	1800	115/208-230	56C	<b>D14CA2JCR</b>	\$160	DS-3F	1.35	10.0	22	7/3.1-3.5	24
	1800	115/208-230	56C	<b>D14CM2JCR</b>	\$175	DS-3F	1.35	10.0	22	7/3.1-3.5	23
1/3	3600	115/208-230	56C	<b>D13C1JCR</b>	\$143	DS-3FMP	1.35	10.5	17	6.4/3.0-3.3	25
	3600	115/208-230	56C	<b>D13CA1JCR</b>	\$168	DS-3FMP	1.35	10.5	17	6.4/3.0-3.3	24
	1800	115/230	56C	<b>D13CA2PCR</b>	\$249	DS-3FMP	1.35	10.1	19	7.6/3.8	24
	1800	115/208-230	56C	<b>D13C2JCR</b>	\$218	DS-3F	1.35	10.4	20	6.4/3.2	25
1/2	3600	115/208-230	48	<b>D12C1JCR</b>	\$155	DS-3FMP	1.25	11.0	22	9.2/4.4-4.6	25
	3600	115/208-230	56C	<b>D12CA1JCR</b>	\$180	DS-3FMP	1.25	11.0	22	9.2/4.4-4.6	24
	1800	115/230	56C	<b>6184</b>	\$293	DS-3FMP	1.25	11.0	20	8.4/4.2	24
	1800	115/208-230	56C	<b>D12C2JCR</b>	\$256	DS-3F	1.25	10.4	20	9.0/4.3-4.5	25
	1200	115/208-230	56C	<b>D12C3JCR</b>	\$502	DS-3F	1.25	12.0	35	10.4/5.1-5.2	25
3/4	3600	115/208-230	56C	D34CA1JCR	\$225	DS-3FMP	1.25	11.4	23	10.4/5.3-5.2	24, LA
	3600	115/208-230	56C	D34CM1JCR	\$240	DS-3FMP	1.25	11.4	23	10.4/5.3-5.2	23, LA
	1800	115/230	56C	<b>D34C2PCR</b>	\$314	DS-3F	1.25	10.9	22	12.2/6.1	25
	1800	115/230	56C	<b>6186</b>	\$355	DS-3FMP	1.25	10.8	26	12.4/6.2	24, LA
	1800	115/208-230	56C	<b>D34CA2JCR</b>	\$355	DS-3F	1.25	11.0	26	11.4/5.7-5.7	24
	1200	115/230	56C	<b>6189</b>	\$560	DS-3FMP	1.25	12.6	39	11.0/5.5	25, LA
	1200	115/208-230	56C	<b>D34C3JCR</b>	\$560	DS-3F	1.25	13.0	39	10.6/5.4-5.3	25
1	3600	115/208-230	56C	<b>D1C1JCR</b>	\$235	DS-3FMP	1.25	11.4	29	14.6/6.9-7.3	25
	3600	115/208-230	56C	<b>D1CA1JCR</b>	\$260	DS-3FMP	1.25	11.4	28	14.6/6.9-7.3	24
	1800	115/230	56C	<b>6188</b>	\$362	DS-3FMP	1.25	11.0	20	13.6/6.8	24
	1800	115/208-230	56C	<b>D1C2JCR</b>	\$341	DS-3F	1.25	10.9	22	14.8/7.5-7.3	25
1-1/2	3600	115/208-230	56C	<b>D32C1JCR</b>	\$290	DS-3FMP	1.15	11.9	31	18.6/9.8-9.3	25
	3600	115/208-230	56C	<b>D32CA1JCR</b>	\$315	DS-3FMP	1.15	11.9	31	18.6/9.8-9.3	24
	1800	115/208-230	145TC	<b>D32C2J14CR</b>	\$372	DS-3F	1.15	13.0	45	19.2/10.0-9.6	25
	1800	115/208-230	56C	<b>D32C2JCR</b>	\$357	DS-3F	1.15	12.4	39	19.2/10.0-9.6	25
	1800	115/208-230	56C	<b>D32CA2JCR</b>	\$382	DS-3F	1.15	12.4	39	20.4/10.0-10.2	24
2	3600	115/208-230	145C	<b>D2C1J14CR</b>	\$375	DS-3FMP	1.15	12.4	36	22.4/12.4-11.2	25
	3600	115/208-230	56C	<b>D2CA1JCR</b>	\$400	DS-3FMP	1.15	12.4	36	22.4/12.4-11.2	24
	3600	115-208/230	56C	<b>D2C1JCR</b>	\$375	DS-3FMP	1.15	12.4	36	22.4/12.4-11.2	25
	1800	115/208-230	145TC	<b>D2C2J14CR</b>	\$509	DS-3F	1.15	13.0	40	20.0/11.3-10.0	25
	1800	115/208-230	145TC	<b>D2CA2J14CR</b>	\$534	DS-3F	1.15	14.0	40	20.0/11.3-10.0	24
	1800	115/230	182TC	<b>D2C2PC18R</b>	\$612	DS-3SP	1.15	15.8	75	25.6/12.8	25
	1800	115/208-230	56C	<b>D2CA2JCR</b>	\$534	DS-3F	1.15	14.0	40	20.0/11.3-10.0	24
	1800	115-208/230	56C	<b>D2C2JCR</b>	\$509	DS-3F	1.15	13.0	40	20.0/11.3-10.0	25
3	3600	208-230	56C	<b>D3CA1JCR</b>	\$450	DS-3FMP	1.15	13.4	41	16.3-14.7	24
	1800	115/230	184TC	<b>D3C2PC18R</b>	\$828	DS-3SP	1.15	17.8	72	33.0/16.5	25

Note 23 Manual Reset Thermal Overload Protector  
 Note 24 Automatic Reset Thermal Overload Protector

Note 25 Non-protected  
 Note LA Limited Availability