

Special Application Close Coupled Pump Single Phase Open Dripproof (ODP)



APPLICATIONS:

Designed for the specific requirements of centrifugal pumps where the pump impeller is mounted directly on the motor shaft.

FEATURES:

- Class F Insulation
- Rolled Steel Frame
- Oversized Ball Bearings w/Locked Shaft End Construction
- Reversible
- F1 Assembly Position
- Shaft Slinger On Pulley End
- Lifting Provisions 180 Frame & Up
- "JM" Shaft For Mechanical Seal
- Conversion Kits: Canopy Kits

JM Shaft

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Amps	Notes
1	1800	115/208-230	143JM	EJM104B	\$437	DS-3PO	1.15	13.8	32	14.2/7.2-7.1	25
1-1/2	1800	115/208-230	145JM	EJM154B	\$517	DS-3PO	1.15	13.8	34	16.0/8.3-8.0	18, 25
2	3600	115/208-230	145JM	EJM202B	\$576	DS-3PO	1.15	14.6	35	19.6/10.7-9.8	18, 25
	1800	115/208-230	182JM	EJM204B	\$590	DS-3PO	1.15	15.3	40	18.6/10.1-9.3	18, 25
	1800	115/230	182JM	DJ2C2P18M	\$624	DS-3PO	1.15	17.5	70	23.2/11.6	18
3	3600	115/230	182JM	DJ3C1P18M	\$690	DS-3PO	1.15	19.6	81	16.0/32.0	18
	3600	208-230	184JM	EJM302B	\$568	DS-3PO	1.15	15.3	40	14.0-13.2	18, 25
	1800	115/230	184JM	DJ3C2P18M	\$629	DS-3PO	1.15	17.5	66	38.0/19.0	18
5	3600	208-230	184JM	EJM502B	\$656	DS-3PO	1.15	16.3	45	24.0-23.7	18, 25
	3600	230	184JM	DJ5C1K18M	\$830	DS-3PO	1.15	19.6	82	19.6	18
	1800	230	184JM	DJ5C2K18M	\$794	DS-3PO	1.15	19.6	86	22.0	18
	1800	230	213JM	DJ5C2K21M	\$954	DS-3PO	1.15	20.5	105	22.0	25
7-1/2	3600	230	213JM	DJ7C1K21M	\$1,198	DS-3PO	1.15	20.5	141	30.4	25
	1800	230	215JM	DJ7C2K21M	\$1,019	DS-3PO	1.15	22.0	110	35.6	25
10	3600	230	215JM	DJ10C1K21M	\$1,406	DS-3PO	1.15	22.0	173	40	25
	1800	230	215JM	DJ10C2K21M	\$1,296	DS-3PO	1.15	22.0	115	42	25

Note 18 Incorporates Run Capacitor

Note 25 Non-protected