

BALDOR • RELIANCE®

**Jet Pump,
Three Phase, ODP**

1/2 thru 3 Hp

NEMA 56J

Applications: Residential and industrial pumps, swimming pool pumps, etc.

Features: Diecast aluminum end plates with machined steel bearing seat insert.



Hp	RPM	NEMA Frame	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
Stainless Steel Threaded Shaft, Footless											
1/3	3600	56J	JM225	198	K	11.58	23	64	230	1.6	30,80
		56J	JM3006	246	K	11.72	19	62	230/460	0.8	30
	1800	56J	JM245	209	K	11.58	26	64	230	1.6	30,80
		56J	JM3104	269	K	11.72	21	68	230/460	0.8	30
1/2	3600	56J	JM3107	260	K	11.72	22	70	230/460	1.2	30
		56J	JM325	216	K	11.58	22	70	230	2	30,80
	1800	56J	JM3108	311	K	11.85	22	74	230/460	1	30
		56J	JM345	241	K	11.58	20	72	230	2	30,80
3/4	3600	56J	JM3111	309	K	11.72	23	74	208-230/460	1.5	
		56J	JM425	226	K	11.58	23	72	230	3	30,80
	1800	56J	JM3112	343	K	12.34	26	75.5	208-230/460	1.5	
1	3600	56J	JM445	287	K	13.22	23	74	208-230	2.8	80
		56J	JM3115	343	K	12.34	26	77	230/460	1.6	30
	1800	56J	JM525	257	K	11.83	27	80	230	3	30,80
1 1/2	3600	56J	JM3116	376	K	13.22	29	78.5	208-230/460	1.7	1
		56J	JM545	293	K	13.22	31	74	208-230	3.6	80
	1800	56J	JM3120	410	K	13.22	30	74	230/460	2.2	30
2	3600	56J	JM625	276	K	12.84	32	78.5	230/460	3.6	30,80
		56J	JM3154	449	K	13.72	33	77	208-230/460	2.8	
	1800	56J	JM3155	487	K	13.72	34	82.5	230/460	2.7	30
3	3600	56J	JM3157	492	K	13.74	28	78.5	208-230/460	3.2	
		56J	JM3158	578	K	13.74	41	80	208-230/460	4	
	1800	56J	JM3161	636	K	14.62	48	82.5	208-230/460	4.2	1
Stainless Steel Threaded Shaft, Foot Mounted											
1/3	3600	56J	CJM225	199	K	11.48	21	64	230	1.6	30,80
		56J	CJM3006	254	K	11.91	20	62	230/460	0.8	30
	1800	56J	CJM245	231	K	11.58	21	70	230/460	0.7	30,80
		56J	CJM3104	294	K	11.85	22	68	230/460	0.8	30
1/2	3600	56J	CJM3107	270	K	11.72	23	70	230/460	1.2	30
		56J	CJM325	209	K	11.58	20	70	230	2	30,80
	1800	56J	CJM3108	330	K	11.72	24	74	230/460	1	30
		56J	CJM345	272	K	11.58	21	72	230/460	1	30,80
3/4	3600	56J	CJM3111	309	K	11.72	24	74	208-230/460	1.5	
		56J	CJM425	239	K	11.58	22	72	230	3	30,80
	1800	56J	CJM3112	353	K	12.34	27	75.5	208-230/460	1.5	
1	3600	56J	CJM445	286	K	11.83	24	72	230/460	1.5	30,80
		56J	CJM3115	345	K	12.34	28	77	230/460	1.6	30
	1800	56J	CJM525	266	K	11.83	28	80	230	3	30,80
1 1/2	3600	56J	CJM3120	420	K	13.22	31	81.5	230/460	2	30
2	3600	56J	CJM3155	500	K	13.72	36	82.5	230/460	2.7	30
3	3600	56J	CJM3158	592	K	13.74	39	80	208-230/460	4	

(a) See notes on inside back flap and pages 5-6.

All threaded shaft single phase motors are connected single rotation - CCW when viewing drive end.

ALL ABOVE RATINGS CAN BE UL 1081 COMPLIANT THROUGH MOD EXPRESS. SEE THE MOD EXPRESS PROGRAM SECTION IN THIS CATALOG FOR MORE DETAILS.