

# General Purpose Three Phase, Totally Enclosed Fan Cooled (TEFC) Unimount® Energy Efficient



UT, FUT

## APPLICATIONS:

Designed for pumps, fans, compressors, material handling and other general purpose applications in damp, dusty or dirty environments.

## FEATURES:

- Class F Insulation, Class B Rise at Full Load (4)
- Aluminum Frame (180-280)
- Rolled Steel Frame (56-140)
- Aluminum, End Shields with Steel Bearing Inserts
- Conduit Box Shipped Loose (180 Frame & Up Only)
- Full 50 & 60 Hertz Operating Data on Nameplate (3)
- 40°C Ambient, NEMA® Design B Performance (4)
- Conversion Kits: C&D Flanges, Canopy, Brakes (56-210 Frames)
- Full HP @ 50 Hz
- Regreasable Bearings 250 Frame & Up
- Doubled Shielded Bearings 180-280
- Suitable For Wye-Delta Start 250 Frame & Larger
- Dual Voltage Ratings Suitable For Part Winding Start (PWS) On Low Voltage
- CE Mark On Nameplate 140 Frame & Larger
- Lifting Provisions 180 Frame & Up
- Removable Base 180 Frame & Up

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Eff.	Full Load Amps	Notes
1/4	1800	208-230/460	48	TN14S2D4	\$224	DS-3FMP	1.00	9.0	17	-	1.2-1.2/0.6	28
	1800	208-220/440	56	T14S2M	\$243	DS-3F	1.00	10.5	17	-	1.4/0.7	19, LA
	1800	208-230/460	56	T14S2A	\$243	DS-3F	1.15	10.9	17	-	1.1-1.1/0.5	-
	1200	208-230/460	56	T14S3D	\$334	DS-3FMP	1.15	11.1	17	-	1.4-1.4/0.7	-
1/3	3600	208-230/460	48	TN13S1D4	\$217	DS-3FMP	1.00	8.9	17	-	1.3-1.4/0.7	28
	1800	230/460	48	TN13S2B4	\$261	DS-3FMP	1.00	9.0	19	-	1.3/0.65	28
	1800	208-220/440	56	T13S2M	\$250	DS-3F	1.35	10.5	19	-	1.5/0.75	19
	1800	230/460	56	TN13S2B	\$250	DS-3FMP	1.00	10.8	25	-	1.1/0.55	28, LA
1/2	3600	208-230/460	48	T12S1D4	\$251	DS-3FMP	1.00	10.5	19	-	1.8-1.8/0.9	-
	3600	575	56	4439	\$251	DS-3FMP	1.00	10.7	20	-	0.77	LA
	3600	208-230/460	56	T12S1A	\$251	DS-3F	1.00	10.8	20	-	2.0-2.0/1.0	-
	1800	230/460	48	T12S2B4	\$306	DS-3FMP	1.00	10.5	19	-	1.9/0.95	-
	1800	575	56	4357	\$195	DS-3FMP	1.00	10.1	22	-	0.77	-
	1800	208-230/460	56	8795	\$210	DS-3FMP	1.00	10.5	20	-	2.0/1.0	LA
	1800	208-220/440	56	T12S2M	\$310	DS-3F	1.00	11.4	21	-	2.0/1.0	19
	1800	230/460	56	TN12S2B	\$292	DS-3FMP	1.00	10.5	26	-	1.6/0.8	28
	1800	575	56	T12S2G	\$310	DS-3F	1.00	11.3	23	-	0.80	-
	1200	208-220/440	56	T12S3M	\$355	DS-3F	1.00	11.2	26	-	2.1-2.2/1.1	19, LA
	1200	208-230/460	56	T12S3A	\$355	DS-3F	1.00	10.5	23	-	2.2-2.3/1.1	-
	1200	575	56	T12S3G	\$355	DS-3F	1.00	10.5	26	-	0.85	-
3/4	3600	230/460	48	T34S1B4	\$277	DS-3FMP	1.00	10.1	22	-	2.4/1.2	-
	3600	575	56	T34S1G	\$305	DS-3F	1.00	11.3	22	-	0.95	LA
	3600	208-230/460	56	T34S1A	\$305	DS-3F	1.00	11.4	22	-	2.5-2.5/1.2	-
	1800	230/460	48	T34S2B4	\$332	DS-3FMP	1.00	11.3	22	-	3.0/1.5	-
	1800	208-220/440	56	T34S2M	\$333	DS-3F	1.15	11.9	25	-	2.7-2.8/1.4	19, LA
	1800	230/460	56	TN34S12B	\$314	DS-3FMP	1.00	12.3	28	-	2.3/1.1	28
	1800	208-230/460	56	T34S2A	\$333	DS-3F	1.25	12.5	23	-	3.0-3.0/1.5	-
	1800	575	56	T34S2G	\$333	DS-3F	1.25	12.5	25	-	1.1	37
	1200	208-230/460	143T	T34S3B14	\$414	DS-3FMP	1.25	12.5	30	75.5	3.4-3.5/1.7	-
	1200	208-220/440	56H	T34S3MH	\$414	DS-3FMP	1.25	12.8	31	-	3.0-3.0/1.5	-

Note 02 Suitable for Wye-Delta start on voltages shown  
 Note 03 60/50 Hz rated with no derate on horsepower, 230/460 volt 60 Hz ratings operate on 190/380 volt 50 Hz. 460 Volt 60 Hz ratings operate on 380 volt 50 Hz power. Full 60 Hz and 50 Hz data is displayed on N/P  
 Note 04 On 60 Hertz Sine Wave power  
 Note 16 Motors marked 208-230/460 volts may not meet all NEMA® (MG-1) performance standards when operated at 208 volts

Note 19 Also rated for 190/380, 220/415 volt 50 Hz at 1.0 Service Factor  
 Note 26 Does not include World Motor® features  
 Note 28 TENV Enclosure  
 Note 37 Q-3 leads for across-the-line start  
 Note LA Limited Availability  
 † All non-Emerson Electric Co. marks shown within this document are properties of their other respective owners

# General Purpose Three Phase, Totally Enclosed Fan Cooled (TEFC) Unimount® Energy Efficient



UT, FUT

## APPLICATIONS:

Designed for pumps, fans, compressors, material handling and other general purpose applications in damp, dusty or dirty environments.

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Eff.	Full Load Amps	Notes
1	3600	200	56	U1E1H	\$267	DS-3F	1.25	12.8	32	-	3.4	-
	3600	208-230/460	56	<b>U1E1D</b>	\$267	DS-3F	1.25	12.8	32	-	3.1-2.7/1.4	03
	3600	575	56	U1E1G	\$267	DS-3F	1.25	12.3	32	-	1.2	-
	1800	200	143T	<b>U1E2H</b>	\$291	DS-3FTE	1.25	12.3	35	82.5	3.4	-
	1800	208-230/460	143T	<b>U1E2D</b>	\$291	DS-3FTE	1.25	11.5	35	82.5	3.1-3.0/1.5	03
	1800	575	143T	U1E2G	\$291	DS-3FTE	1.25	12.3	35	82.5	1.2	-
	1800	575	56H	<b>4381</b>	\$275	DS-3FMP	1.15	12.7	26	-	1.4	-
	1800	208-230/460	56H	8799	\$234	DS-3FMP	1.25	12.8	29	-	3.4-3.4/1.7	LA
	1800	208-220/440	56H	<b>T1S2MH</b>	\$275	DS-3FMP	1.25	12.8	29	-	3.4-3.4/1.7	-
	1800	230/460	56H	<b>TN1S2MH</b>	\$324	DS-3FMP	1.25	12.8	32	-	3.1/1.5	28
	1800	208-230/460	56HZ	<b>T1E2DHZ</b>	\$304	DS-3FMP	1.15	12.2	28	-	4.0-3.8/1.9	-
	1200	200	145T	U1E3H	\$455	DS-3FTE	1.25	12.7	40	80	4.2	-
	1200	208-230/460	145T	<b>U1E3D</b>	\$455	DS-3FTE	1.25	16.1	40	80	3.7-3.5/1.8	03
	1200	575	145T	U1E3G	\$455	DS-3FTE	1.25	16.1	40	80	1.5	-
	1200	208-230/460	56H	<b>T1S3D</b>	\$421	DS-3FMP	1.25	16.1	32	-	4.2-4.3/2.2	-
	1200	208-230/460	56HZ	<b>T1E3DHZ</b>	\$615	DS-3FMP	1.25	12.8	32	-	4.0-4.0/2.0	-
	900	200	182T	U1E4H	\$840	DS-3FTE	1.25	12.8	60	75.5	5.2	-
900	208-230/460	182T	<b>U1E4D</b>	\$840	DS-3FTE	1.25	12.3	60	74	4.4-4.7/2.4	03	
900	575	182T	U1E4G	\$840	DS-3FTE	1.25	12.8	60	74	1.9	-	
1-1/2	3600	200	143T	U32E1H	\$378	DS-3FTE	1.25	12.8	35	82.5	4.5	-
	3600	208-230/460	143T	<b>U32E1D</b>	\$378	DS-3FTE	1.25	12.8	35	82.5	4.3-3.9/1.9	03
	3600	575	143T	U32E1G	\$378	DS-3FTE	1.25	12.8	35	82.5	1.6	-
	3600	208-230/460	56H	<b>T32S1AH</b>	\$356	DS-3F	1.00	12.7	26	80	4.7-4.5/2.2	-
	1800	200	145T	U32E2H	\$297	DS-3FTE	1.25	12.7	40	84	5.0	-
	1800	208-230/460	145T	<b>U32E2D</b>	\$297	DS-3FTE	1.25	16.1	40	84	4.6-4.4/2.2	03
	1800	575	145T	<b>U32E2G</b>	\$297	DS-3FTE	1.25	14.9	40	84	1.8	-
	1800	575	56H	8779	\$309	DS-3FMP	1.25	16.1	39	-	1.8	LA
	1800	208-230/460	56H	<b>T32S2MH</b>	\$309	DS-3FMP	1.25	16.1	34	77.0	4.9-4.8/2.4	-
	1800	208-230/460	56HZ	<b>T32E2DHZ</b>	\$312	DS-3FMP	1.15	13.2	34	84	5.0-4.9/2.5	-
	1200	200	182T	U32E3H	\$525	DS-3FTE	1.25	16.9	64	85.5	6.1	-
	1200	208-230/460	182T	<b>S32E3D</b>	\$525	DS-3FTE	1.25	16.9	64	85.5	5.5-5.4/2.7	04,16,26
	1200	208-230/460	182T	<b>U32E3D</b>	\$525	DS-3FTE	1.25	16.9	64	85.5	5.3-5.3/2.7	03
	1200	575	182T	U32E3G	\$525	DS-3FTE	1.25	12.8	64	85.5	2.1	-
	1200	208-230/460	56	<b>T32S3AH</b>	\$483	DS-3FMP	1.25	12.8	41	-	5.4-5.3/2.6	-
	900	200	184T	U32E4H	\$994	DS-3FTE	1.25	12.3	70	78.5	7.4	-
	900	208-230/460	184T	<b>U32E4D</b>	\$994	DS-3FTE	1.25	12.3	70	78.5	6.2-6.6/3.3	03
900	575	184T	U32E4G	\$994	DS-3FTE	1.25	13.1	70	78.5	2.6	-	
2	3600	200	145T	U2E1H	\$435	DS-3FTE	1.25	12.8	40	84	5.8	-
	3600	208-230/460	145T	<b>U2E1D</b>	\$435	DS-3FTE	1.25	12.8	40	84	5.6-5/2.5	03
	3600	575	145T	U2E1G	\$435	DS-3FTE	1.25	12.8	40	84	2.0	-

Note 02 Suitable for Wye-Delta start on voltages shown  
 Note 03 60/50 Hz rated with no derate on horsepower, 230/460 volt 60 Hz ratings operate on 190/380 volt 50 Hz. 460 Volt 60 Hz ratings operate on 380 volt 50 Hz power. Full 60 Hz and 50 Hz data is displayed on N/P  
 Note 04 On 60 Hertz Sine Wave power  
 Note 16 Motors marked 208-230/460 volts may not meet all NEMA® (MG-1) performance standards when operated at 208 volts

Note 19 Also rated for 190/380, 220/415 volt 50 Hz at 1.0 Service Factor  
 Note 26 Does not include World Motor® features  
 Note 28 TENV Enclosure  
 Note 37 Q-3 leads for across-the-line start  
 Note LA Limited Availability  
 † All non-Emerson Electric Co. marks shown within this document are properties of their other respective owners

GEN. PURPOSE SINGLE PHASE  
 GEN. PURPOSE THREE PHASE  
 SEVERE DUTY  
 HAZARDOUS LOCATION  
 C-FACE SINGLE & THREE PHASE  
 MULTI-SPEED THREE PHASE  
 INVERTER DUTY  
 VECTOR DUTY  
 DRIVES  
 BRAKE MOTORS  
 U FRAME MOTORS  
 DIRECT CURRENT (DC)

# General Purpose Three Phase, Totally Enclosed Fan Cooled (TEFC) Unimount® Energy Efficient



UT, FUT

## APPLICATIONS:

Designed for pumps, fans, compressors, material handling and other general purpose applications in damp, dusty or dirty environments.

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Eff.	Full Load Amps	Notes
2	3600	575	56H	<b>4455</b>	\$400	DS-3FMP	1.00	12.8	31	0	2.3	-
	3600	208-230/460	56H	<b>T2S1AH</b>	\$400	DS-3F	1.00	13.2	33	80	6.0-5.4/2.7	-
	3600	208-230/460	56HZ	<b>T2E1AHZ</b>	\$435	DS-3F	1.00	13.2	32	84	6.3-6.1/3.1	-
	1800	200	145T	<b>U2E2H</b>	\$313	DS-3FTE	1.25	16.9	45	84	6.8	-
	1800	208-230/460	145T	<b>U2E2D</b>	\$313	DS-3FTE	1.25	15.9	45	84	5.8-5.7/2.8	03
	1800	575	145T	<b>U2E2G</b>	\$313	DS-3FTE	1.25	16.9	45	84	2.4	-
	1800	208-220/440	56H	<b>T2S2MH</b>	\$334	DS-3FMP	1.25	16.9	36	80.0	6.2-6.2/3.1	-
	1800	575	56H	<b>T2S1G</b>	\$400	DS-3F	1.25	18.6	31	80	2.3	-
	1800	208-230/460	56HZ	<b>4342</b>	\$350	DS-3FMP	1.25	18.6	36	84	6.0/3.0	-
	1800	575	56HZ	4422	\$350	DS-3FMP	1.25	18.6	36	0	2.4	LA
	1200	200	184T	U2E3H	\$565	DS-3FTE	1.25	13.8	74	86.5	7.7	-
	1200	208-230/460	184T	<b>S2E3D</b>	\$565	DS-3FTE	1.25	13.8	74	86.5	7.0-6.8/3.4	04, 16, 26
	1200	208-230/460	184T	<b>U2E3D</b>	\$565	DS-3FTE	1.25	16.1	74	86.5	7.0-6.8/3.4	03
	1200	575	184T	U2E3G	\$565	DS-3FTE	1.25	14.9	74	86.5	2.7	-
	900	200	213T	U2E4H	\$1,262	DS-3FTE	1.25	16.1	90	82.5	8.7	-
	900	208-230/460	213T	U2E4D	\$1,262	DS-3FTE	1.25	16.1	90	82.5	7.9-7.6/3.8	03
900	575	213T	U2E4G	\$1,262	DS-3FTE	1.25	14.2	90	82.5	3.0	-	
3	3600	200	145T	U3E1HF	\$479	DS-3FTE	1.25	16.1	53	85.5	8.3	-
	3600	208-230/460	145T	<b>U3E1DF</b>	\$479	DS-3FTE	1.25	14.9	53	85.5	8.2-7.2/3.6	03
	3600	575	145T	U3E1GF	\$479	DS-3FTE	1.25	16.1	53	85.5	2.9	-
	3600	200	182T	U3E1H	\$531	DS-3FTE	1.25	16.1	60	85.5	9.2	-
	3600	208-230/460	182T	<b>S3E1D</b>	\$531	DS-3FTE	1.25	18.6	50	85.5	8.6-8/4.0	04, 16, 26
	3600	208-230/460	182T	<b>U3E1D</b>	\$531	DS-3FTE	1.25	18.9	60	85.5	8.7-8.0/4.0	03
	3600	575	182T	U3E1G	\$531	DS-3FTE	1.25	18.6	60	85.5	3.2	-
	3600	208-230/460	56HZ	<b>U3E1AHZ</b>	\$499	DS-3F	1.25	18.6	45	86	8.5-7.3/3.6	-
	1800	200	182T	<b>U3E2H</b>	\$369	DS-3FTE	1.25	20.1	60	87.5	9.1	-
	1800	208-230/460	182T	<b>S3E2D</b>	\$369	DS-3FTE	1.25	20.1	55	87.5	8.4	04, 16, 26
	1800	208-230/460	182T	<b>U3E2D</b>	\$369	DS-3FTE	1.25	20.1	60	87.5	8.6-8.1/4.1	03
	1800	575	182T	<b>U3E2G</b>	\$369	DS-3FTE	1.25	15.9	60	87.5	3.2	-
	1200	200	213T	U3E3H	\$712	DS-3FTE	1.25	16.1	105	87.5	10.4	-
	1200	208-230/460	213T	<b>S3E3D</b>	\$712	DS-3FTE	1.25	16.9	130	87.5	9.7-9.1/4.5	04, 16, 26
	1200	208-230/460	213T	<b>U3E3D</b>	\$712	DS-3FTE	1.25	16.9	105	87.5	9.8-9.3/4.6	03
	1200	575	213T	U3E3G	\$712	DS-3FTE	1.25	15.9	105	87.5	3.6	-
	900	200	215T	U3E4H	\$1,379	DS-3FTE	1.25	16.9	125	84	12.8	-
	900	208-230/460	215T	<b>U3E4D</b>	\$1,379	DS-3FTE	1.25	16.9	125	84	11.7-11.1/5.5	03
	900	575	215T	U3E4G	\$1,379	DS-3FTE	1.25	20.1	125	84	4.5	-
5	3600	200	184T	U5E1H	\$611	DS-3FTE	1.25	18.9	70	87.5	14.2	-
	3600	208-230/460	184T	<b>S5E1D</b>	\$611	DS-3FTE	1.25	20.1	65	87.5	13.7-12.3/6.1	04, 16, 26
	3600	208-230/460	184T	<b>U5E1D</b>	\$611	DS-3FTE	1.25	20.1	70	87.5	13.8-12.3/6.1	03
	3600	575	184T	<b>U5E1G</b>	\$611	DS-3FTE	1.25	23.9	70	87.5	4.9	-

Note 02 Suitable for Wye-Delta start on voltages shown  
 Note 03 60/50 Hz rated with no derate on horsepower, 230/460 volt 60 Hz ratings operate on 190/380 volt 50 Hz. 460 Volt 60 Hz ratings operate on 380 volt 50 Hz power. Full 60 Hz and 50 Hz data is displayed on N/P  
 Note 04 On 60 Hertz Sine Wave power  
 Note 16 Motors marked 208-230/460 volts may not meet all NEMA® (MG-1) performance standards when operated at 208 volts

Note 19 Also rated for 190/380, 220/415 volt 50 Hz at 1.0 Service Factor  
 Note 26 Does not include World Motor® features  
 Note 28 TENV Enclosure  
 Note 37 Q-3 leads for across-the-line start  
 Note LA Limited Availability  
 † All non-Emerson Electric Co. marks shown within this document are properties of their other respective owners

# General Purpose Three Phase, Totally Enclosed Fan Cooled (TEFC) Unimount® Energy Efficient



UT, FUT

## APPLICATIONS:

Designed for pumps, fans, compressors, material handling and other general purpose applications in damp, dusty or dirty environments.

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Eff.	Full Load Amps	Notes
5	1800	200	184T	U5E2H	\$425	DS-3FTE	1.25	23.9	70	87.5	14.4	-
	1800	208-230/460	184T	S5E2D	\$425	DS-3FTE	1.25	23.9	65	86.5	14.2-12.8/6.4	04,16,26
	1800	208-230/460	184T	U5E2D	\$425	DS-3FTE	1.25	16.9	60	87.5	14.1-13/6.5	03
	1800	575	184T	U5E2G	\$425	DS-3FTE	1.25	18.6	70	87.5	5.1	-
	1200	200	215T	U5E3H	\$857	DS-3FTE	1.25	18.9	135	87.5	16.5	-
	1200	208-230/460	215T	S5E3D	\$857	DS-3FTE	1.25	18.6	115	87.5	15.6-14.5/7.2	04,16,26
	1200	208-230/460	215T	U5E3D	\$857	DS-3FTE	1.25	18.6	135	87.5	15.6-14.5/7.3	03
	1200	575	215T	U5E3G	\$857	DS-3FTE	1.25	18.6	135	87.5	5.8	-
	900	200	254T	U5E4H	\$1,705	DS-3FTE	1.25	18.9	180	85.5	17.3	02
	900	208-230/460	254T	U5E4D	\$1,705	DS-3FTE	1.25	18.6	180	85.5	16.4-15.4/7.7	02, 03
900	575	254T	U5E4G	\$1,705	DS-3FTE	1.25	18.6	180	86.5	6.1	02	
7-1/2	3600	208-230/460	184T	U7E1A	\$900	DS-3FTE	1.25	23.9	70	88.5	20.4-17.9/9.0	-
	3600	200	213T	U7E1H	\$900	DS-3FTE	1.25	23.9	105	88.5	21.2	-
	3600	208-230/460	213T	S7E1D	\$900	DS-3FTE	1.25	23.9	85	88.5	20.6-18.4/9.2	04,16,26
	3600	208-230/460	213T	U7E1D	\$900	DS-3FTE	1.25	25.6	105	88.5	20.4-18.4/9.2	03
	3600	575	213T	U7E1G	\$900	DS-3FTE	1.25	25.6	105	88.5	7.4	-
	1800	200	213T	U7E2H	\$543	DS-3FTE	1.25	25.6	105	89.5	21.5	-
	1800	208-230/460	213T	S7E2D	\$543	DS-3FTE	1.25	20.1	90	91	20.1-18.3/9.1	04,16,26
	1800	208-230/460	213T	U7E2D	\$543	DS-3FTE	1.25	18.9	105	89.5	20.8-18.9/9.4	03
	1800	575	213T	U7E2G	\$543	DS-3FTE	1.25	20.1	105	89.5	7.5	-
	1200	200	254T	U7E3H	\$1,215	DS-3FTE	1.25	20.1	180	89.5	21.8	-
	1200	208-230/460	254T	U7E3D	\$1,215	DS-3FTE	1.25	20.1	180	89.5	20.8-18.8/9.4	02, 03
	1200	575	254T	U7E3G	\$1,215	DS-3FTE	1.25	18.9	180	89.5	7.5	02
	900	200	256T	U7E4H	\$2,299	DS-3FTE	1.25	20.1	300	86.5	25.4	02
	900	208-230/460	256T	U7E4D	\$2,299	DS-3FTE	1.25	20.1	300	86.5	23.8-22.2/11.1	02, 03
	900	575	256T	U7E4G	\$2,299	DS-3FTE	1.25	25.6	300	86.5	8.8	02
	10	3600	200	215T	U10E1H	\$943	DS-3FTE	1.25	25.6	120	89.5	27.3
3600		208-230/460	215T	S10E1D	\$943	DS-3FTE	1.25	25.6	110	89.5	26.5-23.5/11.7	04,16,26
3600		208-230/460	215T	U10E1D	\$943	DS-3FTE	1.25	21.6	120	89.5	26.7-23.8/11.9	03
3600		575	215T	U10E1G	\$943	DS-3FTE	1.25	23.9	120	89.5	9.4	-
1800		200	215T	U10E2H	\$661	DS-3FTE	1.25	23.9	135	89.5	28.4	-
1800		208-230/460	215T	S10E2D	\$661	DS-3FTE	1.25	23.9	120	91	26.6-23.8/11.9	04,16,26
1800		208-230/460	215T	U10E2D	\$661	DS-3FTE	1.25	23.9	105	89.5	27.5-24.8/12.4	03
1800		575	215T	U10E2G	\$661	DS-3FTE	1.25	23.9	135	89.5	9.9	-
1200		200	256T	U10E3H	\$1,352	DS-3FTE	1.25	23.9	210	89.5	28.8	02
1200		208-230/460	256T	U10E3D	\$1,352	DS-3FTE	1.25	25.6	210	89.5	27.5-25/12.5	02, 03
1200		575	256T	U10E3G	\$1,352	DS-3FTE	1.25	25.6	210	89.5	10.0	02
15		3600	208-230/460	215T	U15E1AF	\$1,198	DS-3FTE	1.25	25.6	140	90.2	40-35/17.7
	3600	200	254T	U15E1H	\$1,418	DS-3FTE	1.25	25.6	190	90.2	40	02
	3600	208-230/460	254T	U15E1D	\$1,418	DS-3FTE	1.25	25.6	190	90.2	40-35/17.7	02, 03

Note 02 Suitable for Wye-Delta start on voltages shown  
 Note 03 60/50 Hz rated with no derate on horsepower, 230/460 volt 60 Hz ratings operate on 190/380 volt 50 Hz. 460 Volt 60 Hz ratings operate on 380 volt 50 Hz power. Full 60 Hz and 50 Hz data is displayed on N/P  
 Note 04 On 60 Hertz Sine Wave power  
 Note 16 Motors marked 208-230/460 volts may not meet all NEMA® (MG-1) performance standards when operated at 208 volts

Note 19 Also rated for 190/380, 220/415 volt 50 Hz at 1.0 Service Factor  
 Note 26 Does not include World Motor® features  
 Note 28 TENV Enclosure  
 Note 37 Q-3 leads for across-the-line start  
 Note LA Limited Availability  
 † All non-Emerson Electric Co. marks shown within this document are properties of their other respective owners

# General Purpose Three Phase, Totally Enclosed Fan Cooled (TEFC) Unimount® Energy Efficient



UT, FUT

## APPLICATIONS:

Designed for pumps, fans, compressors, material handling and other general purpose applications in damp, dusty or dirty environments.

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Eff.	Full Load Amps	Notes
15	3600	575	254T	U15E1G	\$1,418	DS-3FTE	1.25	25.6	190	90.2	14.0	02
	1800	200	254T	<b>U15E2H</b>	\$1,102	DS-3FTE	1.25	28.3	190	91	43	02
	1800	208-230/460	254T	<b>U15E2D</b>	\$1,102	DS-3FTE	1.25	28.3	190	91	41-38/18.9	02, 03
	1800	575	254T	<b>U15E2G</b>	\$1,102	DS-3FTE	1.25	28.3	190	91	14.7	02
20	3600	200	256T	U20E1H	\$1,558	DS-3FTE	1.25	26.9	210	90.2	53	02
	3600	208-230/460	256T	<b>U20E1D</b>	\$1,558	DS-3FTE	1.25	26.9	210	90.2	54-47/23.5	02, 03
	3600	575	256T	U20E1G	\$1,558	DS-3FTE	1.25	26.9	210	90.2	18.7	02
	1800	200	256T	<b>U20E2H</b>	\$1,332	DS-3FTE	1.25	28.3	230	91	56	02
	1800	208-230/460	256T	<b>U20E2D</b>	\$1,332	DS-3FTE	1.25	28.3	230	91	55-51/25.7	02, 03
	1800	575	256T	<b>U20E2G</b>	\$1,332	DS-3FTE	1.25	28.3	230	91	19.5	02
25	3600	200	284T	U25E1H	\$1,982	DS-3FTE	1.25	26.9	250	91	66	02
	3600	208-230/460	284T	<b>U25E1D</b>	\$1,982	DS-3FTE	1.25	26.9	250	91	65-57/28.7	02, 03
	3600	575	284T	U25E1G	\$1,982	DS-3FTE	1.25	26.9	250	91	22.9	02
	3600	200	284TS	U25E1HS	\$1,982	DS-3FTE	1.25	28.3	250	91	66	02
	3600	208-230/460	284TS	<b>U25E1DS</b>	\$1,982	DS-3FTE	1.25	28.3	250	91	65-57/28.7	02, 03
	3600	575	284TS	U25E1GS	\$1,982	DS-3FTE	1.25	28.3	250	91	22.9	02
	1800	200	284T	U25E2H	\$1,649	DS-3FTE	1.25	26.9	290	92.4	69	02
	1800	208-230/460	284T	<b>U25E2D</b>	\$1,649	DS-3FTE	1.25	26.9	290	92.4	67-59/29.6	02, 03
	1800	575	284T	<b>U25E2G</b>	\$1,649	DS-3FTE	1.25	26.9	290	92.4	23.7	02
	1800	200	284TS	U25E2HS	\$1,649	DS-3FTE	1.25	9.0	290	92.4	69	02
	1800	208-230/460	284TS	U25E2DS	\$1,649	DS-3FTE	1.25	10.5	290	92.4	67-59/29.6	02, 03
	1800	575	284TS	U25E2GS	\$1,649	DS-3FTE	1.25		290	92.4	23.7	02
30	1800	200	286T	U30E2H	\$1,947	DS-3FTE	1.25	11.1	325	92.4	82	02
	1800	208-230/460	286T	<b>U30E2D</b>	\$1,947	DS-3FTE	1.25	8.9	325	92.4	80-72/36	02, 03
	1800	575	286T	<b>U30E2G</b>	\$1,947	DS-3FTE	1.25	9.0	325	92.4	28.6	02
	1800	200	286TS	U30E2HS	\$1,947	DS-3FTE	1.25	10.5	325	92.4	82	02
	1800	208-230/460	286TS	<b>U30E2DS</b>	\$1,947	DS-3FTE	1.25	10.8	325	92.4	80-72/36	02, 03
	1800	575	286TS	U30E2GS	\$1,947	DS-3FTE	1.25	10.5	325	92.4	28.6	02

Note 02 Suitable for Wye-Delta start on voltages shown  
 Note 03 60/50 Hz rated with no derate on horsepower, 230/460 volt 60 Hz ratings operate on 190/380 volt 50 Hz. 460 Volt 60 Hz ratings operate on 380 volt 50 Hz power. Full 60 Hz and 50 Hz data is displayed on N/P  
 Note 04 On 60 Hertz Sine Wave power  
 Note 16 Motors marked 208-230/460 volts may not meet all NEMA® (MG-1) performance standards when operated at 208 volts

Note 19 Also rated for 190/380, 220/415 volt 50 Hz at 1.0 Service Factor  
 Note 26 Does not include World Motor® features  
 Note 28 TENV Enclosure  
 Note 37 Q-3 leads for across-the-line start  
 Note LA Limited Availability  
 † All non-Emerson Electric Co. marks shown within this document are properties of their other respective owners