

Split Phase Belted Fan & Blower

Totally Enclosed Air Over (TEAO), Resilient Base

APPLICATIONS:

Designed for use on belted fans and blowers in dusty environments.

FEATURES:

- Extended Mounting Stud on Shaft Endshields
- Ball Bearings Unless Otherwise Noted
- 448Y Frame have Slots to Match 48 & 56 Frame
- Reversible Rotation
- Automatic Reset Thermal Overload Protector
- Discount Symbol: DS-3HAC

Single Speed

HP	RPM	Volts	NEMA Frame	Catalog Number	List Price	SF	"C" Dim. (inches)	Ship Wgt.	Full Load Amps	Notes
1/6	1200	115	56Z	4753	\$206	1.00	8.9	18	4.6	25, 61
1/4	1800	115	48Y	4754	\$144	1.00	8.9	16	4.8	61
	1800	115	48	4755	\$194	1.00	8.9	16	4.8	
	1800	115/230	56	4758	\$215	1.35	9.8	18	4.4/2.2	SD
	1800	115	56Z	4759	\$150	1.00	8.9	16	4.7	61
	1800	115	56Z	4761	\$144	1.00	8.9	16	4.7	25, 61
	1725	115	48	4760	\$138	1.00		16	4.3	
	1725	115	48	4757	\$151	1.00		16	4.5	
	1200	115	56Z	4763	\$274	1.00	9.4	21	6.0	61
	1200	115	56Z	4764	\$255	1.00	9.4	21	6.0	25, 61
1/3	1800	115	48Y	4765	\$179	1.00	9.4	19	5.2	61
	1800	115/230	56	4767	\$241	1.35	9.8	20	5.2/2.6	SD
	1800	115	56Z	4768	\$178	1.00	8.9	18	5.5	61
	1800	115	56Z	4770	\$191	1.00	8.9	18	5.5	25
	1800	230	56Z	4769	\$181	1.00	8.9	20	2.8	61
	1800	230	56Z	4771	\$193	1.00	8.9	20	2.8	25, 61
	1725	115	48	4766	\$193	1.00		19	5.2	
1/2	1800	115	56	4772	\$291	1.00	10.7	24	6.5	SD
	1800	115	56	4773	\$238	1.00	10.8	24	6.5	61, SD
	1800	115	56	4774	\$258	1.00	10.3	26	7.0	25, SD
	1800	230	56	4776	\$278	1.00	10.3	26	3.6	25, 61, SD

Two Speed

HP	RPM	Volts	Catalog Number	List Price	Amps	Shaft Length	Shaft Dia.	"C" Dim. (inches)	Ship Wgt.	Notes
1/4 (1/12)	1800/1200 (2)	115	4778	\$206	4.7/2.5	1.5	0.5	9.7	19	LA
1/3 (1/9)	1800/1200 (2)	115	4780	\$265	6.4/4.5	1.5	0.5	9	23	LA

Note 25 Non-protected
Note 61 Sleeve Bearings

Note SD Shaft Dimension is 0.625 x 1.875