

Special Application Commercial Door Three Phase Totally Enclosed Fan Cooled (TEFC) Rigid Base



APPLICATIONS:

Designed for commercial door openers and most medium start reversing applications.

FEATURES:

- 40°C Ambient
- 1.0 Service Factor
- Rigid Base
- Reversible Rotation
- 208/230-460 Volt, 60 Hertz
- Permanent Lubricated Ball Bearings
- Continuous Duty
- Class B Insulation

| HP | RPM | Voltage | Frame | Catalog Number | List | Discount Symbol | SF | "C" Dim. (inches) | Ship Wt. (lbs.) | Full Load Amps | Notes |
|-----|------|-------------|-------|----------------|-------|-----------------|------|-------------------|-----------------|----------------|-------|
| 1/2 | 1800 | 208-230/460 | 56 | T12SR2J | \$160 | DS-3FMP | 1.00 | 12.0 | 17 | 2.1-2.2/1.1 | |
| 3/4 | 1800 | 208-230/460 | 56 | T34SR2J | \$170 | DS-3FMP | 1.00 | 12.0 | 18 | 2.4-2.9/1.5 | |
| 1 | 1800 | 208-230/460 | 56 | T1SR2J | \$180 | DS-3FMP | 1.00 | 11.9 | 22 | 3.3-3.3/1.7 | |