

# General Purpose Single Phase Open Dripproof (ODP), Resilient Base, Split Phase



## APPLICATIONS:

Designed for commercial and industrial ventilation systems.

## FEATURES:

- 40°C Ambient, 60 Hertz
- Reversible Rotation
- Continuous Duty
- Class A or B Insulation
- 56Z has 1/2" X 1-1/2" Shaft
- Ball Bearing (except where noted)

## Single Speed

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Amps	Notes
1/12	1800	115	42	D0112B2N4Z9	\$130	DS-3FMP	1.40	7.4	9.8	3	25
1/6	1800	115/208-230	48	D16BA2J49	\$200	DS-3FMP	1.35	8.4	13	3.6/1.7-1.8	24
	1800	115	48Z	D16B2N4Z9	\$98	DS-3FMP	1.35	9.2	15	3.5	20, 25
	1200	115	48Z	D16B3N4Z9	\$159	DS-3FMP	1.35	10.4	17	4	20, 25
	1200	115	56Z	D16B3NZA9	\$147	DS-3FMP	1.35	8.8	18	4.6	25, 61
	900	115	56	D16B4N9	\$265	DS-3FMP	1.35	8.9	29	5.9	21, 25
1/4	1800	115	48	D14B2N4A9	\$83	DS-3FMP	1.35	8.4	14	5.1	20, 25, 61
	1800	115	48	D14B2N4A9S	\$82	DS-3FMP	1.00	9.4	14	5.4	20, 25, 61
	1800	230	48	D14B2K4A9	\$92	DS-3FMP	1.35	8.9	15	2.2	25, 61
	1800	115	48Z	D14B2N4Z9	\$108	DS-3FMP	1.35	8.8	14	5.1	20, 25
	1800	115	56Z	D14B2NZA9	\$100	DS-3FMP	1.00	9.4	15	5.4	20, 25, 61
	1800	115	56Z	D14BA2N29	\$118	DS-3F	1.35	9.8	20	5.1/2.5	15, 24
	1200	115	56	D14B3N9	\$189	DS-3FMP	1.35	9.7	25	5.4	21, 25
	900	115	56	D14B4N9	\$324	DS-3FMP	1.25	11.8	32	6.9	21, 25
	1/3	3600	115	48	D13B1N49	\$114	DS-3FMP	1.35	9.9	15	5.3
1800		115	48	D13B2N4A9	\$88	DS-3FMP	1.00	9.4	15	6.8	25, 61
1800		230	48	D13B2K4A9	\$97	DS-3FMP	1.00	9.4	15	3	25, 61
1800		115	48Z	D13B2N4Z9	\$120	DS-3FMP	1.35	9.2	16	6.5	20, 25
1800		115	56Z	2876	\$147	DS-3FMP	1.00	9.4	18	6	24
1800		115	56Z	D13B2NZA9	\$100	DS-3FMP	1.00	9.8	15	6	25, 61
1800		115	56Z	D13BA2N29	\$138	DS-3F	1.35	9.8	25	6.1/3.1	15, 24
1200		115/230	56	D13B3P9	\$220	DS-3FMP	1.35	9.8	25	7.5/3.8	21, 25
1/2		1800	115	48	D12B2N49	\$156	DS-3FMP	1.00	9.7	18	8.8
	1800	115	56	6737	\$183	DS-3FMP	1.00	9.8	17	8.6	24
	1800	115	56	D12B2NA9	\$140	DS-3FMP	1.00	9.7	21	8.6	25, 61
	1800	230	56	D12B2K9	\$148	DS-3FMP	1.00	9.2	21	4.6	25
	1800	115	56Z	D12B2NZA9	\$129	DS-3FMP	1.00	9.2	18	8.1	25, 61
	3/4	1800	115	56	D34B2N9	\$171	DS-3FMP	1.00	9.8	21	11

Note 15 Split Phase, sleeve bearings with 48/56 Frame: 48 Frame Motor diameter 3.5" Shaft Height, 0.5" Shaft Diameter with flat, includes shaft adaptor for conversion to 5/8" Shaft  
 Note 20 Stud Extensions in 3 5/8" Square Pattern

Note 21 Stud Extensions in 4 3/16" Square Pattern  
 Note 24 Automatic Reset Thermal Overload Protector  
 Note 25 Non-protected  
 Note 61 Sleeve Bearings (have all angle thrust system)