

For Simple Tank Cleaning

LKRRK Spray Balls

Application


The LKRRK is a fixed spray ball used for cleaning storage tanks in the food and beverage industries. Fixed spray balls are used for less demanding cleaning duties.

Materials

	LKRRK
Housing and sprayhead assembly:	AISI 316L
Finish:	Bright

Spray pattern for LKRRK

The 64 mm spray ball is available with 2 mm holes. The 94 mm spray ball is available with 2 mm or 3 mm holes. (See capacity diagrams).



F-version

T-version

B-version



LKRRK Spray Balls.

Connections LKRRK

Type LKRRK 64: ISO tube: 25 mm.
DIN tube: DN25 - pipe range 1 and 2.


Type LKRRK 94: ISO tube: 51 mm.
DIN tube: DN50 - pipe range 1 and 2.

OD = Outside diameter.

ID = Inside diameter.

Dimensions (mm) LKRRK


Size	64	94
A	58	77.5
B	17.5	22.5
ISO tube		
OD/ID/t	28.5/25.5/1.5	54.4/51.4/1.5
DIN tube		
OD/ID/t	32.5/28.5/2	54.4/52.4/1
Pipe range 1		
DIN tube		
OD/ID/t	34.2/29.5/2.35	57.4/53.4/2
Pipe range 2		
Weight (kg)	0.2	0.3




TD 510-001

Dimensions LKRRK.


Cleaning range of 2 mm spray holes - LKRK




Cleaning range of 3 mm spray holes - LKRK




Pressure drop/capacity diagrams - LKRK



Type LKRK 64 with 2 mm holes:
bottom drilled, top drilled, fully drilled



Type LKRK 94 with 2 mm holes, 51 mm (DN 50) tube:
bottom drilled, top drilled, fully drilled



Type LKRK 94 with 3 mm holes, 51 mm (DN 50) tube:
bottom drilled, top drilled, fully drilled

Ordering

Please state the following when ordering:

- Type and size.
- Spray pattern.
- Type of connection.