

Close-Coupled Pump, Three Phase, TEFC and ODP, C-Face

Hp	RPM	NEMA Frame	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
Open Drip Proof, Foot Mounted (continued)											
10	3600	213JM	EJMM3312T	1,330	L1	19.31	136	91.7	230/460	11.5	1,30
	1800	215JM	EJMM3313T	1,311	L1	19.31	163	91.7	230/460	12.5	1,30
15	3600	215JM	EJMM3314T	1,712	L1	19.31	165	91.7	230/460	17	1,30
	1800	254JM	EJMM2513T	1,939	L1	23.19	234	93	230/460	17.7	1,30
20	3600	254JM	EJMM2514T	2,155	L1	23.19	186	92.4	230/460	22.5	1,30
	1800	256JM	EJMM2515T	2,322	L1	23.19	237	93	230/460	23.5	1,30
25	3600	256JM	EJMM2516T	2,555	L1	23.19	242	93	230/460	28	1,30
30	3600	284JM	EJMM2534T	3,248	L1	24.69	330	93.6	230/460	34	1
40	3600	286JM	EJMM2538T	3,911	L1	25.94	377	94.1	230/460	45	1
50	3600	324JM	EJMM2542T	4,409	L1	27.44	447	94.1	230/460	55	1
Open Drip Proof, Footless											
1	1800	143JM	VEJMM3116T	545	L1	15.43	40	86.5	208-230/460	1.4	1
1 1/2	1800	145JM	VEJMM3154T	585	L1	16.31	49	86.5	208-230/460	2	1
2	1800	145JM	VEJMM3157T	640	L1	16.31	50	86.5	208-230/460	2.7	1
3	1800	182JM	VEJMM3211T	702	L1	18.06	74	90.2	230/460	4	1,30
5	1800	184JM	VEJMM3218T	795	L1	18.06	87	90.2	230/460	6.6	1,30
7 1/2	1800	213JM	VEJMM3311T	1,199	L1	19.78	119	91.7	230/460	9.6	1,30
10	1800	215JM	VEJMM3313T	1,298	L1	22.41	158	92.4	208-230/460	12.5	1

(a) See notes on inside back flap and pages 5-6.

■ Cast Iron Frame