


General Purpose Single Phase Open Dripproof (ODP), Resilient Base, Split Phase



APPLICATIONS:

Designed for commercial and industrial ventilation systems.

FEATURES:

- 40°C Ambient, 60 Hertz
- Reversible Rotation
- Continuous Duty
- Class A or B Insulation
- Sleeve Bearings Have All Angle Thrust System
- 56Z has 1/2" X 1-1/2" Shaft

Two Speed

HP (HP-Low)	RPM/RPM-Low (# Wdgs)	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Amps	Notes
1/6 (1/18)	1800/1200 (2)	115	48	D16B10N4A9	\$111	DS-3FMP	1.35	9.1	15	3.9/2.8	25
	1800/1200 (2)	115	48Z	D16B10N4Z9	\$125	DS-3FMP	1.35	9.8	17	3.9/2.8	20, 25
1/4 (1/8)	1800/1200 (2)	115	48Y	D14B10N4A9	\$134	DS-3FMP	1.00	10.4	18	5.2/4.2	25
1/4 (1/12)	1800/1200 (2)	115	48Z	D14B10N4Z9	\$158	DS-3FMP	1.35	9.9	17	4.7/2.2	20, 25
1/4 (1/8)	1800/1200 (2)	115	56Z	D14B10NZA9	\$134	DS-3FMP	1.00	8.9	18	5.2/3.6	25
1/4 (1/10)	1200/900 (2)	115	56	D14B34N9	\$279	DS-3FMP	1.35	11.8	29	4.9/3.3	25, LA
1/3 (1/9)	1800/1200 (2)	115	48	D13B10N4A9	\$133	DS-3FMP	1.00	10.4	19	6.4/4.0	20, 25
	1800/1200 (2)	115	56	D13B10N9	\$189	DS-3FMP	1.35	9.2	20	6.8/4.5	21, 25
	1800/1200 (2)	115	56Z	3053	\$190	DS-3FMP	1.00	10.4	19	7.1	25
	1800/1200 (2)	115	56Z	D13B10NZA9	\$147	DS-3FMP	1.00	8.9	19.8	6.8/4.5	25
1/2 (1/6)	1800/1200 (2)	115	56	3306	\$244	DS-3FMP	1.00	10.8	26	9.2	25
	1800/1200 (2)	115	56	D12B10N9	\$228	DS-3FMP	1.25	10.8	23	8.2/4.1	21, 25
1/2 (1/4)	1800/1200 (2)	115	56	D12B10NA9	\$190	DS-3FMP	1.00	10.8	23	9.2/6.0	25
1/2 (1/6)	1800/1200 (2)	230	56	D12B10K9	\$237	DS-3FMP	1.25	10.8	23	5.0/3.1	21, 25
1/2 (1/4)	1800/1200 (2)	230	56	D12B10KA9	\$198	DS-3FMP	1.00	10.8	23	4.6/3.0	25

Note 20 Stud Extensions in 3 5/8" Square Pattern
 Note 21 Stud Extensions in 4 3/16" Square Pattern

Note 25 Non-protected
 Note LA Limited Availability