

Three Phase, Open Drip Proof, Foot Mounted

| Hp | RPM | NEMA Frame | Catalog Number | List Price | Mult. Sym. | "C" Dim. | Aprx. Wt. (lb) | Full Load Efficiency | Voltage | Full Load Amps | Notes (a) |
|-----|------|------------|------------------|------------------|------------|----------|----------------|----------------------|---------|----------------|-----------|
| 60 | 3600 | 326TS | EM2546T | 4,666 | L1 | 25.19 | 463 | 94.5 | 230/460 | 65 | 1 |
| | 1800 | 364T | EM2547T | 4,845 | L1 | 30.69 | 698 | 95 | 230/460 | 68 | 1,30 |
| | | | | P36G51 | 5,280 | L1 | 29.70 | 770 | 95 | 230/460 | 69.5 |
| | 1200 | 404T | EM2548T-4 | 7,910 | L1 | 34.00 | 1,127 | 95 | 460 | 72 | 1,25 |
| 75 | 3600 | 364TS | EM2549T | 6,121 | L1 | 25.81 | 737 | 94.5 | 230/460 | 82 | 1 |
| | 1800 | 365T | EM2551T | 5,947 | L1 | 33.72 | 808 | 95.4 | 230/460 | 86 | 1,30 |
| | | | 365T | P36G52 | 6,482 | L1 | 29.70 | 838 | 95 | 230/460 | 86.5 |
| | 1200 | 405T | EM2552T-4 | 8,807 | L1 | 34.00 | 1,166 | 95 | 460 | 88 | 1,25 |
| 100 | 3600 | 365TS | EM2550T | 6,543 | L1 | 26.81 | 810 | 94.5 | 230/460 | 109 | 1 |
| | 1800 | 404T | EM2555T-4 | 6,919 | L1 | 36.97 | 889 | 95.4 | 460 | 115 | 1,25 |
| | | | 404T | P40G297 | 7,542 | L1 | 34.00 | 1,110 | 95.4 | 230/460 | 115 |
| | 1200 | 444T | EM2583T-4 | 9,694 | L1 | 39.62 | 1,349 | 95 | 460 | 123 | 1,25 |
| 125 | 3600 | 404TS | EM2554T-4 | 8,212 | L1 | 33.60 | 775 | 95.8 | 460 | 138 | 1,25 |
| | | | P40G295 | 9,798 | L1 | 31.00 | 1,108 | 95 | 460 | 143 | 1 |
| | 1800 | 405T | EM2559T-4 | 8,488 | L1 | 34.47 | 1,238 | 95.4 | 460 | 143 | 1,25 |
| | | | 405T | P40G298 | 9,251 | L1 | 34.00 | 930 | 95.4 | 460 | 141 |
| | 1200 | 445T | EM2557T-4 | 10,469 | L1 | 39.62 | 1,535 | 95.8 | 460 | 146 | 1,25 |
| | | | | | | | | | | | |
| 150 | 3600 | 405TS | EM2556T-4 | 10,130 | L1 | 34.60 | 831 | 95.8 | 460 | 164 | 1,25 |
| | 1800 | 444T | EM2558T-4 | 9,429 | L1 | 39.62 | 1,405 | 95.8 | 460 | 170 | 1,25 |
| | | | 444T | P44G455 | 9,429 | L1 | 39.56 | 1,528 | 96.2 | 460 | 170 |
| | 1200 | 445T | EM2560T-4 | 12,329 | L1 | 39.62 | 1,620 | 95.8 | 460 | 176 | 1,25 |
| 200 | 3600 | 444TS | EM2562T-4 | 11,480 | L1 | 35.88 | 1,326 | 95.4 | 460 | 217 | 1,25 |
| | 1800 | 445T | EM2563T-4 | 11,783 | L1 | 39.62 | 1,496 | 95.8 | 460 | 226 | 1,25 |
| | | | 447T | EM2564T-4 | 16,207 | L1 | 48.12 | 1,909 | 95.8 | 460 | 234 |
| | 250 | 1800 | 445T | EM2566T-4 | 22,774 | L1 | 39.62 | 1,592 | 95.8 | 460 | 280 |
| 300 | 1800 | 445T | EM2569T-4 | 23,897 | L1 | 39.62 | 1,702 | 95.8 | 460 | 335 | 1,25 |

(a) See notes on inside back flap and pages 5-6.

Custom TEFC motors available through 2,250 Hp; Open and WPII custom motors through 15,000 Hp. Contact your local Baldor Sales Representative.

■ Cast Iron Frame