

RESCUE® Motors Permanent Split Capacitor Direct Drive Fan & Blower

5.6" Diameter, Open, Air Over

APPLICATIONS:

Commercial and Residential Air Handlers and Furnaces. Can replace a range of horsepower applications and a variety of mounting styles.

FEATURES:

- Extended Mounting Studs
- Designed For Use With 370v Capacitors
- Class B Insulation
- 36" Leads
- High Efficiency Design®
- Includes Side Shell Holes For Rheem® Units
- Continuous Duty, Air Over
- Reversible Rotation
- Automatic Reset Thermal Overload Protector
- 2.5" Dia. Hub Rings Included
- Discount Symbol: DS-3HAC

HP	RPM	Volts	Catalog Number	List Price	Max Ambient	Speed Tap	Bearings	MFD	Cap Amps	N	Shaft XD	Base XI	Shell C	Total Wgt.	Ship Notes
1/2	1075	115	5460	\$115	High	Med-Low	Slv	10	7.3	5.0	5.4	4.8	9.8	15	1, 2
1/3					High	Med-Low	Slv	5	6.9						
1/4					Med-Hi	Low	Slv	5	5.5						
1/5					Med-Low	Low	Slv	5	3.6						
1/6					Low	Low	Slv	5	2.8						
1/2	1075	208-230	5461	\$118	High	Med-Low	Slv	10	3.6	5.0	5.4	4.8	9.8	15	1, 2
1/3					High	Med-Low	Slv	5	3.5						
1/4					Med-Hi	Low	Slv	5	2.8						
1/5					Med-Low	Low	Slv	5	1.9						
1/6					Low	Low	Slv	5	1.3						
3/4	1075	115	5470	\$138	High	Med-Low	Ball	20	8.1	5.0	6.6	6.1	11.6	22	1
1/2					High	Low	Ball	10	6.6						
1/3					Med-Hi	Low	Ball	10	4.6						
1/4					Med-Low	Low	Ball	10	3.8						
1/5					Low	Low	Ball	10	3.1						
3/4	1075	208-230	5471	\$141	High	Med-Low	Ball	20	3.8	5.0	6.6	6.1	11.6	21	1
1/2					High	Low	Ball	10	3.7						
1/3					Med-Hi	Low	Ball	10	2.5						
1/4					Med-Low	Low	Ball	10	1.8						
1/5					Low	Low	Ball	10	1.7						

Note 1 Screws For Shell Mounting Included In Carton

Note 2 For 1/3 To 1/6 HP, if more air flow is needed, a 7.5 mfd capacitor may be used.

† All non-Emerson Electric Co. marks shown within this document are properties of their other respective owners.