

Painted Washdown, Yoke Mount, Non-Oscillating Fan Motors

APPLICATIONS:

Designed for air circulators where motor is mounted directly to fan column in a washdown application.

FEATURES:

- Class F Insulation
- USDA^{®†} Approved Non-Toxic White Epoxy Paint
- V-Ring Rotating Lip Seal On Shaft End
- F1 Assembly Position
- Totally Enclosed Air Over (TEAO)
- Double Sealed Ball Bearings
- Internal Corrosion Protection On Rotor, Stator, Winding & Frame
- Stationary Grease Seal On Shaft End
- 303 Stainless Steel Shaft
- Gasketed Conduit Box With NPT Lead Hole

Permanent Split Capacitor

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Amps	Notes
1/4	1800	115/230	56YZ	WD14AA2PZ7	\$274	DS-3FMP	1.00	10.4	3.2/1.6	19	24
1/3	1800	115/230	56YZ	WD13AA2PZ7	\$288	DS-3FMP	1.00	10.7	4.4/2.2	16	24
1/2	1800	115/230	56YZ	WD12AA2PZ7	\$309	DS-3FMP	1.00	10.4	5.6/2.8	18	24

Note 24 Automatic Reset Thermal Overload Protector

† All non-Emerson Electric Co. marks shown within this document are properties of their other respective owners