

**Standard-E & Super-E 1/2 thru 20 Hp
Stainless Steel,
Three Phase,
Totally Enclosed,
C-Face**

NEMA 56C thru 256TC

Applications: Food processing, packaging, outdoor and highly corrosive environments.

Features: All external surfaces 300 series stainless steel: motor frame, endplates, conduit box, shaft and base. Moisture resistant 200°C ISR® magnet wire. Four condensate drains in each endplate. Endplate rabbets sealed and conduit box gasketed. Lip seals. Especially effective in highly corrosive environments where paint or other finishes do not hold up. CESSWDM Super-E® motors have NEMA Premium® efficiency and 3 year warranty. See page 84 for 1/2-10 Hp Super-E® all stainless motors.



Hp	RPM	NEMA Frame	Enclosure	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
C-Face, Foot Mounted												
1/2	3600	56C	TENV	CSSWDM3537	960	WD	11.09	34	70	208-230/460	0.9	1
	1800	56C	TENV	CSSWDM3538	1,031	WD	11.09	37	75.5	230/460	0.8	1,30
3/4	3600	56C	TENV	CSSWDM3541	993	WD	11.09	40	80	230/460	1.1	1,30
	1800	56C	TENV	CSSWDM3542	1,067	WD	12.09	44	78.5	208-230/460	1	1
1	3600	56C	TENV	CSSWDM3545	1,089	WD	11.09	39	82.5	230/460	1.3	1
	1800	56C	TENV	CSSWDM3546	1,096	WD	12.09	45	85.5	208-230/460	1.4	1
1 1/2	3600	56C	TENV	CSSWDM3550	1,102	WD	12.09	50	85.5	230/460	2	1
	1800	56C	TEFC	CSSWDM3554	1,120	WD	13.34	53	85.5	208-230/460	2.1	1
2		3600	145TC	TEFC	CSSWDM3554T	1,120	WD	13.42	53	85.5	208-230/460	2.1
	145TC		TEFC	CSSWDM3555T	1,348	WD	14.30	59	84	208-230/460	2.6	1
	1800	56C	TEFC	CSSWDM3558	1,362	WD	13.34	55	84	230/460	2.8	1
3	3600	145TC	TEFC	CSSWDM3559T	1,622	WD	14.30	61	85.5	230/460	3.7	1
		182TC	TEFC	CSSWDM3610T	1,685	WD	15.61	89	85.1	208-230/460	3.7	1
	1800	182TC	TEFC	CESSWDM3611T	1,649	WD	16.82	91	89.5	230/460	4	1
		182TC	TEFC	CSSWDM3611T	1,557	WD	16.82	89	87.5	208-230/460	4.5	1
5	3600	184TC	TEFC	CESSWDM3613T	1,919	WD	18.32	103	90.2	230/460	5.7	1
		184TC	TEFC	CSSWDM3613T	1,774	WD	16.82	95	87.5	208-230/460	5.7	1
	1800	184TC	TEFC	CESSWDM3615T	1,856	WD	18.32	115	90.2	230/460	6.4	1,30
7 1/2	3600	184TC	TEFC	CSSWDM3615T	1,788	WD	18.32	109	87.5	208-230/460	6.5	1
		213TC	TEFC	CESSWDM3709T	2,252	WD	19.03	164	91	230/460	8.3	1
	1800	213TC	TEFC	CSSWDM3709T	2,066	WD	19.03	157	88.5	208-230/460	8.9	1
		213TC	TEFC	CESSWDM3710T	2,322	WD	20.16	157	91.7	230/460	9.5	1
10	3600	213TC	TEFC	CSSWDM3710T	2,110	WD	20.16	152	89.5	208-230/460	9.7	1
		215TC	TEFC	CESSWDM3711T	2,513	WD	20.16	185	91.7	208-230/460	10.6	1
	1800	215TC	TEFC	CSSWDM3711T	2,346	WD	20.16	174	89.5	208-230/460	11.9	1
		215TC	TEFC	CESSWDM3714T	2,384	WD	21.66	187	89.5	208-230/460	12.4	1,20
15	3600	254TC	TEFC	CESSWDM3714T	2,562	WD	21.66	158	92.4	230/460	12.5	1
	1800	254TC	TEFC	CESSWDM23994T	5,130	WD	21.94	240	91.7	230/460	17.6	1
20	3600	256TC	TEFC	CESSWDM23933T	5,048	WD	23.57	246	92.4	230/460	18	1,30
	1800	256TC	TEFC	CESSWDM41906T	5,888	WD	23.57	292	92.4	230/460	23	1
20	3600	256TC	TEFC	CESSWDM23934T	5,855	WD	23.57	300	93	230/460	24	1,30

(a) See notes on inside back flap and pages 5-6.

General Information
Single Phase Motors
General Purpose Industrial Motors
Premium Efficient Super-E® Motors
Severe Duty Motors
Washdown Duty Motors
Explosion Proof Motors
Pump Motors
Commercial Motors
HVAC Motors

Standard-E & Super-E Stainless Steel, Three Phase, Totally Enclosed, C-Face

Hp	RPM	NEMA Frame	Enclosure	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
C-Face, Footless												
1/2	3600	56C	TENV	VSSWDM3537	938	WD	11.09	34	70	208-230/460	0.9	1
		56C	TENV	VSSWDM3538	1,009	WD	11.09	37	75.5	230/460	0.8	1,30
	1800	56C	TEFC	VSSFWDM3538	1,067	WD	12.88	43	84.3	208-230/460	0.8	1
3/4	3600	56C	TENV	VSSWDM3541	973	WD	11.09	40	80	230/460	1.1	1,30
		56C	TENV	VSSWDM3542	1,046	WD	12.09	44	78.5	208-230/460	1	1
	1800	56C	TEFC	VSSFWDM3542	1,102	WD	12.88	45	82.5	208-230/460	1	1
1	3600	56C	TENV	VSSWDM3545	1,067	WD	11.09	38	82.5	230/460	1.3	1
		56C	TENV	VSSWDM3546	1,075	WD	12.09	47	85.5	208-230/460	1.4	1
	1800	56C	TEFC	VSSFWDM3546	1,131	WD	14.94	49	86.5	208-230/460	1.4	1
1 1/2	3600	56C	TENV	VSSWDM3550	1,081	WD	12.09	49	85.5	230/460	2	1
	1800	145TC	TEFC	VSSWDM3554T	1,098	WD	13.42	51	85.5	208-230/460	2.1	1
2	3600	145TC	TEFC	VSSWDM3555T	1,326	WD	14.30	57	84	208-230/460	2.6	1
	1800	145TC	TEFC	VSSWDM3558T	1,341	WD	13.42	52	84	230/460	2.8	1
3	3600	145TC	TEFC	VSSWDM3559T	1,600	WD	14.30	57	85.5	230/460	3.7	1
	1800	182TC	TEFC	VSSWDM3611T	1,521	WD	16.82	86	87.5	208-230/460	4.5	1
5	3600	184TC	TEFC	VSSWDM3613T	1,739	WD	16.82	92	87.5	208-230/460	5.7	1
	1800	184TC	TEFC	VSSWDM3615T	1,752	WD	18.32	108	87.5	208-230/460	6.5	1

(a) See notes on inside back flap and pages 5-6.

General Information

Single Phase Motors

General Purpose Industrial Motors

Premium Efficient Super-E® Motors

Severe Duty Motors

Washdown Duty Motors

Explosion Proof Motors

Pump Motors

Commercial Motors

HVAC Motors