

BALDOR • RELIANCE

Single Phase, TEFC, C-Face, No Drip Cover

1/6 thru 10 Hp

NEMA 56C thru 215TC

**Applications:** Pumps, fans, conveyors, machine tools, gear reducers and other applications requiring a NEMA C-face motor.

**Features:** Pressure cast aluminum end plates with ribbed design for rigidity. Ball bearings with a locked drive end bearing, heavy-gauge steel frame, and gasketed conduit box and capacitor cover.



Hp	RPM	NEMA Frame	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
<b>C-Face, Foot Mounted</b>											
1/4	1800	56C	CL3403	279	K	11.48	18	55	115/208-230	2.5	3
	3600	56C	CL3405	278	K	11.48	19	55	115/208-230	3	3
1/3	1800	56C	CL3501	292	K	11.35	23	60	115/230	3	3,30
	3600	56C	CL3503	293	K	11.35	24	66	115/230	3.5	3,30
1/2	1800	56C	CL3504	341	K	11.97	28	68	115/230	3.7	3,30
	3600	56C	CL3506	326	K	11.97	29	66	115/230	4.8	3,30
3/4	1800	56C	CL3507	408	K	12.47	35	72	115/230	4.2	30,65
	3600	56C	CL3509	376	K	12.25	35	68	115/230	5.9	3,30
1	1800	56C	CL3510	460	K	13.25	40	67	115/230	6.4	3,30
	3600	56C	CL3513	488	K	13.25	44	70	115/230	7.5	3,30
1 1/2	3600	56C	CL3514	546	K	14.12	49	70	115/230	7.5	30,65
		56C	CL3515	629	K	14.12	48	74	115/230	11.5	1,3,30
	1800	145TC	CL3515T	634	L1	14.19	51	74	115/230	11.5	1,3,30
2	1800	145TC	CL3516TM	811	L1	14.19	49	78	230	8.3	1,65
	3600	184TC	CL3619TM	1,056	L1	16.54	81	81.5	230	13.2	2,20
3	1800	184TC	CL3608TM	1,143	L1	18.05	91	83	230	19.5	2,20
	3600	184TC	CL3612TM	1,106	L1	18.05	101	80	230	23	2,20
5	3600	215TC	CL3711T	1,860	L1	19.75	167	82	230	40	2,20
	1800	215TC	CL3712T	1,881	L1	21.25	163	86.5	230	38	2,20
<b>C-Face, Footless</b>											
1/6	1800	56C	KL3400	272	K	11.35	18	49	115/230	1.9	3,30
	1200	56C	KL3401	380	K	11.35	23	47	115/230	2.3	3,30
1/4	1800	56C	KL3403	279	K	11.35	20	55	115/230	2.5	3,30
		56C	KL3500	424	K	12.25	30	47	115/230	3	30
1/3	3600	56C	KL3405	257	K	11.35	21	55	115/208-230	3	3
		56C	VL3405	258	K	11.48	20	—	115/208-230	3	
	1800	56C	VL3501	287	K	11.35	22	60	115/230	3	3,30
1/2	3600	56C	VL3503	289	K	11.35	21	66	115/230	3.5	3,30
	1800	56C	VL3504	334	K	11.97	27	68	115/230	3.7	3,30
	1200	56C	VL3505	620	K	13.25	41	59	115/230	4	3,30
3/4	3600	56C	VL3506	321	K	11.97	29	66	115/230	4.8	3,30
		56C	VL3506A	355	K	11.97	28	66	115/230	4.8	3
	1800	56C	VL3507	384	K	12.47	34	72	115/230	4.2	30,65
1	3600	56C	VL3508	714	K	13.25	41	68	115/230	5	2,30,65
		56C	VL3509	371	K	12.25	33	68	115/230	5.9	3,30
	1800	56C	VL3509A	405	K	13.25	40	66	115/230	6	3
1 1/2	3600	56C	VL3510	440	K	13.25	38	67	115/230	6.4	3,30
		143TC	VL3510T	440	L1	13.31	39	67	115/230	6.4	3,30
	1800	56C	VL3513	483	K	13.25	40	70	115/230	8	3,30
2	3600	143TC	VL3513T	512	L1	13.31	38	70	115/230	8	3,30
		56C	VL3514	498	K	14.12	47	75.5	115/230	8	30,65
	1800	145TC	VL3514T	504	L1	14.18	47	75.5	115/230	8	30,65
3	3600	56C	VL3515	618	K	14.12	51	74	115/230	11.5	1,3,30
		145TC	VL3515T	629	L1	14.19	50	74	115/230	11.5	1,3,30
	1800	182TC	VL3605T	893	L1	16.55	66	75.5	115/230	11.5	3,30
3	3600	184C	VL3605	1,010	L1	15.68	62	75.5	115/230	11.5	3,30
		182TC	VL3606T	996	L1	16.55	71	76	115/230	14.5	1,3,30
3	1800	184TC	VL3609T	1,054	L1	16.55	76	78	115/230	14	2,20,30,65

(a) See notes on inside back flap and pages 5-6.

**Single Phase,  
ODP, Foot Mounted**

**1/6 thru 10 Hp**

**NEMA 48 thru 215T**



**Applications:** Compressors, pumps, conveyors, machine tools, air handling, and others.

**Features:** Copper windings, dynamically balanced rotors, ball bearings, heavy-gauge steel frames, and other industrial quality features.

Hp	RPM	NEMA Frame	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)	
1/6	1800	48	L1200	215	K	9.13	18	49	115/230	1.9	30	
	1200	48	L1201	329	K	9.38	23	47	115/230	2.3	30	
1/4	1800	48	EL1203	280	K	9.76	23	74	115/230	1.25	1,65	
		48	L1203	218	K	9.13	19	59.5	115/230	2.2	30	
		48	L1203M	251	K	9.13	20	55	115/230	2.5	30	
	1200	48	L1204	352	K	9.75	25	48	115/230	3.2	30	
		56	L1300	365	K	10.13	26	48	115/230	3.2	30	
		48	L1205	206	K	9.13	20	55	115/208-230	3	30	
1/3	1800	48	L1206	251	K	9.13	21	60	115/230	3	30	
		48	L1206M	282	K	9.13	22	60	115/230	3	30	
		56	EL1301	332	K	10.13	26	77	115/230	1.6	1,65	
		56	L1301	254	K	9.51	22	60	115/230	3	30	
		56	L1301M	297	K	9.51	22	60	115/230	3	30	
	1200	48	L1207	375	K	10.63	28	54	115/230	3.7	30	
		56	L1302	375	K	11.01	29	54	115/230	3.7	30	
		48	L1208	228	K	9.13	22	57	115/230	3.7	30	
		56	L1303	228	K	9.51	21	66	115/230	3.5	30	
		48	L1209	315	K	9.75	24	68	115/230	3.7	30	
1/2	1800	48	L1209M	351	K	9.38	24	62	115/230	4.2	30	
		56	EL1304	380	K	11.00	31	78.5	115/230	2.3	1,65	
		56	L1304	280	K	9.76	24	68	115/230	3.7	30	
		56	L1304A	333	K	9.76	25	62	115/230	4.2	30	
		56	L1304M	351	K	9.76	25	62	115/230	4.2	30	
		1200	56H	L1305	564	K	11.75	38	62	115/230	4.1	30,36
	3/4	3600	56	L1306	278	K	12.85	26	72	115/230	4.7	30
			56	L1306A	293	K	11.75	31	69	115/230	5.5	
		1800	56	EL1307	469	K	12.06	35	84	115/230	3.25	1,65
			56	L1307	346	K	11.51	32	68	115/230	5.1	30
56			L1307A	407	K	11.51	32	68	115/230	5.1	30	
56			L1307M	417	K	11.51	32	68	115/230	5.1	30	
1200		56H	L1308	635	K	11.75	42	68	115/230	5	30,36,65	
1		3600	56	L1309	292	K	11.01	31	65	115/230	7.5	30
	56		L1309A	311	K	11.01	30	70	115/230	6.6		
	56H		L1318	414	K	11.75	39	67	115/230	6.2	30,36	
	1800	56H	L1318M	451	K	11.75	39	67	115/230	6.2	2,36	
		56	EL1310	510	K	12.94	40	84	115/230	4.3	1,65	
		56	L1310	378	K	11.07	34	66	115/230	6.7	30	
		56H	L1310M	485	K	11.75	33	66	115/230	6.7	30,36	
		143T	L1318T	431	L1	13.00	39	67	115/230	6.2	30	
		143T	L1318TM	451	L1	12.12	39	67	115/230	6.2	2	
		182	L1401	616	L1	12.75	50	70	115/230	7	30	
1200	184	L1407	668	L1	12.75	48	70	115/230	7			
1200	184	L1407	1,081	L1	14.13	63	65	115/230	8	30		

(a) See notes on inside back flap and pages 5-6.

General Information

Single Phase Motors

General Purpose Industrial Motors

Premium Efficient Super-E® Motors

Severe Duty Motors

Washdown Duty Motors

Explosion Proof Motors

Pump Motors

Commercial Motors

HVAC Motors

Single Phase, ODP, Foot Mounted

Hp	RPM	NEMA Frame	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)	
1 1/2	3600	56H	L1313A	429	K	11.75	40	68	115/230	9	30,36	
		56H	L1313	410	K	11.75	34	80	115/230	6.4	30,36,65	
		143T	L1313T	410	L1	11.12	33	70	115/230	8.9	30	
	1800	56H	L1319	489	K	11.75	41	68	115/230	9	30,36	
		56H	L1319M	545	K	11.75	39	68	115/230	9	36	
		56H	EL1319	669	K	14.00	47	85.5	115/230	6.25	1,36,65	
		145T	EL1319T	694	L1	13.00	49	85.5	115/230	6.25	1,65	
		145T	L1319T	462	L1	12.12	39	68	115/230	9	30	
		145T	L1321T	554	L1	13.00	45	70	115/230	10.5	30	
		145T	L1321TM	601	L1	13.00	45	70	115/230	10.5		
		184	L1403	687	L1	12.75	56	68	115/230	9.5	30	
		184	L1403M	729	L1	12.75	56	68	115/230	9.5		
2	3600	56H	L1317	545	K	11.75	40	70	115/230	13	30,36	
		56H	L1317A	561	K	11.75	40	70	115/230	12	30,36	
		145T	L1320T	585	L1	12.12	44	71	115/230	11.5	30,65	
	1800	145T	L1322T	565	L1	13.00	48	75.5	115/230	10.2	65	
		145T	L1322TM	615	L1	13.00	45	78.5	115/230	9.2	65	
		182T	EL1405T	783	L1	15.87	65	82.5	115/230	8.8	1,65	
		182T	L1405T	580	L1	15.00	65	71	115/230	12	30	
		184	L1405	722	L1	14.13	64	71	115/230	12	30	
		213	L1502	1,240	L1	14.32	82	69	115/230	12.5	30	
	1200	215	L1503	1,689	L1	15.94	104	68	115/230	14	30	
	3	3600	182T	L1406T	665	L1	15.00	65	78	115/230	14	30
		1800	184T	EL1408T	819	L1	16.50	78	85.5	230	11.2	1,65
184T			L1408T	627	L1	15.00	73	78	115/230	16	30,65	
184T			L1408TM	739	L1	15.00	78	78	115/230	16	65	
215			L1505	1,374	L1	15.94	102	75	115/230	18	30	
1200		215	L1506	1,974	L1	15.94	111	75	115/230	16	30,65	
5	3600	184T	L1409T	791	L1	15.00	76	75	230	23	30	
	1800	184T	EL1410T	936	L1	18.00	95	86.5	230	19.1	1,65	
		184T	L1410T	751	LS	16.50	86	82.5	230	23	1,30,65	
		184T	L1410TM	899	L1	16.50	84	82.5	230	23	1,30,65	
		184T	L1430T	681	L1	16.55	79	84	230	20.6	1,30,65	
		184T	L1430TM	899	L1	16.55	84	80	230	24	1,30,65	
		213T	L1508T	980	L1	16.32	113	77	230	27		
7 1/2	3600	213T	L1509T	1,223	L1	18.37	101	82.5	230	30	1,30,65	
	1800	215T	L1510T	1,064	L1	17.45	134	85.5	230	31	30,65	
10	3600	215T	L1511T	1,543	L1	17.45	130	83	230	46	1,30	
	1800	215T	L1512T	1,554	L1	17.45	140	85.5	230	39	2,65	

(a) See notes on inside back flap and pages 5-6.

General Information

Single Phase Motors

General Purpose Industrial Motors

Premium Efficient Super-E® Motors

Severe Duty Motors

Washdown Duty Motors

Explosion Proof Motors

Pump Motors

Commercial Motors

HVAC Motors

**Single Phase,  
ODP, C-Face**

**1/6 thru 5 Hp**

**NEMA 56C thru 184TC**



**Applications:** Pumps, fans, conveyors, machine tools, gear reducers and other applications requiring a NEMA C-face motor.

**Features:** Pressure cast aluminum end plates with ribbed design for rigidity. Ball bearings with a locked drive end bearing, heavy-gauge steel frame, and gasketed conduit box and capacitor cover.

Hp	RPM	NEMA Frame	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
<b>C-Face, Foot Mounted, No Drip Cover</b>											
1/3	1800	56C	CL1301	284	K	10.10	23	60	115/230	3	30
1/2	3600	56C	CL1303	252	K	10.06	24	66	115/230	3.5	30
	1800	56C	CL1304	323	K	10.35	25	62	115/230	4.2	30
3/4	1800	56C	CL1307	371	K	12.06	34	68	115/230	5.1	30
1	1800	56C	CL1310	426	K	11.06	31	66	115/230	6.7	30
3	1800	184TC	CL1408TM	781	L1	15.00	78	78	115/230	16	65
5	1800	184TC	CL1410TM	940	L1	16.50	88	82.5	230	23	1,30,65
<b>C-Face, Foot Mounted, Drip Cover</b>											
5	1800	184TC	CL1430TM	940	L1	16.55	84	80	230	24	1,30,65
<b>C-Face, Footless, Drip Cover</b>											
1/6	1800	56C	KL1200	230	K	11.22	18	49	115/230	1.9	30
1/4	1800	56C	KL1203	234	K	11.22	20	55	115/230	2.5	30
1/3	3600	56C	KL1205	222	K	11.22	21	55	115/208-230	3	30
		56C	KL1205A	228	K	11.35	21	55	115/230	3	30
1/2	1800	56C	VL1301	269	K	11.22	22	60	115/230	3	30
	3600	56C	VL1303	244	K	11.22	21	66	115/230	3.5	30
	1800	56C	VL1304	296	K	11.47	24	62	115/230	4.2	30
3/4	1200	56C	VL1305	580	K	13.24	36	62	115/230	4.1	30
	3600	56C	VL1306	293	K	12.85	27	72	115/230	4.7	30
	1800	56C	VL1307	362	K	13.22	33	68	115/230	5.1	30
	1200	56C	VL1308	650	K	13.24	43	68	115/230	5	30
1	3600	56C	VL1309	308	K	12.72	32	65	115/230	7.5	30
	1800	56C	VL1310	394	K	12.24	34	66	115/230	6.7	30
1 1/2		56C	VL1318	429	K	13.24	42	67	115/230	6.2	30
	3600	56C	VL1313	426	K	12.73	32	80	115/230	6.4	30
	1800	56C	VL1319	504	K	13.24	42	68	115/230	9	30
2	145TC	VL1321T	570	L1	14.18	49	70	115/230	10.5	30	
	3600	56C	VL1317	561	K	13.24	43	70	115/230	13	30
3	1800	145TC	VL1322T	581	L1	14.18	47	75.5	115/230	10.2	65
	3600	182TC	VL1406T	706	L1	15.18	59	75.5	115/230	13.6	30,65
	1800	184TC	VL1408T	715	L1	16.55	76	78	115/230	16	30,65

(a) See notes on inside back flap and pages 5-6.

General Information  
Single Phase Motors  
General Purpose Industrial Motors  
Premium Efficient Super-E® Motors  
Severe Duty Motors  
Washdown Duty Motors  
Explosion Proof Motors  
Pump Motors  
Commercial Motors  
HVAC Motors