

C Flange Pool & Spa Motors

Switch Type, 5.5" Diameter



FEATURES:

- Two Compartment
- 1081 Design
- Open Dripproof
- 303 Stainless Steel Shaft
- Triple Bearing Protection
- Shaft Threads – 7/16-20 UNC-2A
- Continuous Duty
- Sealed Ball Bearings
- Thermally Protected
- Class B Insulated
- 50°C Ambient
- Voltage Selection Device (Dual Voltage Only)
- **Discount Symbol: DS-FPS**

Standard Efficient, Full Service Factor, Full Rated, Category J

HP	SF	RPM	Voltage	Freq	SF Amps	Shaft	Catalog Number	List Price	Frame	Length Less Shaft	Ship Wt. (lbs.)
1/2	1.60	3450	230/115	60	5.0/10.0	Threaded	EST1052*	139.47	56J	9.34	19
3/4	1.50	3450	230/115	60	6.8/13.6	Threaded	EST1072*	155.26	56J	10.09	22
1	1.50	3450	230/115	60	7.8/15.6	Threaded	EST1102*	177.63	56J	10.59	24
1-1/2	1.30	3450	230/115	60	8.4/16.8	Threaded	EST1152	244.74	56J	10.84	27
2	1.30	3450	230	60	10.0	Threaded	EST1202	287.63	56J	11.09	29

Standard Efficient, Low Service Factor, Up Rated, Category J

HP	SF	RPM	Voltage	Freq	SF Amps	Shaft	Catalog Number	List Price	Frame	Length Less Shaft	Ship Wt. (lbs.)
3/4	1.00	3450	230/115	60	5.0/10.0	Threaded	EUST1072*	139.47	56J	9.34	19
1	1.00	3450	230/115	60	6.8/13.6	Threaded	EUST1102*	155.26	56J	10.09	22
1-1/2	1.00	3450	230/115	60	7.8/15.6	Threaded	EUST1152*	177.63	56J	10.59	24
2	1.00	3450	230/115	60	8.4/16.8	Threaded	EUST1202	244.74	56J	10.84	27
2-1/2	1.00	3450	230	60	10.0	Threaded	EUST1252	287.63	56J	11.09	29

Sta-Rite Max-E-GLAS® & DURA-GLAS® Replacement Motor Base Available (PN B357434490000) *Non-compliant with the California Energy Commission's (CEC) Title 20 regulations.

†Catalog numbers are for competitive comparison purposes only and do not indicate an affiliation between Emerson and any other company. All non-Emerson Electric Co. marks shown within this document are properties of their other respective owners.