

Shaded Pole & Permanent Split Capacitor Ventilation Direct Drive Blower

5.0", 5.6" & 6.3 Diameter, Open, Air Over



APPLICATIONS:

Designed for direct drive ventilation units.

FEATURES:

- Capacitor Included and Mounted On PSC Models
- Automatic Reset Thermal Overload Protector
- Continuous Duty
- Discount Symbol: DS-3HAC
- Ball Bearings Unless Noted
- 40°C Ambient Rated
- 1.0 Service Factor

HP	RPM/Spd.	Volts	NEMA Frame	Catalog Number	List Price	Amps	Motor Type	Shaft Length	Shaft Dia.	Rotation Lead End	Body Length	Total Length	Ship Wgt.	Notes
1/20	1550	115	42YZ	6478	\$109	1.9	SP	1.33	.312	CCW	4.40	5.73	8	1, 2, 3
1/12	850	115	48YZ	4740	\$105	1.7	PSC	3.25	.500	CCW	5.81	9.06	9	
1/8	1625	115	48Y	6463	\$125	1.9	PSC	3.00	.625	CCW	5.47	8.47	17	3
1/6	1650	115	48YZ	6492	\$93	2.3	PSC	3.25	.500	CW	5.80	9.10	19	
	1650	115	42YZ	4742	\$91	2.7	PSC	3.25	.500	CW	5.81	9.06	10	
1/4	850	115	48YZ	4744	\$311	3.6	PSC	3.25	.625	CW	5.81	9.10	13	LA
1/3	850	115	48YZ	4747	\$348	4.4	PSC	3.25	.625	CW	6.56	9.80	15	LA
	1100	115	48YZ	4746	\$129	4.4	PSC	3.30	.625	CCW	5.80	9.10	17	
	1650	115	48YZ	4745	\$124	4.0	PSC	3.25	.500	CW	6.06	9.31	14	
1/2	850	208-230/460	56YZ	6465	\$304	2.9-3.0/1.5	PSC	2.0	.625	CW/CCW	9.90	12.5	24	4
	1100	115/230	48YZ	4749	\$163	6.2/3.1	PSC	3.30	.625	CCW	6.60	9.90	20	
	1650	115/230	48YZ	4748	\$156	8.0/4.0	PSC	3.25	.625	CW	6.31	9.56	18	
3/4	1100	115/230	48YZ	4750	\$175	10.0/5.0	PSC	3.25	.625	CCW	6.56	9.81	24	

Note 1 Includes Resilient Base
 Note 2 Sleeve Bearing
 Note 3 Totally Enclosed

Note 4 Three Phase
 Note LA Limited Availability