

General Purpose Single Phase Totally Enclosed Fan Cooled (TEFC) Rigid Base, Capacitor Start



APPLICATIONS:

Designed for air compressors, pumps, conveyors, blowers and general industrial equipment

FEATURES:

- Double Shielded Ball Bearings
- Class B Insulation, Continuous Duty, 40°C Ambient
- Capacitor Start, Induction Run
- F1 Assembly
- Reversible Rotation
- T14CA2P49 is a Resilient Base

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Amps	Notes
1/6	900	115/230	56	6175	\$287	DS-3FMP	1.00	11.8	31	7.8/3.9	25
1/4	1800	115/208-230	48	T14C2J4	\$197	DS-3F	1.00	10.0	20	6.5/2.8-3.2	25
	1800	115/208-230	48	T14CA2J4	\$240	DS-3F	1.00	10.0	17	6.5/2.8-3.2	24
	1800	115/208-230	48	T14CM2J4	\$255	DS-3F	1.00	10.0	20	6.6/2.9-3.3	23
	1800	115/230	56	8789	\$230	DS-3FMP	1.15	10.5	20	5.8/2.9	25, LA
	1800	115/208-230	56	T14CA2P	\$246	DS-3FMP	1.15	10.4	20	5.8/2.9	24, LA
	1800	115/208-230	56	T14C2J	\$230	DS-3F	1.00	11.0	20	6.5/2.8-3.2	25
	1800	115/208-230	56	T14CA2J	\$246	DS-3F	1.00	11.0	20	6.5/2.9-3.3	24
	1200	115/230	56	6171	\$348	DS-3FMP	1.00	11.0	25	6.2/3.1	25, LA
	1200	115/208-230	56	T14C3J	\$348	DS-3F	1.00	11.0	23	6.4/3.0-3.2	25
1/3	3600	115/230	48	6165	\$214	DS-3FMP	1.00	10.0	18	5.4/2.7	24
	3600	115/230	48	6167	\$204	DS-3FMP	1.00	10.0	19	5.4/2.7	25, LA
	3600	115/208-230	48	T13C1J4	\$153	DS-3FMP	1.15	10.8	19	5.5/2.7-2.8	25
	1800	110/220	56	T13C2L	\$303	DS-3F	1.00	10.0	23	7.4/3.7	25, LA
	1800	115/230	56	T13CA2P	\$317	DS-3F	1.00	11.1	23	3.8/1.9	24, 28, LA
	1800	115/230	48	T13CA2P4	\$262	DS-3FMP	1.00	10.0	20	5.8/2.9	24
	1800	115/208-230	48	T13C2J4	\$229	DS-3F	1.35	10.7	19	6.6/3.0-3.3	25
	1800	115/208-230	48	T13CM2J4	\$269	DS-3F	1.00	10.0	20	6.6/3.0-3.3	23
	1800	115/230	56	1950	\$200	DS-3FMP	1.00	10.0	21	6.0/3.0	23, 92, LA
	1800	115/230	56	4005	\$190	DS-3FMP	1.15	10.5	19	6.0/3.0	24, 92
	1800	100-120/200-240	56	6169	\$238	DS-3FMP	1.35	12.0	23	4.3-4.3/2.2-2.2	25
	1800	115/208-230	56	T13C2J	\$233	DS-3F	1.15	10.6	30	6.6/2.9-3.3	25
	1800	115/208-230	56	T13CM2J	\$248	DS-3F	1.15	10.6	22	6.6/3.0-3.3	23
	1200	115/230	56	T13C3P	\$336	DS-3F	1.00	11.3	27	7.3/3.7	25, LA
	1200	115/208-230	56	T13C3J	\$336	DS-3F	1.00	11.0	23	6.8/3.4-3.4	25
1/2	3600	115/230	48	6166	\$243	DS-3FMP	1.00	11.0	21	7.2/3.6	24
	3600	115/208-230	48	T12C1J4	\$168	DS-3FMP	1.15	11.3	28	8.0/3.8-4.0	25
	3600	115/230	56	6173	\$243	DS-3FMP	1.00	11.1	21	7.2/3.6	24
	3600	115/208-230	56	T12C1J	\$168	DS-3FMP	1.15	11.6	30	8.0/3.8-4.0	25
	3600	115/208-230	56	T12CM1J	\$208	DS-3F	1.15	11.6	28	8.0/3.8-4.0	23
	1800	115/230	56	T12CA2P	\$299	DS-3F	1.15	11.4	26	9.0/4.5	24
	1800	115/230	48	T12CA2P4	\$296	DS-3FMP	1.00	10.6	21	8.4/4.2	24
	1800	115/208-230	48	T12C2J4	\$267	DS-3F	1.25	10.7	21	9/4.3-4.5	25

Note 18 Incorporates Run Capacitor
 Note 19 Also rated for 190/380, 220/415 volt 50 Hz at 1.0 Service Factor
 Note 23 Manual Reset Thermal Overload Protector
 Note 24 Automatic Reset Thermal Overload Protector

Note 25 Non-protected
 Note 28 TENV Enclosure
 Note 92 Rigid base, removable; Accepts C-Face kit #56
 Note LA Limited Availability

General Purpose Single Phase Totally Enclosed Fan Cooled (TEFC) Rigid Base, Capacitor Start



APPLICATIONS:

Designed for air compressors, pumps, conveyors, blowers and general industrial equipment

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Amps	Notes
1/2	1800	115/208-230	48	T12CM2J4	\$307	DS-3F	1.00	11.0	21	9.0/4.3-4.5	23
	1800	115/230	56	1951	\$231	DS-3FMP	1.00	11.0	22	7.4/3.7	23, 92, LA
	1800	100-120/200-240	56	6174	\$272	DS-3FMP	1.25	12.0	27	6.3-5.6/3.1-2.8	25
	1800	115/208-230	56	T12C2J	\$271	DS-3F	1.15	11.1	30	9.0/4.3-4.5	25
	1800	115/208-230	56	T12CM2J	\$305	DS-3F	1.15	11.1	28	9.0/4.3-4.5	23
	1200	115/230	56	T12C3P	\$477	DS-3F	1.00	11.3	37	10.4/5.2	25
3/4	3600	115/230	56	T34CA1P	\$248	DS-3FMP	1.00	11.0	26	9.8/4.9	24
	3600	115/208-230	56	T34C1J	\$222	DS-3F	1.15	11.89	25	10.4/5.3-5.2	25
	3600	115/208-230	56	T34CM1J	\$262	DS-3F	1.15	11.89	25	10.4/5.3-5.2	23
	1800	100-120/200-240	56	6172	\$323	DS-3FMP	1.25	11.3	30	9.2-8.4/4.6-4.2	25
	1800	115/208-230	56	T34C2J	\$329	DS-3F	1.15	12.1	33	11.4/5.7-5.7	25
	1800	115/208-230	56	T34CA2J	\$335	DS-3F	1.00	11.3	28	11.4/5.7-5.7	24
	1800	115/208-230	56	T34CM2J	\$344	DS-3F	1.15	12.1	31	11.4/5.7-5.7	23
	1200	115/230	56H	6170	\$599	DS-3FMP	1.00	12.8	41	12.0/6.0	25, LA
	1200	115/208-230	56H	T34C3JH	\$599	DS-3F	1.00	13.0	39	10.6/5.4-5.3	25
1	3600	115/230	56	T1CA1P	\$276	DS-3FMP	1.00	11.0	27	12.0/6.0	24
	3600	115/208-230	56	T1C1J	\$264	DS-3FMP	1.15	12.39	30	13.6/6.9-6.8	25
	3600	115/208-230	56	T1CM1J	\$304	DS-3F	1.15	12.39	27	13.6/6.9-6.8	23
	1800	115/208-230	143T	T1CA2J14	\$395	DS-3F	1.00	13.0	36	14.0/6.9-7.0	24
	1800	115-208/230	143T	T1C2J14	\$370	DS-3F	1.00	13.0	33	14.0/6.9-7.0	25
	1800	115/230	182	T1C2P18Z	\$641	DS-3SP	1.00	14.1	72	13.8/6.9	25
	1800	115/230	56	3963	\$284	DS-3FMP	1.15	13.0	40	14.4/7.2	24, 92
	1800	115/230	56	1853	\$287	DS-3FMP	1.15	11.3	31	14.0/7.0	24
	1800	115/208-230	56	T1C2J	\$356	DS-3F	1.15	13.1	28	14.4/7.2	25, LA
	1800	115/208-230	56	T1CM2J	\$371	DS-3F	1.15	13.1	40	14.2/7.1	23
	1800	100-120/200-240	56	6178	\$372	DS-3FMP	1.15	12.5	42	11.0-9.2/5.5-4.7	25
	1800	115/230	56H	3449	\$380	DS-3FMP	1.15	12.3	33	14.0/7.0	24
	1800	115/230	56H	4411	\$280	DS-3FMP	1.00	12.0	31	14.0/7.0	23, LA
	1800	115/208-230	56H	T1C2JH	\$356	DS-3F	1.00	12.0	28	14.0/6.9-7.0	25
	1800	115/230	56HZ	T1CM2PHZ	\$405	DS-3FMP	1.15	12.6	36	14.0/7.0	23
	1200	115/208-230	56H	T1C3JH	\$695	DS-3F	1.00	14.0	44	12.6/6.6-6.3	25
1-1/2	3600	115/230	56	8788	\$370	DS-3FMP	1.15	12.0	34	16.8/8.4	23, LA
	3600	115/208-230	143T	T32C1J14	\$330	DS-3FMP	1.15	13.25	34	14.6/8.1-7.4	25
	3600	115/230	56H	6179	\$360	DS-3FMP	1.00	12.3	34	16.4/8.2	24, LA
	3600	115/208-230	56H	T32CM1JH	\$370	DS-3FMP	1.15	12.89	34	14.6/8.1-7.4	23
	3600	115-208/230	56H	T32C1JH	\$330	DS-3FMP	1.15	12.89	32	14.6/8.1-7.4	25
	1800	115/230	56	678	\$340	DS-3FMP	1.15	13.0	42	16.8/8.4	18, 24, 92, LA
	1800	115/230	56H	T32CA2PH	\$415	DS-3F	1.15	12.8	41	16.2/8.1	24, LA
	1800	115/230	145T	T32C2P14	\$373	DS-3SP	1.15	13.2	40	16.2/8.1	25, LA
	1800	115/208-230	145T	T32C2J14	\$373	DS-3F	1.00	13.2	41	14.4/8.0-7.2	25
	1800	115/208-230	145T	T32CA2J14	\$398	DS-3F	1.00	14.0	40	14.4/8.0-7.2	24

Note 18 Incorporates Run Capacitor
 Note 19 Also rated for 190/380, 220/415 volt 50 Hz at 1.0 Service Factor
 Note 23 Manual Reset Thermal Overload Protector
 Note 24 Automatic Reset Thermal Overload Protector

Note 25 Non-protected
 Note 28 TENV Enclosure
 Note 92 Rigid base, removable; Accepts C-Face kit #56
 Note LA Limited Availability

General Purpose Single Phase Totally Enclosed Fan Cooled (TEFC) Rigid Base, Capacitor Start



APPLICATIONS:

Designed for air compressors, pumps, conveyors, blowers and general industrial equipment

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Amps	Notes
1-1/2	1800	115/230	184	T32C2P18Z	\$696	DS-3SP	1.00	15.1	79	18.4/9.2	25
	1800	115/208-230	56	T32C2J	\$407	DS-3F	1.15	13.1	30	16.6/8.3	25
	1800	115/208-230	56	T32CM2J	\$418	DS-3F	1.15	13.6	28	16.6/8.3	23, LA
	1800	115/208-230	56H	T32CA2JH	\$415	DS-3F	1.00	12.8	41	14.4/8.0-7.2	24
	1800	115/208-230	56H	T32CM2JH	\$418	DS-3F	1.00	14.0	28	14.4/8.0-7.2	23
	1800	115/230	56HZ	6177	\$450	DS-3FMP	1.15	13.1	46	16.2/8.1	23
	1800	115/230	56HZ	T32C2PHZ	\$432	DS-3FMP	1.15	13.1	41	16.2/8.1	25, LA
2	3600	115/230	56H	T2CM1PH	\$505	DS-3F	1.15	13.4	39	16.6/8.3	23, LA
	3600	115/208-230	145T	T2C1J14	\$432	DS-3FMP	1.15	13.25	41	19.5/10.8-9.7	25
	3600	115/208-230	145T	T2CM1J14	\$472	DS-3FMP	1.15	13.75	40	19.5/10.8-9.7	23
	3600	115/208-230	56H	T2C1JH	\$432	DS-3FMP	1.15	12.89	40	19.5/10.8-9.7	25
	3600	115/208-230	56H	T2CM1JH	\$472	DS-3FMP	1.15	12.89	39	19.5/10.8-9.7	23
	1800	115/208-230	145T	T2C2J14	\$539	DS-3F	1.00	14.0	54	18.9/10.3-9.4	25
	1800	115/208-230	145T	T2CA2J14	\$564	DS-3F	1.00	15.0	54	18.9/10.3-9.4	24
	1800	115/208-230	145T	T2CM2J14	\$579	DS-3F	1.00	14.0	54	18.9/10.3-9.4	23
	1800	115/230	182T	T2C2P18	\$526	DS-3SP	1.00	15.2	50	23.6/11.8	18, 25
	1800	115/230	213	T2C2P21Z	\$859	DS-3SP	1.00	17.6	72	24.0/12.0	18, 25
	1800	115/230	56H	T2C2PH	\$539	DS-3F	1.00	13.3	54	19.0/9.5	25
	1800	115/208-230	56H	T2CA2JH	\$564	DS-3F	1.00	14.0	54	18.9/10.3-9.4	24
	1800	115/208-230	56H	T2CM2JH	\$579	DS-3F	1.00	14.0	54	18.9/10.3-9.4	23
3	3600	115/230	182T	T3C1P18	\$648	DS-3SP	1.00	16.6	83	32.0/16.0	18, 25
	1800	115/230	184T	T3C2P18	\$613	DS-3SP	1.00	17.7	119	30.0/15.0	18, 25
	1800	115/230	215	T3C2P21	\$1,292	DS-3SP	1.00	19.6	83	33.6/16.8	18, 25
5	3600	230	184T	T5C1K18	\$876	DS-3SP	1.00	17.4	91	19.6	18, 25
	1800	230	213T	T5C2K21	\$732	DS-3SP	1.00	19.6	121	23.0	18, 25
	1800	230	215	T5C2K21Z	\$1,479	DS-3SP	1.00	19.6	90	20.0	18, 25
7-1/2	3600	230	213T	T7C1K21	\$1,150	DS-3SP	1.00	20.0	92	30.3	18, 25
	1800	230	215T	T7C2K21	\$1,167	DS-3SP	1.00	22.0	90	30.0	18, 25

Note 18 Incorporates Run Capacitor
 Note 19 Also rated for 190/380, 220/415 volt 50 Hz at 1.0 Service Factor
 Note 23 Manual Reset Thermal Overload Protector
 Note 24 Automatic Reset Thermal Overload Protector

Note 25 Non-protected
 Note 28 TENV Enclosure
 Note 92 Rigid base, removable; Accepts C-Face kit #56
 Note LA Limited Availability