

General Purpose Single Phase Open Dripproof (ODP) Rigid Base, Capacitor Start



APPLICATIONS:

Designed for air compressors, pumps, conveyors, blowers and general industrial equipment

FEATURES:

- Double Shielded Ball Bearings
- Rigid Base Standard
- Resilient Mount
- Class B Insulation, Continuous Duty, 40°C Ambient
- F1 Assembly
- Reversible Rotation

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Amps	Notes
1/4	1800	115/208-230	48	D14C2J4	\$172	DS-3F	1.35	8.6	18	4.8/2.4	25
	1800	115/208-230	48	D14CA2J4	\$197	DS-3F	1.00	9.0	18	7/3.3-3.5	24
	1800	115/208-230	48	D14CM2J4	\$212	DS-3F	1.00	9.0	18	7/3.3-3.5	23
	1800	115/230 110/220	48	6347	\$187	DS-3FMP	1.35	8.8	17	4.4/2.2 & 4.9/2.5	24, 98
	1800	115/230	48	4117	\$156	DS-3FMP	1.35	8.8	16	6.2/3.1	24, 61
	1800	115	56	6339	\$243	DS-3FMP	1.00	9.4	15	6	23, LA
	1800	115/230	56	6331	\$213	DS-3FMP	1.35	8.9	17	6.2/3.1	24, LA
	1800	115/208-230	56	D14C2J	\$188	DS-3F	1.00	9.0	17	7/3.3-3.5	25
	1800	115/208-230	56	D14CA2J	\$213	DS-3F	1.00	9.0	17	7/3.3-3.5	24
1200	115/230	56	6338	\$327	DS-3FMP	1.35	10.2	23	6.2/3.1	25	
1/3	3600	115/230	48	6335	\$155	DS-3FMP	1.35	9.1	16	6.8/3.4	24
	3600	115/208-230	48	D13C1J4	\$128	DS-3FMP	1.00	9.0	18	6/2.9-3.0	25
	3600	115/208-230	56	D13C1J	\$128	DS-3FMP	1.00	9.0	18	6/2.9-3.0	25
	1800	115/208-230	48	D13C2J4	\$203	DS-3F	1.35	7.5	22	6.2/3.1	25
	1800	115/208-230	48	D13CA2J4	\$228	DS-3F	1.00	9.0	22	8.8/3.9-4.4	24
	1800	115/230 110/220	48	6349	\$243	DS-3FMP	1.35	9.1	20	6.5/3.3 & 7.3/3.6	24, 98
	1800	115/230	48	4139	\$204	DS-3FMP	1.35	9.5	17	6.5/3.3 & 7.3/3.6	24, 98
	1800	115/230	56	8751	\$220	DS-3FMP	1.35	9.2	19	6.8/3.4	24, LA
	1800	115/230	56	D13C2P	\$208	DS-3F	1.35	9.0	25	6.0/3.0	25
	1800	115/208-230	56	D13CA2J	\$233	DS-3F	1.00	9.0	19	8.8/3.9-4.4	24
	1800	115/208-230	56	D13CM2J	\$223	DS-3F	1.35	9.0	16	6.0/3.0	23
	1800	115/230 110/220	56	6336	\$220	DS-3FMP	1.35	9.9	20	6.5/3.3 & 7.3/3.6	25, 98
	1800	115/230 110/220	56	6337	\$252	DS-3FMP	1.35	9.2	19	6.5/3.3 & 7.3/3.6	24, 98
	1200	115/208-230	56	D13C3J	\$340	DS-3F	1.00	11.0	16	6.8/3.4-3.4	25
1/2	3600	115/208-230	56	D12C1J	\$220	DS-3F	1.25	9.4	27	8.0/4.0	25
	3600	115/230	48	6334	\$231	DS-3FMP	1.25	9.1	17	8.9/4.5	24, LA
	3600	115/230	48	6345	\$248	DS-3FMP	1.25	10.4	17	9.8/4.9	23
	3600	115/230 110/220	48	6341	\$220	DS-3FMP	1.25	9.5	17	9.8/4.9&12.3/6.2	25, 98
	3600	115/208-230	48	D12CA1J4	\$165	DS-3FMP	1.00	10.0	17	7/3.4-3.5	24
	3600	115/208-230	56	D12C1J	\$140	DS-3FMP	1.25	9.4	27	8.0/4.0	25
	1800	115/208-230	56	D12CM2J	\$261	DS-3F	1.35	9.5	29	8.6/4.3	23
	1800	115/208-230	48	D12C2J4	\$242	DS-3F	1.25	7.5	24	8.2/4.1	25
	1800	115/230	48	4141	\$200	DS-3FMP	1.00	10.7	26	8.2/4.1	24
	1800	115/230	48	6343	\$271	DS-3FMP	1.25	9.8	20	8.2/4.1	24
	1800	115/208-230	48	D12CA2J4	\$271	DS-3F	1.00	9.0	20	10.3/4.8-5.3	24
	1800	115/230	56	8758	\$170	DS-3FMP	1.00	9.0	21	9.0/4.5	25, LA

Note 23 Manual Reset Thermal Overload Protector
 Note 24 Automatic Reset Thermal Overload Protector
 Note 25 Non-Protected

Note 61 Sleeve Bearing
 Note 98 50/60 Hertz
 Note LA Limited Availability

General Purpose Single Phase Open Dripproof (ODP) Rigid Base, Capacitor Start



APPLICATIONS:

Designed for air compressors, pumps, conveyors, blowers and general industrial equipment

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Amps	Notes	
1/2	1800	115/230	56	D12C2P	\$246	DS-3F	1.25	9.5	27	8.6/4.3	25	
	1800	115/230	56	8752	\$250	DS-3FMP	1.25	9.7	20	9.0/4.5	24, LA	
	1800	115/208-230	56	D12CA2J	\$250	DS-3F	1.00	11.0	20	9.0/4.3-4.5	24	
	1200	115/208-230	56	D12C3J	\$506	DS-3F	1.00	12.0	34	10.4/5.1-5.2	25	
3/4	3600	115/230	48	6346	\$218	DS-3FMP	1.25	10.3	19	11.8/5.9	23, LA	
	3600	115/208-230	48	D34C1J4	\$178	DS-3FMP	1.00	10.2	18	11.3/5.6-5.7	25	
	3600	115/230	56	8755	\$230	DS-3FMP	1.25	10.3	23	12.0/6.0	23, LA	
	3600	115/230	56	6333	\$220	DS-3FMP	1.25	10.6	19	11.8/5.9	24	
	3600	115/208-230	56	D34C1J	\$185	DS-3FMP	1.25	9.9	27	11.2/5.6	25	
	3600	115/208-230	56	D34CM1J	\$230	DS-3FMP	1.00	11.4	23	10.4/5.3-5.2	23	
	1800	115/230	56	4454	\$310	DS-3FMP	1.25	10.0	25	12.4/6.2	24	
	1800	115/230	56	7902	\$208	DS-3FMP	1.00	10.0	25	11.2/5.6	25, LA	
	1800	115/230	56	D34CM2P	\$328	DS-3F	1.25	10.0	24	11.2/5.6	23	
	1800	115/208-230	56	D34C2J	\$303	DS-3F	1.25	11.4	27	11.4/5.7	25	
	1200	115/230	56H	4396	\$384	DS-3FMP	1.25	12.8	38	11.6/5.8	25	
	1	3600	115/230	56	D1C1P	\$248	DS-3F	1.00	11.3	31	13.4/6.7	25, LA
3600		115/230	56	4142	\$198	DS-3FMP	1.00	11.0	31	13.4/6.8-6.7	25, LA	
3600		115/230	56	6332	\$252	DS-3FMP	1.25	10.6	25	13.8/6.9	24, LA	
3600		115/208-230	56	6344	\$248	DS-3FMP	1.00	11.2	31	13.4/6.7	25	
3600		115/208-230	56	D1CM1J	\$260	DS-3FMP	1.00	11.4	31	14.6/6.9-7.3	23	
1800		115/230	143T	D1C2P14	\$306	DS-3SP	1.15	11.9	35	13.6/6.8	25, LA	
1800		115/208-230	143T	D1C2J14	\$306	DS-3F	1.00	12.0	32	14.8/7.5-7.3	25	
1800		115/208-230	143T	D1CA2J14	\$331	DS-3F	1.00	12.0	30	14.8/7.5-7.3	24	
1800		115/208-230	143T	D1CM2J14	\$346	DS-3F	1.00	12.0	35	14.8/7.5-7.3	23	
1800		115/230	182	D1C2P18Z	\$542	DS-3SP	1.25	12.8	69	14.4/7.2	25	
1800		115/230	56	3759	\$266	DS-3FMP	1.00	12.0	34	16.4/8.2	LA	
1800		115/230	56	D1C2P	\$331	DS-3F	1.25	11.0	31	16.4/8.2	25, LA	
1800		115/230	56H	4328	\$340	DS-3FMP	1.25	10.7	28	13.6/6.8	25	
1800		115/230	56H	8753	\$345	DS-3FMP	1.25	10.7	28	13.6/6.8	24, LA	
1800		115/208-230	56H	D1CA2JH	\$345	DS-3F	1.00	12.0	28	14.8/7.5-7.3	24	
1800		115/208-230	56H	D1CM2JH	\$346	DS-3F	1.00	12.0	31	14.8/7.5-7.3	23	
1800		115/230	56HZ	D1C2PHZ	\$371	DS-3FMP	1.25	11.9	32	13.6/6.8	25, LA	
1200		115/208-230	56H	D1C3JH	\$420	DS-3F	1.00	13.0	44	12.6/6.4-6.3	25	
1-1/2		3600	115/230	143T	D32C1P14	\$368	DS-3FMP	1.15	12.4	31	17.5/8.8	25, LA
		3600	115/208-230	143T	D32C1J14	\$275	DS-3FMP	1.00	12.3	31	18.6/9.8-9.3	25
	3600	115/208-230	56H	D32C1JH	\$275	DS-3FMP	1.00	11.9	31	18.6/9.8-9.3	25	
	3600	115/208-230	56H	D32CM1JH	\$315	DS-3FMP	1.00	11.9	32	18.6/9.8-9.3	23	
	1800	115/230	145T	D32C2P14	\$357	DS-3SP	1.15	12.9	45	20.4/10.2	25, LA	
	1800	115/208-230	145T	D32CA2J14	\$382	DS-3F	1.00	13.0	45	19.2/10.0-9.6	24	
	1800	115/230	184	D32C2P18Z	\$614	DS-3SP	1.15	15.1	71	22.0/11.0	25	
	1800	115/208-230	56	D32CM2J	\$392	DS-3F	1.15	12.4	39	21.4/10.7	25, LA	
	1800	115/230	56H	8754	\$410	DS-3FMP	1.15	12.4	40	18.0/9.0	24, LA	
	1800	115/208-230	56H	D32C2JH	\$400	DS-3FMP	1.00	13.0	37	19.2/10.0-9.6	25	
	1800	115/208-230	56H	D32CA2JH	\$410	DS-3F	1.00	13.0	40	19.2/10.0-9.6	24	
	1800	115/208-230	56H	D32CM2JH	\$420	DS-3F	1.00	13.0	37	19.2/10.0-9.6	23	

Note 23 Manual Reset Thermal Overload Protector
 Note 24 Automatic Reset Thermal Overload Protector
 Note 25 Non-Protected

Note 61 Sleeve Bearing
 Note 98 50/60 Hertz
 Note LA Limited Availability

General Purpose Single Phase Open Dripproof (ODP) Rigid Base, Capacitor Start



APPLICATIONS:

Designed for air compressors, pumps, conveyors, blowers and general industrial equipment

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Amps	Notes
1-1/2	1800	115/230	56HZ	6354	\$406	DS-3FMP	1.15	12.9	39	20.4/10.2	25
	1800	115/230	56HZ	D32CM2PHZ	\$405	DS-3FMP	1.15	12.4	39	20.4/10.2	23
2	3600	115/230	145T	D2C1P14	\$459	DS-3F	1.15	13.1	36	22.4/11.2	25, LA
	3600	115/208-230	145T	D2C1J14	\$459	DS-3F	1.00	12.8	36	22.4/12.4-11.2	25
	3600	115/230	56	6353	\$467	DS-3FMP	1.00	12.0	35	23.0/11.5	25, LA
	3600	115/230	56H	4362	\$480	DS-3FMP	0.00	13.0	35	22.0/11.0	23
	3600	115-208/230	56H	D2C1JH	\$360	DS-3FMP	1.00	12.4	35	22.4/12.4-11.2	25
	1800	115/208-230	145T	D2CM2J14	\$524	DS-3F	1.00	14.0	42	20.0/11.3-10.0	23
	1800	115/230	182T	D2C2P18	\$468	DS-3SP	1.15	14.8	70	23.2/11.6	25
	1800	115/230	213	D2C2P21Z	\$779	DS-3SP	1.15	15.0	75	24.6/12.3	25
	1800	115/230	56H	6352	\$480	DS-3FMP	1.00	13.0	40	21.4/10.7	25, LA
	1800	115/230	56H	D2CA2PH	\$508	DS-3FMP	1.00	12.0	41	19.4/9.7	24
	1800	115/208-230	56H	D2C2JH	\$480	DS-3F	1.00	13.0	40	20.0/11.3-10.0	25
	1800	115/208-230	56H	D2CM2JH	\$524	DS-3F	1.00	14.0	42	20.0/11.3-10.0	23
	1800	115/208-230	56HZ	6355	\$509	DS-3FMP	1.00	14.0	42	21.4/12.2-10.7	24
	1800	115/230	56HZ	D2C2PHZ	\$490	DS-3F	1.15	14.3	42	21.4/12.2-10.7	25
3	3600	115/230	182	D3C1P18	\$631	DS-3SP	1.15	17.3	81	32.0/16.0	25
	3600	208-230	56	D3CM1K	\$525	DS-3F	1.00	13.0	121	15.0-15.0	23
	1800	115/230	184T	D3C2P18	\$590	DS-3SP	1.15	15.8	66	38.0/19.0	25
	1800	115/230	215	D3C2P21	\$984	DS-3SP	1.15	16.9	72	35.6/17.8	25
5	3600	230	184T	D5C1K18	\$650	DS-3SP	1.15	18.0	82	19.6	25
	1800	230	184T	D5C2K18	\$893	DS-3SP	1.15	16.3	76	22.0	25
	1800	230	213T	D5C2K21	\$896	DS-3SP	1.15	17.3	86	22.0	25
	1800	230	215	D5C2K21Z	\$1,304	DS-3SP	1.15	18.9	86	22.0	25
7-1/2	3600	230	213T	D7C1K21	\$813	DS-3SP	1.15	19.1	89	30.3	25
	1800	230	215T	D7C2K21	\$1,026	DS-3SP	1.15	19.9	105	35.5	25
10	3600	230	215T	D10C1K21	\$1,470	DS-3SP	1.15	20.6	92	40.0	25
	1800	230	215T	D10C2K21	\$1,153	DS-3SP	1.15	19.9	150	42.0	25

Note 23 Manual Reset Thermal Overload Protector
 Note 24 Automatic Reset Thermal Overload Protector
 Note 25 Non-Protected

Note 61 Sleeve Bearing
 Note 98 50/60 Hertz
 Note LA Limited Availability