

Special Application Farm Single & Three Phase Direct Drive Poultry Fan



APPLICATIONS:

Designed for direct drive exhaust and vent fans in poultry and livestock houses.

FEATURES:

- Ball Bearings
- 40C Ambient
- TEAO Enclosure except where noted
- Class B Insulation
- Continuous Air Over Duty
- Discount Symbol: **DS-3FMP**

Single Phase, Permanent Split Capacitor

HP	RPM	Voltage	Frame	Catalog Number	List	Mounting	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Amps	Shaft Dim. (inches)	Notes
1/4	1800	115/230	48YZ	FD14AA2P4Z9	\$148	Resilient	1.00	9.9	16	3.4/1.7	0.5 x 2.5	24
1/3	1800	115/230	48YZ	FD13AA2P4Z7	\$163	Yoke	1.00	10.5	19	3.8/1.9	0.5 x 2.375	24
	1200	115	48YZ	FD13AA3N4ZS	\$108	Stud	1.00	8.3	16	5.2	0.5 x 2.5	24
1/2	1800	115/230	48YZ	1850	\$175	Resilient	1.00	10.9	25	5.0/2.5	0.5 x 2.5	24
	1800	115/230	48YZ	FD12AA2P4Z7	\$176	Yoke	1.00	11.1	23	5.0/2.5	0.5 x 2.375	24
	900	115/230	48YZ	8102	\$259	Stud	1.25	10.2	22	6.0/3.0	0.5 x 2.625	24
	900	115/230	48YZ	FD12AA4P4ZS	\$179	Stud	1.00	9.2	23	6.4/3.2	0.625 x 2.625	24
	900	115/230	56Z	FD12AA4P	\$341	Rigid	1.00	11.4	35	6.4/3.2	0.625 x 2.5	24
1	900	230	56CZ	FD1AA4KC	\$320	Face	1.00	13.9	45	5.8	0.625 x 2.5	24
	900	230	56YZ	1837	\$486	Face	1.00	13.3	37	5.2	0.75 x 3.25	

Three Phase

HP	RPM	Voltage	Frame	Catalog Number	List	Mounting	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Amps	Shaft Dim. (inches)	Notes
1	900	440-460	56YZ	8101	\$515	Face	1.00	13.6	24	2.0	0.75 x 3.25	24
1-1/2	900	460	184TCH	UN32S4CKR	\$1,361	Face	1.25	16.9	70	3.9		28, FTLS

Note 24 Automatic Reset Thermal Overload Protector
Note 28 TENV Enclosure

Note FTLS Footless