

General Information

Single Phase Motors

General Purpose Industrial Motors

Premium Efficient Super-E® Motors

Severe Duty Motors

Washdown Duty Motors

Explosion Proof Motors

Pump Motors

Commercial Motors

HVAC Motors

**BALDOR • RELIANCE****Premium Efficient Super-E® Motors****F-2 Mount,  
Three Phase,  
TEFC and ODP,  
Foot Mounted****1 thru 60 Hp****NEMA 145T thru 364T****Applications:** Pumps, compressors, fans, conveyors, machine tools and other applications requiring three phase F-2 mounted motors.**Features:** Copper windings, ball bearings, heavy-gauge steel frame with base seam-welded. EFM Super-E® motors have NEMA Premium® efficiency and 3 year warranty.

Hp	RPM	NEMA Frame	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
<b>Totally Enclosed Fan Cooled</b>											
15	1800	254T	<b>EFM2333T</b>	1,780	L1	23.16	255	92.4	230/460	18.5	1,30
20	1800	256T	<b>EFM2334T</b>	2,156	L1	23.16	286	93	230/460	24	1,30
25	1800	284T	<b>EFM4103T</b>	2,820	L1	27.76	392	93.6	230/460	30	1,30
30	1800	286T	<b>EFM4104T</b>	3,349	L1	27.76	444	94.1	230/460	36	1,30
<b>Open Drip Proof</b>											
1	1800	145T	<b>EFM3116T</b>	478	L1	11.12	36	85.5	208-230/460	1.4	1
1 1/2	1800	145T	<b>EFM3154T</b>	500	L1	12.12	37	88.5	208-230-460	2.1	1
2	1800	145T	<b>EFM3157T</b>	536	L1	13.00	43	86.5	208-230/460	2.7	1
3	1800	182T	<b>EFM3211T</b>	578	L1	15.00	66	90.2	230/460	4	1
5	1800	184T	<b>EFM3218T</b>	633	L1	16.50	84	90.2	230/460	6.6	1,30
7 1/2	1800	213T	<b>EFM3311T</b>	931	L1	16.32	111	91.7	230/460	9.6	1,30
10	1800	215T	<b>EFM3313T</b>	1,127	L1	17.45	123	91.7	230/460	12.5	1,30
15	1800	254T	<b>EFM2513T</b>	1,597	L1	21.69	234	93	230/460	17.7	1,30
20	1800	256T	<b>EFM2515T</b>	2,005	L1	21.69	237	93	230/460	23.5	1,30
25	1800	284T	<b>EFM2531T</b>	2,444	L1	23.81	332	94.1	230/460	30	1,30
30	1800	286T	<b>EFM2535T</b>	2,673	L1	25.06	372	94.1	230/460	35	1,30
40	1800	324T	<b>EFM2539T</b>	3,487	L1	26.69	477	94.5	230/460	46	1,30
50	1800	326T	<b>EFM2543T</b>	3,848	L1	27.69	472	94.5	230/460	57	1,30
60	1800	364T	<b>EFM2547T</b>	4,845	L1	30.69	782	95	230/460	68	1,30

(a) See notes on inside back flap and pages 5-6.

■ Cast Iron Frame