

General Purpose Single Phase, Capacitor Start Totally Enclosed Fan Cooled (TEFC) C-Face Footless



APPLICATIONS:

Designed for air compressors, pumps, conveyors, blowers and general industrial equipment.

FEATURES:

- Double Shielded Ball Bearings
- Class B Insulation, Continuous Duty, 40°C Ambient
- Capacitor Start, Induction Run
- F1 Assembly
- Reversible Rotation

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Amps	Notes
1/6	1800	115/230	42CZ	T16C2P42ZCR	\$194	DS-3FMP	1.00	11.6	17	3.8/2.0	25
	1800	115/208-230	56C	6181	\$247	DS-3FMP	1.15	11.5	18	4.5/2.1-2.2	23
	1200	115/208-230	56C	6182	\$347	DS-3FMP	1.15	11.5	21	4.1/2.0-2.1	23
1/4	1800	115/230	48CZ	T14C2P42ZCR	\$222	DS-3FMP	1.00	11.6	19	4.7/2.4	25
	1800	115/230	56C	T14C2PCR	\$212	DS-3F	1.15	11.5	31	5.0/2.5	25
	1200	115/230	56C	6190	\$202	DS-3FMP	1.00	11.0	26	6.2/3.1	25, LA
	1200	115/208-230	56C	T14C3JCR	\$202	DS-3F	1.15	11.4	26	6.4/3.0-3.2	25
1/3	3600	115/230	56C	6183	\$210	DS-3FMP	1.15	10.6	20	6.4/3.2	25, LA
	3600	115/208-230	56C	T13CA1JCR	\$193	DS-3FMP	1.15	11.7	18	5.5/2.7-2.8	24
	1800	115/230	42CZ	T13C2P42ZCR	\$229	DS-3FMP	1.00	11.6	21	6.2/3.1	25
	1800	115/230	56C	T13C2PCR	\$244	DS-3F	1.15	11.5	31	6.1/3.0	25
	1800	115/208-230	56C	T13CM2JCR	\$259	DS-3F	1.15	11.5	20	6.2/3.1	23, LA
	1800	115/230	56C	8769	\$198	DS-3FMP	1.00	10.3	20	6.6/3.3	25
	1800	100-120/200-240	56C	6191	\$262	DS-3FMP	1.35	12.0	20	4.2-3.9/2.1-2.0	25, 98
	1800	115/208-230	56C	T13CA2JCR	\$244	DS-3F	1.15	11.0	31	6.6/3.0-3.3	24
	1800	115/208-230	56C	T13CM2JCR	\$259	DS-3F	1.15	11.0	20	6.6/3.0-3.3	23
1/2	1200	115/208-230	56C	T13C3JCR	\$351	DS-3F	1.15	11.4	25	6.8/3.4-3.4	25
	3600	115/208-230	56C	T12CA1JCR	\$208	DS-3FMP	1.15	12.1	23	8.0/3.8-4.0	24
	1800	115/230	56C	4415	\$222	DS-3FMP	1.15	-	22	9.0/4.5	25, LA
	1800	115/230	56C	6192	\$319	DS-3FMP	1.15	10.5	23	9.0/4.5	24, LA
	1800	115/230	56C	T12C2PCR	\$282	DS-3F	1.15	11.5	22	9.0/4.5	25, LA
	1800	100-120/200-240	56C	T12C2ZCR	\$344	DS-3FMP	1.25	12.2	25	6.3-5.6/3.1-2.8	25, 98
	1800	115/208-230	56C	T12C2JCR	\$282	DS-3F	1.15	11.0	22	9.0/4.3-4.5	25
	1800	115/208-230	56C	T12CA2JCR	\$319	DS-3F	1.15	11.4	23	9.0/4.3-4.5	24
	1800	115/208-230	56C	T12CM2JCR	\$297	DS-3F	1.15	11.4	20	9.0/4.3-4.5	23
3/4	1200	115/208-230	56C	T12C3JCR	\$532	DS-3F	1.15	11.4	22	10.4/5.1-5.2	25
	3600	115/208-230	56C	T34C1JCR	\$250	DS-3F	1.15	12.0	34	9.2/4.6	25, LA
	3600	115/230	56C	4291	\$260	DS-3FMP	1.00	11.0	26	10.2/5.1	24
	1800	115/230	56C	6194	\$374	DS-3FMP	1.15	10.6	27	11.4/5.7	24, LA
	1800	100-120/200-240	56C	T34C2ZCR	\$406	DS-3FMP	1.25	12.4	32	9.2-8.4/4.6-4.2	25, 98
	1800	115/208-230	56C	T34C2JCR	\$339	DS-3F	1.15	11.9	25	11.4/5.7-5.7	25
	1800	115/208-230	56C	T34CA2JCR	\$374	DS-3F	1.15	11.9	27	11.4/5.7-5.7	24
	1800	115/208-230	56C	T34CM2JCR	\$354	DS-3F	1.15	11.6	24	11.4/5.7-5.7	23
	1200	115/230	56C	6195	\$599	DS-3FMP	1.00	13.1	28	12.2/6.1	25, LA
1200	115/208-230	56C	T34C3JCR	\$599	DS-3F	1.15	13.4	28	10.8/5.4-5.3	25	

Note 23 Manual Reset Thermal Overload Protector
 Note 24 Automatic Reset Thermal Overload Protector
 Note 25 Non-protected

Note 98 50/60 Hertz
 Note LA Limited Availability

GEN. PURPOSE SINGLE PHASE
 GEN. PURPOSE THREE PHASE
 SEVERE DUTY
 HAZARDOUS LOCATION
 C-FACE SINGLE & THREE PHASE
 MULTI-SPEED THREE PHASE
 INVERTER DUTY
 VECTOR DUTY
 DRIVES
 BRAKE MOTORS
 U FRAME MOTORS
 DIRECT CURRENT (DC)

General Purpose Single Phase, Capacitor Start Totally Enclosed Fan Cooled (TEFC) C-Face Footless



APPLICATIONS:

Designed for air compressors, pumps, conveyors, blowers and general industrial equipment.

HP	RPM	Voltage	Frame	Catalog Number	List	Discount Symbol	SF	"C" Dim. (inches)	Ship Wt. (lbs.)	Full Load Amps	Notes
1	3600	115/208-230	56C	T1CA1JCR	\$304	DS-3FMP	1.15	12.39	27	13.6/6.9-6.8	24
	1800	115/208-230	143TC	T1C2J14CR	\$410	DS-3F	1.15	13.1	30	14.0/6.9-7.0	25
	1800	115/208-230	143TC	T1CA2J14CR	\$435	DS-3F	1.15	13.1	33	14.0/6.9-7.0	24
	1800	115/208-230	143TC	T1CM2J14CR	\$450	DS-3F	1.15	12.0	30	14.0/6.9-7.0	23
	1800	100-120/200-240	56C	6219	\$414	DS-3FMP	1.15	12.6	40	11.0-9.2/5.5-4.7	25, 98
	1800	115/208-230	56C	T1C2JCR	\$367	DS-3F	1.15	13.1	43	14.0/6.9-7.0	25
	1800	115/208-230	56C	T1CA2JCR	\$392	DS-3F	1.15	12.0	43	14.0/6.9-7.0	24
	1800	115-208/230	56C	T1CM2JCR	\$407	DS-3F	1.15	13.1	24	14.0/6.9-7.0	23
	1200	115/208-230	56C	T1C3JCR	\$650	DS-3F	1.15	14.0	44	12.6/6.6-6.3	25
1-1/2	3600	115/208-230	143TC	T32C1J14CR	\$370	DS-3FMP	1.15	12.94	32	14.6/8.1-7.4	25
	3600	115/208-230	56C	T32C1JCR	\$361	DS-3F	1.15	13.6	34	16.8/8.4	25
	3600	115/208-230	56C	T32CA1JCR	\$370	DS-3FMP	1.15	12.89	32	14.6/8.1-7.4	24
	1800	115/208-230	145TC	T32C2J14CR	\$465	DS-3F	1.15	13.1	47	14.4/8.0-7.2	25
	1800	115/208-230	145TC	T32CA2J14CR	\$490	DS-3F	1.15	14.0	47	14.4/8.0-7.2	24
	1800	115/208-230	145TC	T32CM2J14CR	\$505	DS-3F	1.15	14.0	47	14.4/8.0-7.2	23
	1800	115/208-230	56C	T32C2JCR	\$418	DS-3F	1.15	13.1	31	14.4/8.0-7.2	25
	1800	115/208-230	56C	T32CA2JCR	\$443	DS-3F	1.15	14.0	31	14.4/8.0-7.2	24
	1800	115/208-230	56C	T32CM2JCR	\$458	DS-3F	1.15	14.0	31	14.4/8.0-7.2	23
2	3600	115/230	143TC	6198	\$549	DS-3FMP	1.15	14.0	34	20.4/10.2	25, LA
	3600	115/208-230	145C	T2C1J14CR	\$472	DS-3FMP	1.15	13.44	34	19.5/10.8-9.7	25
	3600	115/208-230	56C	T2CA1JCR	\$472	DS-3FMP	1.15	13.39	40	19.5/10.8-9.7	24
	1800	115/208-230	145TC	T2CM2J14CR	\$663	DS-3F	1.15	14.0	40	18.9/10.3-9.4	23
	1800	115/208-230	145TC	T2C2J14CR	\$623	DS-3F	1.15	14.0	35	18.9/10.3-9.4	25
	1800	115/208-230	145TC	T2CA2J14CR	\$648	DS-3F	1.15	14.0	40	18.9/10.3-9.4	24
	1800	115/208-230	56C	T2C2JCR	\$475	DS-3F	1.15	14.0	31	18.9/10.3-9.4	25
	1800	115/208-230	56C	T2CA2JCR	\$500	DS-3F	1.15	14.0	31	18.9/10.3-9.4	24
	1800	115/208-230	56C	T2CM2JCR	\$515	DS-3F	1.15	14.0	31	18.9/10.3-9.4	23

Note 23 Manual Reset Thermal Overload Protector

Note 24 Automatic Reset Thermal Overload Protector

Note 25 Non-protected

Note 98 50/60 Hertz

Note LA Limited Availability