

# Classic Valves/Boiler Drains



125 PSI/8.6 Bar Non-Shock Cold Working Pressure to 100° F

Maximum Temperature 180° F/82° C





## Boiler Drains (Female to Hose) 73-CL

| Size              | Dimensions |     | Weight |     |
|-------------------|------------|-----|--------|-----|
|                   | B          |     | Lbs.   | Kg. |
|                   | In.        | mm. |        |     |
| 1/2 <sup>Cl</sup> | 3.25       | 83  | 50     | 23  |
| 3/4 <sup>Cl</sup> | 3.31       | 84  | 50     | 23  |





## Quarter Turn Boiler Drains (Cup or Male Threads to Hose) QT74X

| Size | Dimensions |     |      |     | Weight |     |
|------|------------|-----|------|-----|--------|-----|
|      | A          |     | B    |     | Lbs.   | Kg. |
|      | In.        | mm. | In.  | mm. |        |     |
| 1/2  | 2.64       | 00  | 1.57 | 00  | .40    |     |
| 3/4  | 2.72       | 00  | 1.65 | 00  | .42    |     |



## Boiler Drains (FIT to Hose) 74-2

| Size             | Dimensions |     | Weight |     |
|------------------|------------|-----|--------|-----|
|                  | B          |     | Lbs.   | Kg. |
|                  | In.        | mm. |        |     |
| 1/2 <sup>C</sup> | 3.38       | 56  | .40    | 18  |



## Boiler Drains (Cup or Male to Hose) 74-CL

| Size               | Dimensions |     | Weight |     |
|--------------------|------------|-----|--------|-----|
|                    | B          |     | Lbs.   | Kg. |
|                    | In.        | mm. |        |     |
| 1/2 <sup>Cl</sup>  | 3.69       | 94  | 50     | 23  |
| 3/4 <sup>Cl*</sup> | 3.75       | 95  | 50     | 23  |

\*3/4 furnished in male threads only.

