

Specifications for all valves



Handlever[†] Material:
Aluminum, Epoxy coated
Polyamide PA 6, 30% glass fibers reinforced



Pneumatic[†] Actuators:
Air Supply 90 psi



Gearbox[†] Material:
Aluminum, Polyurethan coated
Cast Iron, Polyurethan coated

Nominal Bore (ID)*		Pressure Range	Cv	Shaft
mm	Inch	psi	(gal/min)	
40	1-1/2"	0-240	-	Stainless Steel 1.4028, AISI420
50	2"	0-240	421.20	Stainless Steel 1.4404, AISI316
65	2-1/2"	0-240	596.70	
80	3"	0-240	1006.20	
100	4"	0-240	1579.50	
125	5"	0-240	2761.20	
150	6"	0-240	4188.60	
200	8"	0-240	6165.90	
250	10"	0-240	4188.60	
300	12"	0-240	6165.90	
350	14"	0-240	-	
400	16"	0-240	-	
450	18"	0-240	-	
500	20"	0-240	-	
600	24"	0-240	-	
700	28"	0-150	-	
800	32"	0-150	-	
900	36"	0-150	-	
1000	40"	0-150	-	
1100	44"	0-150	-	
1200	48"	0-150	-	

Disc	Liner*	Body Type	Body Material
Ductile Iron GGG40	EPDM	Wafer	Ductile Iron
Relson coated,	EPDM HT	LUG Body	Stainless steel
Ductile Iron GGG40	Nitrile	Flange Body	
Epoxy coated,	Nitrile carboxylit		
Cast Iron	Natural rubber		
Relson coated,	Butyl		
Cast Iron	Hypalon		
Epoxy coated.	Silicon		
	Viton		

*White liners on request

[†] Others styles available