

Model: 72

Bronze, Ductile Iron, Carbon Steel or Stainless Steel SURE CHECK™ Valves Sizes: 2" - 54" (50 - 1350mm)

Pressure/Temperature-Non-Shock		
Model	Material	Rating
72D	Carbon Steel	285psi @ -20°F to 100°F
		19.65 bar @ 37.78°C
		140psi @ 600°F
72B	Bronze	9.65 bar @ 315.140°C
		225psi @ -20°F to 150°F
		15.51 bar @ 65.56°C
72H	Stainless Steel	150psi @ 406°F
		10.34 bar @ 207.78°C
		275psi @ -20°F to 100°F
72I	Ductile Iron	18.96 bar @ 37.78°C
		170psi @ 500°F
		11.72 bar @ 260.00°C

*Seat and/or Spring Materials may limit temperature.

See "How To Order" chart for limitations.

72

Class 150



Model 72



Typical Service

- Designed for liquids and gases where flow reversal can cause surge and water hammer.
- Elastomer seats provide bubble-tight shutoff.

Features

- Compact design with short face-to-face dimensions for minimum space requirements.
- Dual shaft design allows interchangeability of shafts.
- Torsion springs close the valve prior to flow reversal.
- Torsion springs exert a lifting motion on the discs, enabling the center "heel" to open first. This prevents excessive wear of the seat in this area, and provides a consistent wear pattern and long sealing capability.
- Downstream stop shaft stabilizes the discs at high flow rates and prevents them from striking each other, which can cause premature wear, stress on the shaft, and chattering.

Construction

- Robust cast body is wafer style, featuring compact face-to-face dimensions.
- Designed to fit within ANSI bolt circles.
- Variety of trim and seat materials are available, including overlay and metal-to-metal.

Installation

- Can be installed horizontally or vertically.
 - Consult factory for downward vertical flow applications.
 - In horizontal applications, shaft should be in vertical orientation.
- Good piping practice recommends installing a distance of 5 to 10 pipe diameters from elbows, pumps, or others turbulence-creating devices.
- Mueller Steam Specialty strongly recommends the installation of a strainer ahead of the pump to ensure protection of both the pump and the valve from foreign particles.

Special Coatings or Treatments

- For Stainless Steel, pickling and passivation available on request, consult factory

Approvals/Specifications

- Applicable ASTM, ANSI, and API standards
- FM Approved
 - Sizes 2" - 14"

Testing

- API 598


Material

	72B	72D
Body	Bronze ASTM B62 (85-5-5-5)	Carbon Steel ASTM A216 Gr. WCB
Disc	Bronze ASTM B62 (85-5-5-5)	Carbon Steel ASTM A216 Gr. WCB
Shaft/spring	316 SS	316 SS
Seat	Buna-N	Buna-N
	72H	72I
Body	Stainless Steel ASTM A351 Gr. CF8M	Ductile Iron ASTM 536
Disc	Stainless Steel ASTM A351 Gr. CF8M	Ductile Iron ASTM 536
Shaft/spring	316 SS	316 SS
Seat	Buna-N	Buna-N

See Sure Check™ information section in the Mueller Steam Specialty Engineering binder for alternate materials and How To Order options.

Dimensions and Weights

SIZE		DIMENSIONS								WEIGHT	
		A		B		C		D (NPT)			
in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	lbs.	kgs.
2	50	4 $\frac{1}{8}$	104.8	2 $\frac{3}{8}$	60.3	-	-	-	-	5	2.3
2 $\frac{1}{2}$	65	4 $\frac{7}{8}$	123.8	2 $\frac{5}{8}$	66.7	-	-	-	-	7.5	3.4
3	80	5 $\frac{3}{8}$	136.5	2 $\frac{7}{8}$	73.0	2 $\frac{1}{8}$	54.0	$\frac{1}{4}$	6.35	9.5	4.3
4	100	6 $\frac{7}{8}$	174.6	2 $\frac{7}{8}$	73.0	3 $\frac{11}{16}$	93.7	$\frac{7}{8}$	22.2	16	7.3
5	125	7 $\frac{3}{4}$	196.9	3 $\frac{3}{8}$	85.7	4 $\frac{7}{16}$	112.7	1	25.4	21	9.5
6	150	8 $\frac{3}{4}$	222.3	3 $\frac{7}{8}$	98.4	5 $\frac{5}{8}$	142.9	1 $\frac{3}{8}$	34.9	29	13.2
8	200	11	279.4	5	127	7 $\frac{1}{4}$	184.2	1 $\frac{3}{4}$	44.5	52	23.6
10	250	13 $\frac{3}{8}$	339.7	5 $\frac{3}{4}$	146.1	9 $\frac{9}{16}$	242.9	2 $\frac{3}{4}$	69.9	93	42.2
12	300	16 $\frac{1}{8}$	409.6	7 $\frac{1}{8}$	181.0	11 $\frac{1}{4}$	285.8	3	76.2	147	66.7
14	350	17 $\frac{3}{4}$	450.9	7 $\frac{1}{4}$	184.2	12	304.8	3 $\frac{1}{8}$	79.4	220	99.8
16	400	20 $\frac{1}{4}$	514.4	7 $\frac{1}{2}$	190.5	14 $\frac{7}{16}$	366.7	4 $\frac{3}{8}$	111.1	240	109
18	450	21 $\frac{5}{8}$	549.3	8	203.2	16 $\frac{5}{16}$	414.3	5 $\frac{1}{8}$	130.2	280	127
20	500	23 $\frac{7}{8}$	606.4	8 $\frac{5}{8}$	219.0	18 $\frac{1}{4}$	463.6	6	152.4	400	182
24	600	28 $\frac{1}{4}$	717.6	8 $\frac{3}{4}$	222.3	22 $\frac{11}{16}$	576.3	8 $\frac{1}{2}$	215.9	560	254
30	750	34 $\frac{3}{4}$	882.7	12	304.8	28 $\frac{23}{32}$	729.5	11	279.4	1100	499
36	900	41 $\frac{1}{4}$	1047.8	15 $\frac{1}{4}$	387.4	33 $\frac{1}{2}$	850.9	11 $\frac{3}{8}$	289.0	1415	642
42	1050	48	1219.2	17	431.6	41	1041.1	15 $\frac{1}{4}$	387.4	2120	962
48	1200	54 $\frac{1}{2}$	1384.3	20 $\frac{5}{8}$	523.9	47	1193.8	16 $\frac{3}{4}$	425.5	3660	1660
54	1500	61	1549.4	21 $\frac{1}{4}$	539.8	49	1244.6	16 $\frac{1}{2}$	419.1	4600	2087



Apply for Certified Drawings

Mueller Steam Specialty product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Mueller Steam Specialty Technical Service. Mueller Steam Specialty reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Mueller Steam Specialty products previously or subsequently sold.



A Division of Watts Water Technologies, Inc.

USA: 1491 NC Hwy 20 West St. Pauls, NC 28384; www.muellersteam.com

Tel: 910-865-8241 Fax: 910-865-6220

Toll Free Phone 1-800-334-6259 Toll Free Fax: 1-800-421-6772