

FITTINGS

Figure 419 Tee & Figure 460 End Cap




Figure 419 Tee




Figure 460
End Cap

**STAINLESS
STEEL
SYSTEM**

| Nominal Size Inches mm | 419 Tee | | | | |
|------------------------------|---------------------------|------------------------|-----------------------------|------------------------|-----------------------------|
| | Full Flow | | | Fabricated | |
| | Pipe O.D. Inches mm | C to E Inches mm | Approx. Weight lbs kg | C to E Inches mm | Approx. Weight lbs kg |
| 1 | 1.315 | 2.88 | 1.0 | | |
| 25 | 33.4 | 73.2 | 0.5 | | |
| 1¼ | 1.660 | 3.13 | 1.0 | 2.75 | 1.3 |
| 32 | 42.4 | 79.5 | 0.5 | 69.8 | 0.6 |
| 1½ | 1.900 | 3.38 | 1.6 | 2.75 | 1.5 |
| 40 | 48.3 | 85.9 | 0.7 | 69.8 | 0.7 |
| 2 | 2.375 | 4.00 | 2.3 | 3.25 | 2.1 |
| 50 | 60.3 | 101.6 | 1.0 | 82.5 | 0.9 |
| 2½ | 2.875 | 3.07 | 2.2 | 3.75 | 2.8 |
| 65 | 73.0 | 78.0 | 1.0 | 95.2 | 1.3 |
| 3 | 3.500 | 3.77 | 3.1 | 4.25 | 3.9 |
| 80 | 88.9 | 95.8 | 1.4 | 107.9 | 1.8 |
| 4 | 4.500 | 4.47 | 4.9 | 5.00 | 7.8 |
| 100 | 114.3 | 113.5 | 2.2 | 127.0 | 3.2 |
| 5 | 5.563 | 5.91 | 7.1 | | |
| 125 | 141.3 | 150.1 | 3.2 | | |
| 6 | 6.625 | 5.91 | 11.7 | 6.50 | 15.2 |
| 150 | 168.3 | 150.1 | 5.3 | 165.1 | 6.9 |
| 8 | 8.625 | 7.79 | 20.0 | 7.75 | 18.1 |
| 200 | 219.1 | 197.9 | 9.1 | 1196.8 | 8.2 |
| 10 | 10.750 | 8.89 | 34.4 | 9.00 | 36.5 |
| 250 | 273.0 | 225.8 | 15.6 | 228.6 | 16.2 |
| 12 | 12.750 | 10.39 | 52.5 | 10.00 | 51.4 |
| 300 | 323.9 | 263.9 | 23.8 | 254.0 | 23.4 |

Please refer to General Notes on page 17.

| Nominal Size Inches mm | 460 Cap | | | | |
|------------------------------|---------------------------|------------------------|-----------------------------|------------------------|-----------------------------|
| | Full Flow | | | Fabricated | |
| | Pipe O.D. Inches mm | E to E Inches mm | Approx. Weight lbs kg | E to E Inches mm | Approx. Weight lbs kg |
| 1 | 1.315 | .875 | 0.2 | 1.63 | 0.20 |
| 25 | 33.4 | 22.2 | 0.1 | 41.3 | 0.10 |
| 1¼ | 1.660 | .875 | .04 | 1.63 | 0.3 |
| 32 | 42.4 | 22.2 | 0.2 | 41.3 | 0.1 |
| 1½ | 1.900 | .875 | 0.5 | 1.63 | 0.4 |
| 40 | 48.3 | 22.2 | 0.2 | 41.3 | 0.2 |
| 2 | 2.375 | .875 | 0.7 | 1.63 | 0.5 |
| 50 | 60.3 | 22.2 | 0.3 | 41.3 | 0.2 |
| 2½ | 2.875 | .875 | 1.0 | 1.75 | 0.7 |
| 65 | 73.0 | 22.2 | 0.5 | 44.5 | 0.3 |
| 3 | 3.500 | .875 | 2.0 | 1.75 | 1.0 |
| 80 | 88.9 | 22.2 | 0.9 | 44.5 | 0.4 |
| 4 | 4.500 | .875 | 3.1 | 1.75 | 1.6 |
| 100 | 114.3 | 22.2 | 1.4 | 44.5 | 0.7 |
| 5 | 5.563 | 3.00* | 2.3 | | |
| 125 | 141.3 | 76.2 | 1.0 | | |
| 6 | 6.625 | 3.50* | 1.5 | 1.88 | 3.7 |
| 150 | 168.3 | 88.9 | 0.7 | 47.6 | 1.7 |
| 8 | 8.625 | 4.00* | 3.1 | 4.00 | 8.0 |
| 200 | 219.1 | 101.6 | 1.4 | 101.6 | 3.6 |
| 10 | 10.750 | 5.00* | 6.0 | 4.00 | 11.5 |
| 250 | 273.0 | 127.0 | 2.7 | 101.6 | 5.2 |
| 12 | 12.750 | 6.00* | 7.8 | 4.00 | 15.1 |
| 300 | 323.9 | 152.4 | 3.5 | 101.6 | 6.8 |

*Dished Cap