

COUPLINGS

Figures 650 & 652 Concentric Reducer



FIGURE 650 CONCENTRIC REDUCER
GROOVE X GROOVE
CAST





FIGURE 652 CONCENTRIC REDUCER
GROOVE X CUP
WROT COPPER



**COPPER
GROOVED
SYSTEM**

Nominal Size Inches mm	650 Groove x Groove	
	E to E Inches mm	Approx. Weight lbs kg
2½ x 2 65 x 50	3.29 83,6	1.4 0,6
3 x 2 80 x 50	2.50 63,5	1.4 0,6
3 x 2½ 80 x 65	2.50 63,5	1.4 0,6
4 x 2 100 x 50	4.75 120,7	3.2 1,5
4 x 2½ 100 x 65	3.00 76,2	2.3 1,1
4 x 3 100 x 80	3.00 76,2	2.4 1,1
5 x 3 125 x 80	3.88 98,6	3.8 1,7
5 x 4 125 x 100	3.38 85,9	3.8 1,7
6 x 3 150 x 80	4.38 111,3	5.0 2,3
6 x 4 150 x 100	3.88 98,6	5.1 2,3
6 x 5 150 x 125	3.38 85,9	4.9 2,2
8 x 6 200 x 150	5.00 127,0	9.5 4,3

Nominal Size Inches mm	652 Groove x Groove x Cup		
	E to E Inches mm	Cup Inches mm	Approx. Weight lbs kg
2 x 1 50 x 25	2.70 68,6	0.91 23,1	0.5 0,2
2 x 1¼ 50 x 32	3.00 76,2	0.97 24,6	0.4 0,2
2 x 1½ 50 x 40	2.94 74,7	1.09 27,7	0.4 0,2
2½ x 1 65 x 25	2.28 57,9	0.91 23,1	0.5 0,2
2½ x 1¼ 65 x 32	3.52 89,4	0.97 24,6	0.6 0,3
2½ x 1½ 65 x 40	3.45 87,6	1.09 27,7	0.6 0,3
2½ x 2 65 x 50	3.30 83,8	1.34 34,0	0.6 0,3
3 x 1½ 80 x 40	2.59 65,8	1.09 27,7	0.7 0,3
3 x 2 80 x 50	4.10 104,1	1.34 34,0	1.0 0,5
4 x 2 100 x 50	3.41 86,6	1.34 34,0	1.4 0,6

Please refer to General Notes on page 17.