

FITTINGS

Figure 391, 392 & 393 Adapter Nipples

FITTINGS

Nominal Size Inches mm	Pipe OD Inches mm	391, 392 & 393 Fabricated	
		Nominal E to E Inches mm	Approx Weight Lbs. Kg
1¼	1.660	4.00	0.8
32	42.4	101.6	0.4
1½	1.900	4.00	0.9
40	48.3	101.6	0.4
2	2.375	4.00	1.2
50	60.3	101.6	0.5
2½	2.875	4.00	1.9
65	73.0	101.6	0.9
3	3.500	4.00	2.5
80	88.9	101.6	1.1
4	4.500	6.00	5.5
100	114.3	152.4	2.5
5	5.563	6.00	7.4
125	141.3	152.4	3.4
6	6.625	6.00	9.5
150	168.3	152.4	4.3
8	8.625	6.00	14.2
200	219.1	152.4	6.4
10	10.750	8.00	27.0
250	273.0	203.2	12.2
12	12.750	8.00	33.0
300	323.9	203.2	15.0



FIGURE 391
GROOVE x MALE THREAD




FIGURE 392
GROOVE x GROOVE




FIGURE 393
GROOVE x PLAIN END




Figure 395 Hose Adapter Nipple

395 Fabricated		
Nominal Size Inches mm	End to End Inches mm	Approx Weight Lbs. Kg
1	3.25	0.4
25	82.6	0.2
1¼	3.63	0.7
32	92.1	0.3
1½	4.00	0.8
40	101.6	0.4
2	4.63	1.3
50	117.5	0.6
2½	5.50	2.1
65	139.7	1.0
3	6.00	3.3
80	152.4	1.5
4	7.25	5.5
100	184.2	2.5
5	9.75	8.1
125	247.7	3.7
6	11.00	13.2
150	279.4	6.0
8	12.50	24.0
200	317.5	10.9
10	14.00	29.0
250	355.6	13.2
12	16.00	46.0
300	406.4	20.9



FIGURE 395
HOSE ADAPTER NIPPLE





Figure 380 Female Thread Adapter

380 Fabricated			
Nominal Size Inches mm	Grooved End OD Inches mm	End to End Inches mm	Approx Weight Lbs. Kg
1	1.32	2 ¹ / ₁₆	0.7
25	33.4	53.3	0.3
1¼	1.66	2 ⁵ / ₁₆	1.4
32	42.2	63.5	0.6
1½	1.90	2 ⁵ / ₁₆	1.5
40	48.3	63.5	0.7
2	2.38	2½	1.6
50	60.3	64	0.7
3	3.50	2¾	2.5
80	88.9	70	1.1
4	4.50	3¾	4.5
100	114.3	83	2.0



FIGURE 380 ADAPTER
GROOVE x FEMALE
THREAD ADAPTER



Please refer to General Notes on page 17.