


SOCKET WELD FITTINGS TEES



Socket Depth =
Dimension A minus Dimension C

Class 3000

Pipe Size	1/8	1/4	3/8	1/2	3/4	1	1 1/4	1 1/2	2	2 1/2	3	4
Dimension A	13/16	13/16	31/32	1 1/8	1 5/16	1 1/2	1 3/4	2	2 3/8	3	3 3/8	4 3/16
Dimension B	7/8	7/8	1 3/64	1 5/16	1 1/2	1 13/16	2 1/4	2 1/2	3 1/32	3 11/16	4 3/8	5 3/4
Dimension C	7/16	7/16	17/32	5/8	3/4	7/8	1 1/16	1 1/4	1 1/2	1 5/8	2 1/4	2 5/8
Dimension D	.420	.555	.690	.855	1.065	1.330	1.675	1.915	2.406	2.906	3.535	4.545
Approx. Wt. #	.23	.19	.33	.71	.87	1.44	2.19	2.98	4.57	8.60	13.00	31.30

Class 6000

Pipe Size	1/8	1/4	3/8	1/2	3/4	1	1 1/4	1 1/2	2	2 1/2	3	4
Dimension A	13/16	31/32	1 1/8	1 5/16	1 1/2	1 3/4	2	2 3/8	2 1/2	3 1/4	3 3/4	4 1/2
Dimension B	7/8	1 3/64	1 5/16	1 1/2	1 13/16	2 1/4	2 1/2	3 1/32	3 5/16	4	4 3/4	6
Dimension C	7/16	17/32	5/8	3/4	7/8	1 1/16	1 1/4	1 1/2	1 5/8	2 1/4	2 1/2	2 7/8
Dimension D	.420	.555	.690	.855	1.065	1.330	1.675	1.915	2.406	2.906	3.535	4.545
Approx. Wt. #	---	---	---	1.16	1.94	3.17	3.95	7.13	7.72	15.30	23.10	34.90

Class 9000

Pipe Size	1/8	1/4	3/8	1/2	3/4	1	1 1/4	1 1/2	2	2 1/2	3	4
Dimension A	---	---	---	1 1/2	1 3/4	2	2 3/8	2 1/2	3	---	---	---
Dimension B	---	---	---	1 13/16	2 1/4	2 1/2	3 1/32	3 5/16	3 11/16	---	---	---
Dimension C	---	---	---	1	1 1/8	1 1/4	1 3/8	1 1/2	2 1/8	---	---	---
Dimension D	---	---	---	.855	1.065	1.330	1.675	1.915	2.406	---	---	---
Approx. Wt. #	---	---	---	2.37	4.00	5.35	6.50	7.88	8.75	---	---	---

[Back to Capitol's Table of Contents](#)