



THREADED FITTINGS FULL AND HALF COUPLINGS



Full Coupling, Reducer

Class 3000 (Weight # refers to Full Coupling Only)

Pipe Size	1/81	1/42	3/81	1/21	3/41	1	1 1/4	1 1/2	2	2 1/2	3	4
Dimension A	1 1/4	1 3/8	1 1/2	1 7/8	2	2 3/8	2 5/8	3 1/8	3 3/8	3 5/8	4 1/4	4 3/4
Dimension B	3/4	3/4	7/8	1 1/8	1 3/8	1 3/4	2 1/4	2 1/2	3	3 5/8	4 1/4	5 1/2
Approx. Wt. #	.11	.10	.13	..28	.42	.85	1.50	2.19	3.02	4.56	6.79	12.00

Class 6000 (Weight # refers to Full Coupling Only)

Pipe Size	1/81	1/42	3/81	1/21	3/41	1	1 1/4	1 1/2	2	2 1/2	3	4
Dimension A	1 1/4	1 3/8	1 1/2	1 7/8	2	2 3/8	2 5/8	3 1/8	3 3/8	3 5/8	4 1/4	4 3/4
Dimension B	7/8	1	1 1/4	1 1/2	1 3/4	2 1/4	2 1/2	3	3 5/8	4 1/4	5	6 1/4
Approx. Wt. #	.18	.14	.40	.69	.90	1.88	2.31	4.00	7.50	9.25	13.44	22.13

Half Coupling

Class 3000

Pipe Size	1/81	1/42	3/81	1/21	3/41	1	1 1/4	1 1/2	2	2 1/2	3	4
Dimension A	5/8	11/16	3/4	15/16	1	1 3/16	1 5/16	1 9/16	1 11/16	1 13/16	2 1/8	2 3/8
Dimension B	3/4	3/4	7/8	1 1/8	1 3/8	1 3/4	2 1/4	2 1/2	3	3 5/8	4 1/4	5 1/2
Approx. Wt. #	.06	.05	.06	.14	.21	.43	.75	1.09	1.57	2.28	3.40	6.00

Class 6000

Pipe Size	1/81	1/42	3/81	1/21	3/41	1	1 1/4	1 1/2	2	2 1/2	3	4
Dimension A	5/8	11/16	3/4	15/16	1	1 3/16	1 5/16	1 9/16	1 11/16	1 13/16	2 1/8	2 3/8
Dimension B	7/8	1	1 1/4	1 1/2	1 3/4	2 1/4	2 1/2	3	3 5/8	4 1/4	5	6 1/4
Approx. Wt. #	.09	.07	.20	.35	.45	.94	1.15	2.00	3.75	4.62	6.72	11.06