

Five-Disc CD Changer with RS-232C

PMD371



The Marantz Professional PMD371 five-disc CD changer provides up to six hours of uninterrupted music on five discs, and allows up to three discs to be changed while playing. It plays finalized CD-R and CD-RW discs and displays CD and track titles in CD text. The PMD371 is ideal for background music applications, with random play modes and easy programming of play options. It includes an RS-232C port for AMX and Crestron wired control and is packaged with a custom rackmount kit to ensure smooth integration into installations.



Features RS-232

Key Features

- RS-232C serial port (1-way)
- Plays CD, CD-R, CD-RW
- Random play of one disc or all discs
- Program play
- Edit play list to fit length of tape
- Intros can
- A-B loop
- Precision optics and circuitry
- Optical digital out (SPDIF)
- Coaxial digital out
- Headphone jack
- Includes custom rackmount kit
- IR remote (works with Marantz RC-5200P and RC-9200P; touch panel remotes sold separately)

Background Music Applications

The PM371 can play tracks in a random sequence on a single disc or an entire changer full of discs. Intros can lets a user hear the first 10 seconds of every song as an aide in song selection when programming play. It's easy to select and delete songs when creating a program list. When connected to a Marantz tape deck, the PMD371 can edit play lists to fit tape length.

RS-232C for Wired Control


The PMD371 can receive AMX or Crestron compatible control signals via its rear panel RS-232C serial port. It can also accept RC5 commands through this port.

Marantz Performance

The PMD371 is built with precision optics and circuitry for outstanding sound quality.

Accessories

- Custom rackmount kit
- IR remote control unit with 2 AA dry cell batteries
- RCA audio cables
- Operating instructions



PMD371

Specifications

System

Audio Performance

Number of Channels	2
Frequency Response	20 ~ 20,000 Hz +/- 0.5 dB
Signal-to-Noise Ratio	105 dB
Dynamic Range	95 dB
Total Harmonic Distortion	0.005%
Wow and Flutter	Quartz crystal precision
Sampling Frequency	44.1 kHz
D/A Conversion	1 bit P.L.M.
Oversampling	8 times

Outputs

Optical Digital Output (SPDIF)	-19 dBm
Coaxial Digital Output (SPDIF)	0.5 Vp-p (75Ω)
RCA Output	2 V RMS
RS-232C Serial Port	D-sub 9-pin (male) 1-way
RC5 Output	1-way IR command set
General	
Power Requirements	AC 120V, 60 Hz 14W
Dimensions with Rack Kit (W x H x D)	19" x 3U x 12"
Weight	12.8 lbs. (5.8 kg)

Specifications are based on measurement conditions and proper care for the machine, and are subject to change without notice.



D&M Professional

1100 Maplewood Drive Itasca, Illinois 60143
Tel: 630.741.0330 Fax: 630.741.0652
www.d-mpro.com

© 2004 D&M Professional. All rights reserved.



DENON
PROFESSIONAL

marantz
PROFESSIONAL

1 2 3 4 5 6 7 8 9
min | max
LEVEL