

NEW!




VST-36/40/47/52-SI

Articulated/Telescopic Aerial Lift

DEMAND BETTER

Up to 1,000 lbs. of Jib Capacity

100° Hydraulic Platform Rotation



• Working Height: Up to 56' 2" on a Non-CDL Chassis

• Horizontal Reach: Up to 31' 5"

• Platform Capacity: Up to 450 lbs.

| RETRACTED | EXTENDED | "B" | "C" |
|--------------|--------------|-----------|-------------|
| 165.5 (4204) | 281.5 (7150) | 41 (1041) | 73.6 (1870) |
| | | 47 (1194) | 79.6 (2027) |
| | | 53 (1346) | 85.6 (2183) |



For more information about the All-New VST-SI series or any of the other outstanding VERSALIFT machines, contact your authorized VERSALIFT Distributor or call 1.800.825.1085



VST-36/40/47/52-SI

Articulated/Telescopic Aerial Lift

GENERAL SPECIFICATIONS

(Based on 40" frame)

| | VST-36-SI | VST-40-SI | VST-47-SI | VST-52-SI |
|-----------------------|-----------|-----------|-----------|-----------|
| Horizontal reach | 26'-10" | 30'-10" | 31'-5" | 31'-0" |
| Max platform capacity | 450 lbs. | 450 lbs. | 400 lbs. | 400 lbs. |
| Platform rotation | 100° | 100° | 100° | 100° |
| Max jib capacity | 1000 lbs. | 1000 lbs. | 1000 lbs. | 1000 lbs. |

HEIGHTS WITH STANDARD PEDESTAL

| | | | | |
|----------------------|--------|--------|--------|--------|
| Bottom of platform | 36'-0" | 40'-0" | 46'-6" | 51'-2" |
| Working height | 41'-0" | 45'-0" | 51'-6" | 56'-2" |
| Stowed travel height | 10'-6" | 10'-6" | 11'-0" | 11'-6" |

BOOM ACTION

| | | | | |
|-------------------------------|-------------|-------------|-------------|-------------|
| Outer/Inner boom articulation | -25 to +85° | -25 to +85° | -25 to +85° | -25 to +85° |
| Inner boom extension | 79" | 103" | 103" | 53" |
| Lower boom articulation | 87° | 87° | 84° | 84° |
| Rotation | 360° | 360° | 360° | 360° |

INSULATION

| | | | | |
|---------------------------|-----|-----|-----|-----|
| Upper boom insulation gap | 41" | 41" | 59" | 59" |
| Lower boom insulation gap | 12" | 12" | 12" | 12" |

VEHICLE REQUIREMENTS

| | | | | |
|-----------------------|-------------|-------------|-------------|-------------|
| Cab to axle (minimum) | 84" | 84" | 84" | 102" |
| GVWR | 17,500 lbs. | 17,500 lbs. | 17,500 lbs. | 24,000 lbs. |

NOTE:

1. Specifications may vary without prior notification.
2. Required GVWR can vary significantly with chassis, lift mounting location, service body, accessories, and desired payload.



- Auxiliary Outriggers
- Second Set of Tool Power Ports
- Lifting Eye
- Emergency Power
- Two-Speed Manual Throttle Control
- Hydraulic Jib Pole Extension
- Various Pedestal Heights

